

Cordless Rotary Hammer with SDS plus GBH 18V-26 F Professional



Technical Data

webshop-pdp-section-technical-data-table-key-Technical data

Max. impact energy	2.6 J
Impact rate at rated speed	0 – 4,350 bpm
Rated speed	0 – 980 rpm
Tool holder	SDS plus
webshop-pdp-section-technical-data-table-key- Battery and power	
Battery voltage	18 V

from GBP 358.79*

* Price including VAT

Universal rotary hammer with quick-change chuck in the SDS plus cordless category

Part number: 0 611 910 003

> More product information

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	13,0 m/s²
Uncertainty K	1,5 m/s²
Drilling in metal	
Vibration emission value ah	2,5 m/s²
Uncertainty K	1,5 m/s²
Screwdriving	
Vibration emission value ah	2,5 m/s²
Uncertainty K	1,5 m/s²
Noise	
Sound pressure level	91 dB(A)
Sound power level	102 dB(A)
Uncertainty K	3 dB



Advantages

- Optional GDE 18V-16 Professional dust extraction unit integrates with the hammer for a self-contained HEPA dust solution
- KickBack Control and Electronic Precision Control for better tool handling and increased user protection
- Delivers 2.6 J of impact energy for fast drilling and high chisel removal performance

