HIGH RESISTANCE FLOOR VARNISH

	HIGH RESISTANCE FLOOR VARNIS	н
Version: 4	Review date: 02/02/06	91/51/EC (2001/58/EC) - ISO 11014-1
1. IDENTIFICATION OF THE SU	BSTANCE/PREPARATION AND OF THE	E COMPANY/UNDERTAKING
Product name:	HIGH RESISTANCE FLOOR VARNISH	
Uses or/and applications:	wood care	
Product code nr:	140	
Supplier:	V 33 S.A. Rue Croix Bernard La Muyre F-39210 DOMBLANS CEDEX France Phone: +33 (3) 84 35 00 33 Fax: +33 (3) 84 44 63 18	
Emergency phone number (to be used by the practising doctor):	UK - National Poisons Information Service Phone: B - Centre Antipoisons Tél: 070 / 245.245	44 / 191 22 5131
2. COMPOSITION / INFORMATI	ON ON INGREDIENTS	
Preparation name:	HIGH RESISTANCE FLOOR VARNISH	
Formula:	FOVIE23	
Component(s) contributing to the hazard:	 RESINE ALKYDE Conc. wt.(%): 70 < C <= 80 - R-phrase(s): 10-66 NAPHTA LOURD PETROLE HYDROTRAITE - CAS no: *64742-48-9 Conc. wt.(%): 10 < C <= 15 - Symbol(s): Xn - R-phrase(s): 65-66 NAPHTA HYDROTRAITE PT EBU BAS - CAS no: *64742-48-9 Conc. wt.(%): 10 < C <= 15 - Symbol(s): Xn - R-phrase(s): 10-65-66 CARBOXYLATE DE COBALT(2+) - CAS no: 68409-81-4 Conc. wt.(%): 0 < C <= 1 - Symbol(s): Xn - R-phrase(s): 22-38-43 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime - Id No: 616-014-00-0 - CAS no: 96-29-7 - EC no: 202-496-6 Conc. wt.(%): 0 < C <= 1 - Classification: •Carc. Cat. 3; R40•Xn; R21•Xi; R41•R43• 	
3. HAZARDS IDENTIFICATION		
Most important hazards:	Repeated exposure may cause skin dryness or cra Flammable.	acking
Specific hazards:	Repeated and prolonged exposure may cause skir properties of the product.	n irritation and dermatitis due to degreasing
4. FIRST AID MEASURES		
General advice:	In all cases of doubt, or when symptoms persist, so Never give anything by mouth to an unconscious p For symptom description, see item 11.	
Inhalation:	Take victim to fresh air, in a quiet place, in an half advice.	laying position and if necessary take medical
Skin contact:	Remove contaminated clothing. Wash skin thoroug proprietary skin cleaner. If skin irritation persists, take medical advice.	ghly with soap and water or use a
Eye contact:	Wash with plenty of water (during 20 minutes mining soft contact lenses and immediately take medical a	
Ingestion:	Do not induce vomiting. Rinse mouth, do not drink anything, keep quiet, an	d go immediately to hospital or to a doctor.
5. FIRE-FIGHTING MEASURES Suitable extinguishing media:	dry chemical powder, alcohol-resistant foam, carbo	on dioxide (CO2), water spray, sand, earth.
Extinguishing media which must NOT be used for safety reasons:	Do not use a solid water stream as it may scatter a	

HIGH RESISTANCE FLOOR VARNISH		
Version: 4	Review date: 02/02/06	91/51/EC (2001/58/EC) - ISO 11014-1
Specific method(s):		
	Provision to contain effluent from fire extinguishin Cool closed containers exposed to fire with water	
Specific fire hazard(s):		
	Vapours are heavier than air and spread above g In case of fire, product decomposes in:: carbon or Concerning product toxicity, see item 11 and about	xides (CO and CO2) and smokes.
Special protective equipment for fire- fighters:	Use a self-contained breathing apparatus and als	so a protective suit.
6. ACCIDENTAL RELEASE ME	ASURES	
Personal precaution(s):	Evacuate personnel to a safe area. Remove all sources of ignition. Be careful to flashback of fire. Ensure adequate ventilation. Avoid contact with skin, eyes, or clothing. Concerning personal protective equipment to use	a, see item 8.
Environmental precaution(s):	Stop leak without risks if possible. Dike and contain spill. Prevent product from entering drains. Do not allow material to contaminate ground wate Concerning disposal elimination after cleaning, se	
Method(s) for cleaning up:	Scoop spilled material, and gather remainder car Soak up with absorbent material (for example sar gel). Shovel into suitable and closed container for disp Dispose as hazardous waste.	nd, sawdust, neutral absorbent granule, silica

7. HANDLING AND STORAGE

Handling	
- Precaution(s):	Vapours may form flammable mixture with air. Do not eat, drink and do not smoke in areas where product is used. Shower, eyes shower and water point in proximity. Avoid all eyes and skin contact and do not breathe vapour and mist. Wear personal protective equipment (see item 8).
- Technical condition(s):	The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid static electricity discharges. Ventilation along floor.
- Safe handling advice(s):	Opened containers must be carrefully closed and kept uprigth to avoid leakage. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Open container carefully to avoid spurting.
Storage	
- Precaution(s):	Store in a place accessible by authorised persons only. Keep container tightly closed and in a well-ventilated place.
- Technical condition(s):	Waterproof underground retention basin.
- Storage condition(s):	Keep container tightly closed and at a temperature not exceeding (°C): 50 °C Keep away from sources of ignition - No smoking. Store away from direct sunlight or other heat sources. Keep container in a well ventilated place.
 Separation of incompatible product(s): 	Keep away from: strong acids, strong bases and oxidising compounds.
- Packaging / tank material:	stainless steel, mild steel.
- Unsuitable packaging materials:	Avoid certain plastics which are soluble in product. rubbers

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measure(s):

Ensure adequate ventilation, especially in confined areas. Ensure adequate ventilation, especially in confined areas.

HIGH RESISTANCE FLOOR VARNISH

Control parameter(s):	
- Exposure limit(s):	
Personal protection equipment:	
- Respiratory protection:	In case of insufficient ventilation wear suitable respiratory equipment. (breathing apparatus with filter A)
- Hand protection:	nitrile rubber gloves
- Skin and body protection:	solvent-resistant apron and boots
- Eye protection:	safety glasses or face shield
Hygiene measure(s):	Do not eat, drink, or smoke during work. Keep away from food, drink and animal feed. Keep workplace clean and tidy as much as possible.
9. PHYSICAL AND CHEMIC General information	CAL PROPERTIES
- Physical state / form:	liquid
- Colour:	various
Odour	characteristic

9. F

General information

 Physical state / form: 	liquid
- Colour:	various
- Odour:	characteristic
Important health,safety and environmental information	
- PH:	Not applicable.
- Boiling point/range:	155-200°C
- Flash point:	38° C
- Explosion limits:	0.6 % (V/V) < vapours < 6.5 % (V/V)
- Relative density (water = 1):	0.8 <d<0.9< th=""></d<0.9<>
- Viscosity:	Not determined.
- Water solubility:	immiscible
- Fat solubility:	partly soluble
- Solvent solubility:	soluble in most organic solvents
10. STABILITY AND REACT	Ίνιτγ
Stability:	Stable in use and storage conditions as recommended in item 7.

Stability:	Stable in use and storage conditions as recommended in item 7.
Condition(s) to avoid:	None under normal use.
Material(s) to avoid:	Avoid certain plastics which are soluble in product.
Hazardous decomposition products:	Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide

11. TOXICOLOGICAL INFORMATION

Acute toxicity	
- Inhalation:	Irritating to the respiratory system, may cause throat pain and cough. Inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
- Skin contact:	Components of the product may be absorbed into the body through the skin. Frequent or prolonged contacts may defat and dry the skin, leading to discomfort and dermatitis.
- Eyes contact:	Liquid splashes in the eye may cause irritation. (pain, redness)
- Ingestion:	May cause gastrointestinal irritation, nausea, vomiting and diarrhoea. Susceptible to induce: oedema of the lungs, heavy breathing difficulty, dizziness.
Specific effect(s):	Use of alcoholic beverages may enhance toxic effects.

12. ECOLOGICAL INFORMATION

Review date: 02/02/06

HIGH RESISTANCE FLOOR VARNISH

	HIGH RESISTANCE FLOOR VARNISH	
Version: 4	Review date: 02/02/06	91/51/EC (2001/58/EC) - ISO 11014-1
General information(s):	There is no data quailable on the product itself	
	There is no data available on the product itself.	
Persistence and degradability:	Product has only a limited biodegradability in soil and	d water.
Environmental toxicity:	This substance may be hazardous to the environme	nt.
Otheradverse effects		
13. DISPOSAL CONSIDERAT	TIONS	
Waste / unused products:		
	Collect all waste in suitable and labelled containers a Can be recycled. Do not dispose of waste into sewer. Destruction by incineration / pyrolyse. . 02	and dispose according to local legislation.
Contaminated packaging:	Do not burn, or use a cutting torch on the empty drur Dirty containers cannot be handle as normal waste.	m.
Further Information(s):		
14. TRANSPORT INFORMAT	ION	
General information(s):	Transport followed ADR, IMDG, IATA	
UN N°:	1263	
Land (Road / Railway: ADR/RID)		
- Class:	3	
- Verpakkingsgroep: Sea (IMDG)	III	
- Class: Air (ICAO/IATA)	3	
15. REGULATORY INFORMA	TION	
Labelling:	According to european directives on classification, p substances 67/548/ EC. Using the calculation metho	
EC number:	Not applicable.	
Symbol(s):	None according to EC directives.	
R-phrase(s):	10 Flammable. 66 Repeated exposure may cause skin dryness or o	cracking
S-phrase(s):	 Keep out of the reach of children. Do not empty into drains. Use only in well-ventilated areas. If swallowed, do not induce vomiting: seek medic container or label. 	cal advice immediately and show this
Further information(s):	Contains CARBOXYLATE DE COBALT(2+), 2-butar methyl ketone oxime. May produce an allergic react	
16. OTHER INFORMATION		
According legislation(s):	This safety data sheet is in compliance with directive	es and adaptings: 91/155, 67/548, 88/379
Important remarks:	Information in this safety data sheet is based on actue experience. It is recommended to pass the information of this saft appropriated form, to the users.	
Uses or/and applications:	wood care	

HIGH RESISTANCE FLOOR VARNISH

Version: 4	Review date: 02/02/06	91/51/EC (2001/58/EC) - ISO 11014-1
Restrictions:		
	This information relates to the specific material designated and may not be valid in combination with other product(s).	
History		
- First edition date:	12/03/97	
- Previous revision date:	09/09/02	
- Review date:	02/02/06	
- Version:	4	
- Review chapter(s) n°:	16	
Written by:	V33	

This document was created with Win2PDF available at http://www.daneprairie.com. The unregistered version of Win2PDF is for evaluation or non-commercial use only.