

SPHERE

An exceptional field of vision of 180°. The easy to rise headgear and brow guard are adjustable for both height and depth and the SPHERE adapts itself to any situation for any use.



355 g



SPHERPI



FASPHERI






+ ULTRA ENVELOPING 20,5 CM X 39,4 CM X 0,18 CM

+ ADJUSTABLE HEADGEAR AND BROW GUARD

+ PC VISOR

bolle
SAFETY

SPHERE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SPHERE	 Polycarbonate	SPHERPI	2C-1,2  1 BT 8 9 C€	 EN166 8 3 9 BT C€	-
	 Polycarbonate	FASPI	2C-1.2  1 BT 8 9 C€	-	-

LENS MARKING

Optical class symbols:

1. Continuous work

Use symbols:

8. Electrical short circuit arc

9. Molten metal and hot solids

Mechanical strength symbols:

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

C€ European standard  Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.


3. Liquid droplets or splashes.

8. Electrical short circuit arc

9. Molten metal and hot solids

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN 13 CODE		
	SPHERPI	FASPI
Individual packaging	3660740001186	3660740001193
5 face shields per outer pack - 50 spare lenses per outer pack	3660740201180	3660740201197

CHARACTERISTICS	
LENSES	PC - 2.0 mm
FRAME	PP
TEMPLES	Non applicable
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	FASPI



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY