


# SQUALE

## OTG

SQUALE OTG provide excellent protection for wearers of prescription glasses.



SQUPSI



SQUPSJ



SQUWPCC5



43 g

SUPPLIED WITH

Cord  
CORD












- + UPPER PROTECTION
- + ADJUSTABLE TEMPLES
- + LOWER PROTECTION

**bolle**  
SAFETY

# SQUALE

OTG

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SQUALE	 Clear	SQUPSI	2C-1,2  1 FT €€	 EN166 FT €€	Anti-scratch/anti-fog
	 Yellow	SQUPSJ	2C-1,2  1 FT €€	 EN166 FT €€	Anti-scratch/anti-fog
	 Welding shade 5	SQUWPCC5	5  1 S €€	 EN166 S €€	Anti-scratch

## LENS MARKING

### Optical class symbols:

1. Continuous work

### Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s

### Others symbols:

€€ European standard  Manufacturer name

## FRAME MARKING


**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s

€€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE			
	SQUPSI	SQUPSJ	SQUWPCC5
Individual plastic bag	3660740003203	3660740003517	3660740002343
10 safety spectacles per inner box	3660740103200	3660740103514	3660740102340
180 safety spectacles per outer pack	3660740203207	3660740203511	3660740202347

CHARACTERISTICS	
LENSES	PC - 2,0 mm - Curve 4
FRAME	PC
TEMPLES	PC + Nylon
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



01/10/2013

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

bolle-safety.com

**bolle**  
SAFETY