# CONTOUR LIGHTWEIGHT AND EFFECTIVE

21 g of strength: sturdy, protective, stylish, comfortable and lightweight. CONTOUR is one of the top three best-selling models.











CONTPOL

- + ADJUSTABLE NON-SLIP BRIDGE
- **+** NON-SLIP TIPGRIP TEMPLES
- + ANTI-STATIC



# CONTOUR LIGHTWEIGHT AND EFFECTIVE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
CONTOUR	Clear	CONTPSI	2C-1,2 😭 1 KN FT C€	<b>≅</b> EN166 FT <b>C€</b>	Anti-scratch/anti-fog(*?)
	Smoke	CONTPSF	5-2,5 😭 1 KN FT C€	<b>≅</b> EN166 FT <b>C€</b>	Anti-scratch/anti-fog(*?)
	ESP	CONTESP	5-1,4 😭 1 FT C€	<b>≅</b> EN166 FT <b>C€</b>	Anti-scratch
	Polarized	CONTPOL	5-2,5 😭 1 FT C€	<b>≅</b> EN166 FT C€	Anti-scratch

# LENS MARKING

### Optical class symbols:

1. Continuous work

### Mechanical strength symbols:

- **F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

# Others symbols:

- K. Resistance to surface damage by fine particles (optional)
- N. Resistance to fogging (optional)

# TECHNOLOGY

## **∠**ESP

ESP, Extra Sensory Perception.
An innovative coating to reduce dazzle and the harmful affects of blue light.
B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

# **b**POLARIZED

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB.

# \$PL/TINUM

This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes. In all circumstances and at all times the PLATINUM lens innovation guarantees your eyes improved protection.

PACKAGING AND EAN13 CODE							
	CONTPSI	CONTESP	CONTPSF	CONTPOL			
Individual plastic bag	3660740003241	3660740003258	3660740003388	3660740000615			
10 safety spectacles per inner box	3660740103248	3660740103255	3660740103385	3660740100612			
240 safety spectacles per	3660740203245	3660740203252	3660740203382	3660740200619			

# FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for spectacles.
- **T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- K. Resistance to surface damage by fine particles (optional)
- N. Resistance to fogging (optional)

Bollé Safety product approval certificates to CE standards will be sent on request.

# CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly with a mild soap detergent or optical solution.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS				
PC - 2,2 mm - Curve 8				
PC				
Nylon + TPE				
Non applicable				
Non applicable				











01/10/2013

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

