

CONTOUR METAL

STYLISH AND EFFECTIVE

METAL version Contour: success guaranteed!



CONTMPSI



CONTMPSF



CONTMESP



38 g

SUPPLIED WITH

Microfibre pouch
ETUIFS












- + INCREASED UPPER PROTECTION**
- + NON-SLIP TIPGRIP TEMPLES**
- + 160% FLEX TEMPLES**
- + NON-SLIPB RIDGE**
- + ANTI-STATIC**

bolle
SAFETY

CONTOUR METAL

STYLISH AND EFFECTIVE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
CONTOUR MÉTAL	 Clear	CONTMPSI	2C-1,2  1 FT C€	 EN166 FT C€	Anti-scratch/anti-fog
	 Smoke	CONTMPSF	5-3,1  1 FT C€	 EN166 FT C€	Anti-scratch/anti-fog
	 ESP	CONTMESP	5-1,4  1 FT C€	 EN166 FT C€	Anti-scratch

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol,
authorises use for high speed particles at extreme temperatures.

Others symbols:


C€ European standard  Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

B-ESP

ESP, Extra Sensory Perception.
An innovative coating to reduce dazzle and the harmful affects of blue light.
B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE			
	CONTMPSI	CONTMPSF	CONTMESP
Individual plastic bag	3660740003777	3660740003784	3660740003791
10 safety spectacles per inner box	3660740103774	3660740103781	3660740103798
240 safety spectacles per outer pack	3660740203771	3660740203788	3660740203795

CHARACTERISTICS	
LENSES	PC - 2,3 mm - Curve 9,25
FRAME	Metal nickel free
TEMPLES	Metal nickel free + TPE
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY