PRISN HIGH DURABILITY

Thanks to its durable PC frame, the PRISM model offers excellent protection and is great value for money.





PRIPSI



PRIPSF



Adjustable cord CORDC



+ UPPER PROTECTION

+ SPORTYD ESIGN

+ COMFORTABLE, STRAIGHT TEMPLES



PRISN HIGH DURABILITY

| MODEL | VERSIONS | REFERENCES | LENS MARKING | FRAME MARKING | COATINGS |
|-------|----------|------------|------------------|-----------------------|-----------------------|
| DDICM | Clear | PRIPSI | 2C-1,2 🗁 1 FT CC | 🗁 EN166 FT с є | Anti-scratch/anti-fog |
| PRISM | Smoke | PRIPSF | 5-2,5 🗁 1 FT C€ | 🗁 EN166 FT C € | Anti-scratch/anti-fog |

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

CE European standard 🗁 Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- **T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard ☐ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

| CHARACTERISTICS | | | | |
|-----------------|------------------------|--|--|--|
| LENSES | PC - 2,25 mm - Curve 9 | | | |
| FRAME | PC | | | |
| TEMPLES | PC | | | |
| STRAP | Non applicable | | | |
| FOAM | Non applicable | | | |
| SPARE LENSES | No | | | |

| PACKAGING AND EAN13 CODE | | | | | |
|--|---------------|---------------|--|--|--|
| | PRIPSI | PRIPSF | | | |
| Individual plastic bag | 3660740003463 | 3660740003470 | | | |
| 10 safety spectacles per inner box | 3660740103460 | 3660740103477 | | | |
| 300 safety spectacles per outer pack | 3660740203467 | 3660740203474 | | | |



Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél. : 00 33 (0) 4 78 85 23 64 Fax : 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY Tél. : 00 44 (0)208 391 4700 Fax : 00 44 (0)208 391 4733 e-mail : sales@bolle-safety.co.uk 01/10/2013



