## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Kingfisher International Products B.V.

**Supplier's address:** Product quality, Kingfisher International Products B.V. Rapenburgerstraat 175E 1011 VM Amsterdam The Netherlands

Model identifier: 3663602668459

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	E14,220-240V~50Hz				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the neares	0 h), rounded	8	Energy efficiency class	F		
Useful luminous indicating if it re in a sphere (36 cone (120º) or in (90º)	fers to the flux 0°), in a wide	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode po expressed in W	ower (P <sub>on</sub> ),	8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked stand for CLS, express rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	86	Spectral power	See image		
dimensions	Width	50	distribution in the	in last page		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	50	range 250 nm to 800 nm, at full-load				
Claim of equival	lent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
			Chromaticity coordinates (x and y)	0,458			
Parameters for LED and OLED light sources:							
R9 colour rende	ring index value	0	Survival factor	0,90			
the lumen main	tenance factor	0,93					
Parameters for LED and OLED mains light sources:							
displacement fa	ctor (cos φ1)	0,00	Colour consistency in McAdam ellipses	0			
source replaces	an LED light s a fluorescent hout integrated icular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (P	Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)'-' : not applicable;

(b)'-' : not applicable;

