Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Kingfisher International Products B.V.

Supplier's address: Product quality, Kingfisher International Products B.V., Rapenburgerstraat 175E, 1011 VM Amsterdam, The Netherlands

Model identifier: 3663602669265

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	R7S				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in or mode (kWh/1000 h), rounde up to the nearest integer		Energy efficiency class	D		
Useful luminous flux (duse indicating if it refers to the flu in a sphere (360°), in a wid cone (120°) or in a narrow con (90°)	Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on} expressed in W	, 17,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{ne} for CLS, expressed in W an rounded to the second decima	k	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer Height	118	Spectral power	See image		
dimensions Width	28	distribution in the	in last page		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	28	range 250 nm to 800 nm, at full-load			
Claim of equival	ent power ^(a)	-	lf yes, equivalent power (W)	-		
			Chromaticity coordinates (x and y)	0,440		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	0	Survival factor	0,90		
the lumen main	tenance factor	0,93				
Parameters for LED and OLED mains light sources:						
displacement fa	ctor (cos φ1)	0,00	Colour consistency in McAdam ellipses	0		
source replaces	an LED light a fluorescent hout integrated icular wattage.	_(b)	lf yes then replacement claim (W)	-		
Flicker metric (P	st LM)	0,0	Stroboscopic effect metric (SVM)	0,0		

(a)'-' : not applicable;

(b)'-' : not applicable;

