




German quality German engineering

PLANT PROTECTION AND LANDSCAPE MANAGEMENT Sprayers. Misters. Blowers. Granulate spreaders.

SOLO – Pioneers of mobile plant protection technology



Four tips to help you choose the right product

1

Pressure sprayer or backpack sprayer?

The answer to this question often depends on the size of the area to be treated. If it's on the small side, a pressure sprayer with shoulder strap will suffice. For larger areas, backpack sprayers are more suitable as they are comfortable to carry and have a larger capacity. All that is left to decide is whether you want to operate the pump manually or let a battery or petrol driven unit do the work for you.



Tall plants?

If you need to treat tall plants, you should use extension wands. They will help you reach the right places and apply the medium more accurately. As well as being made of plastic material, spray wands are also available in robust brass or even ultra-light carbon. The telescopic carbon spray wand, which can be extended up to 230 cm, weighs just 160 g. This protects the operator's joints even during longer working periods.

3,

Liquid or solid?

All SOLO sprayers are designed for applying liquid media. However, the nozzles vary depending on the application: flat spray nozzles for ground spraying, hollow cone nozzles for individual plants, insecticides and fungicides. Herbicides are best applied with deflector nozzles. With solid granulate, SOLO 421 is the product of choice. It distributes the medium evenly over the required area – and can also be used in winter to apply gritting salt to pathways. 4

When to use a mister rather than a sprayer? In large scale agricultural plantings, orchards, horticulture, vineyards and in many other cultivated plant stocks around the world, it is crucial for the media to successfully reach and penetrate the crops. SOLO power misters are designed to accomplish precisely this. They generate a powerful air flow which splits the plant protection spray medium into a fine mist to effectively cover all the required parts of the plant.

SOLO CLASSIC SOLO COMFORT SOLO PRO

Whether you're an occasional user, a discerning private user or a professional, you're guaranteed to find the right product to suit your requirements in one of our three equipment lines.

It goes without saying that our CLASSIC sprayers are also of the same high quality you would expect from all SOLO products. The differences are found in the equipment features and ease of use. All backpack sprayers in the COMFORT series and above are fitted as standard with FKM seals ("Viton[®]") in all the important places. Moreover, the PRO backpack sprayers feature a lightweight, telescopic spray wand and are especially comfortable to wear, preventing tiredness even after prolonged periods of use.

Three battery-operated sprayers, one power sprayer and three power misters are low in weight and boast a powerful output. Whether they use electric motors, 2-stroke SOLO engines or 4-stroke Honda engines, these tools combine high levels of performance and top quality. In addition to sprayers and misters, the PRO series also features the 421 granulate spreader and the new 468 backpack blower.

SOLO – the right choice for any application

Sample applications for SOLO sprayers and misters			408	401	461	456	424/425/435	425	475	425	441	433	423
4				402	462	457	473D/475	Comfort	Comfort	PRO	442		452
			453			458	Classic				417 416 Li		
	Plants on balconies and patios	•		•							41011		
-	Private gardens, decorative plants, shrubs				•		•	•	•				
tior	Large private gardens, decorative plants, shrubs, plantings				•		•	٠	•				
otec	Large private gardens, decorative plants, shrubs, plantings Professional horticulture and landscaping, greenhouses Espaliered trees, trees High trees						•	•	•				
t pre	Espaliered trees, trees						•	٠	•	٠	٠		
lant	High trees											•*	
₽.	Weed control				٠		•	٠	•	٠			
	Agricultural crops in general							٠	•	٠	٠		
re	e Large scale plantings, such as orchards, vineyards, plantations and horticultural operations												
Agriculture	Plant protection					٠		•	•	•			
Jrice	Disinfection												
Αĝ	Pest control												
lland nance	Plant care								•	•	•		
Plant care Plant care Protection against game attack									•	•			
									i i	With s	uitable	e acces	sorie
			\$			-1		?		With s	suitable	e ao	cces

Care for and fertilise lawns

Herbicides

Care for and fertilise plants

Fertilisers

Eliminate viruses and bacteria

Disinfectant

Are you looking for a sprayer or foam sprayer that is specially designed for cleaning agents and disinfectants? Then ask about our **CLEANLine** sprayers.

ecticides

Eliminate pests

Where can you find what you need in this catalogue?

Fungicides

Eliminate fungi

Manual sprayers	04
Pressure sprayers	08
Trolley sprayers	08
Backpack sprayers	12
Battery-operated pressure sprayer	16
Power sprayers	22
Misters	24
Granulate spreaders	28
Blower	29

Specification	30
Spray wand accessories	32
Nozzle accessories	34
Accessories for sets of seals	35
Other accessories	36
Accessories for power sprayers	37
Accessories for misters	38
Two-stroke oil and mixing container	39
Batteries and chargers	39





MANUAL SPRAYERS

Manual sprayers are an inexpensive and indispensable aid for a variety of applications around the home. Plants on balconies and patios, and of course decorative indoor plants too, are easy to look after with these compact devices. Robust pumps reach the required operating pressure after just a few strokes. Once the pressure is reached, you can apply almost the entire content without additional pumping. The integral safety valve protects the appliance against excess pressure build-up. The high quality hollow cone nozzle is fully adjustable – from a direct jet to the finest mist. The robust tanks have a large filling aperture to prevent spills when being filled and emptied. Their stable base stops them overturning when full. The underside of leaves can be optimally treated with the 401 and 402 models: the pivoting nozzle and small drift guard ensure the spray medium is only applied where actually needed.



MANUAL SPRAYERS



MANUAL SPRAYERS

SOLO 403

Inexpensive manual pressure sprayer with nominal capacity of 1.25 l. For plant protection and care inside the house, on patios, balconies or in conservatories. 1.25 l, 2 bar, 0.5 kg Part no. 40301



SOLO 404

As per SOLO 403, but with nominal capacity of 2 I. 2.0 l, 2 bar, 0.6 kg Part no. 40401





SOLO 460Li

Forget manual pumping! Practical and inexpensive battery-operated sprayer incl. USB charging cable with 1 I nominal capacity and 2 bar pressure. For plant protection and care inside the house, on patios, balconies or





solo

Greater reach:

For the two manual sprayers in the Comfort line, SOLO 401 and 402, a practical accessory is available in the form of a telescopic wand (49628), which can be extended from 25 to 50 cm as required. The telescopic function improves access to parts of plants that are further away or otherwise hard to reach. For example, the nozzle head can be pivoted through 180°, making it convenient and effective to treat the underside of affected leaves.







PRESSURE SPRAYERS

SOLO pressure sprayers with shoulder strap have long been popular and reliable aids in private gardens or for countryside management. They do not take up much storage space and are ready for immediate use whenever required. Various tank volumes are available, depending on the size of the garden. The 5-litre model is the most popular for garden applications. For larger areas, seven or eleven litres may be preferable.

The intensity of use also plays an important role, of course. Occasional users have the choice between the 408 and 409 entry level models, and the 461 or 462 all-rounders from the Comfort line. Use the convenient mobile 453 trolley sprayer to cover longer distances with ease between spray locations. If the terrain is fairly rugged and the application of a more professional nature, such as in horticulture and landscaping, or in agriculture and forestry, we recommend the 456, 457 or 458 professional pressure sprayers. The tanks are some of the most robust on the market thanks to their wall thickness. Even an accidental tumble from their storage area or similar tough tests are no problem for these professional pressure sprayers.

With resistance to UV rays, the transparent tanks are all set for a long service life. Comprehensive accessories, such as extension wands, drift guards and different nozzles for a variety of applications make the SOLO pressure sprayers even more versatile to use.



PRESSURE SPRAYERS



01 High quality nozzles (408/409 adjustable universal nozzle)



Flexible spray wand for the toughest mechanical applications




Spray wand retainer; two clips for the 456-458: for plastic and brass spray wands

Removable top section with large aperture to facilitate filling, draining and cleaning

05 Safety valve automatically compensates in the case of excess pressure inside the tank

06 Long, broad, practical strap

04



09

08 Sturdy reinforced hose with ergonomic handle

Transparent pressure sprayer tank for good visibility of the spray medium level, made from polyethylene with UV resistance

PRESSURE SPRAYERS



SOLO 458

As per SOLO 456, but with nominal capacity of 11 I and stable base Piston pump, 11 l, 2.9 kg Part no. 45802



Accessories: Practical wheel set, comprising large, high traction wheels incl. axle and a handle for easy tilting and movement. Part no. 49211

5010

SOLO 456

The cream of the crop amongst pressure sprayers, with top performance even in tough, continuous use.

Extremely stable 5 I tank, unbreakable 50 cm plastic spray wand and SOLO flat spray and hollow cone nozzle. Piston pump, 5 l, 2.6 kg Part no. 45601



SOLO 457

As per SOLO 456, but with nominal capacity of 7 l. Piston pump, 7 l, 2.8 kg Part no. 45701



Optional accessories: compressed air supply valve to build pressure without having to pump manually. Part no. 49590







BACKPACK SPRAYERS

When it comes to plastic backpack sprayers, we have decades of experience, having started producing full plastic sprayers back in 1960.

The lightness of the material on the one hand and its durability on the other are just two good reasons to choose SOLO backpack sprayers.

Starting with the Comfort models, the backpack sprayers are also equipped with highly resistant FKM seals ("Viton[®]") for applying aggressive liquids. There are four pressure settings so you can apply precise quantities.

With abrasive fluids, the 473 D and 475 sprayer models with diaphragm pump are the ideal choice. The special Tivilon[®] diaphragm in their pumps is highly resistant.

With either piston or diaphragm, the pumps in the SOLO backpack sprayers are

some of the most effortless and efficient on the market. Longer operating times are therefore simple to achieve, thanks also to the exceptional straps, inspired by the outdoor sports sector on the 425 PRO models. Comfortable and padded, they can be adjusted in various ways for a perfect fit – also available as accessories.

The UV-resistant tanks come in four sizes: 10, 15, 16 or 20 litres. They are translucent so the fill level is easily visible. The tank is filled and drained through a large filler neck.

For convenient transport, the Comfort and Pro models with 15-litre tank feature a carrying handle with built-in spray wand retainer.

See page 32 onwards for our extensive range of accessories. These can be used to further extend the application options of these highly resilient sprayers.





BACKPACK SPRAYERS



04 Large filling and cleaning aperture

14

for all permissible spray liquids (Comfort/Pro)

BACKPACK SPRAYERS

SOLO NOVA 424

Inexpensive. Practical. Unique. Sophisticated. Four attributes that best describe the new SOLO NOVA 424 backpack sprayer. Pump lever can be fitted on the right or left side. **16 I, 5.1 kg, 4 bar Part no. 42422**



SOLO 473D CLASSIC

Sprayer with nominal capacity of 10 l and diaphragm pump for applying abrasive fluids. Pump lever can be fitted on the right or left side.

Diaphragm pump, 10 l, 4.2 kg Part no. 47321



SOLO 475 COMFORT

The diaphragm pump model is generally used in conjunction with relatively viscous herbicides in the low pressure range. Diaphragm pump, 15 l, 4.7 kg Part no. 47531



SOLO 425 CLASSIC

A true all-rounder, proven millions of times over, for plant protection applications. Simple, easy to service and robust design. Pump lever can be fitted on the right or left side. Piston pump, 15 l, 4.4 kg Part no. 42521



SOLO 475 CLASSIC

A classic with nominal capacity of 15 l and diaphragm pump. For abrasive fluids. Diaphragm pump, 15 l, 4.6 kg Part no. 47521



SOLO 425 PRO

The ultimate backpack sprayer. Professional carrying system, telescopic spray wand with high quality brass nozzles and pressure gauge are standard features with this model. Piston pump, 15 I, 5.2 kg Part no. 42541



SOLO 425 COMFORT



Backpack sprayers don't come better than this

The SOLO 425 PRO professional model, with its premium features, is designed specifically for professional users. Those who work long hours with a backpack sprayer on a daily basis will appreciate the comfortable and fully adjustable backpack carrying system, inspired by the outdoor sports sector, which has been optimised for maximum user comfort.

The spray wand and nozzles of this sprayer also meet the needs of professionals: the ultra-light telescopic carbon spray wand can be adjusted between 50 cm and 90 cm. Standard delivery includes high quality brass nozzles: flat spray and hollow cone (adjustable).







BATTERY-OPERATED SPRAYERS

The battery-operated sprayers from SOLO are whisper-quiet and free of emissions. With their powerful electric drives, they are the ideal choice when it comes to plant protection in enclosed spaces with large areas requiring treatment. Efficient working practices and high performance are called for in conservatories and greenhouses, too. Of course, these battery-operated sprayers also perform well outdoors. With one press of the Power button, the powerful pump is barely noticeable but for a quiet humming sound.

The entry level battery-operated sprayer is the new SOLO 441, which is based on the current design line as seen in the NOVA 424. The SOLO 441 is the right choice for occasional work in the garden or in enclosed spaces.

The new 442 extends the concept of the 441 with further interesting features, such

as 4 pressure settings from 1-4 bar (see next page). The 416 Li and 417 models offer a higher equipment level and greater comfort. Two power settings are available to the user and the standard pressure gauge helps you apply the correct quantity. Even at the second power setting, the sound emissions are hardly any more audible. This ensures a pleasant working environment without the need for ear protectors. These two power settings regulate the pressure range of the powerful 12 V pumps to up to 4.3 bar. When the battery runs out, it can be quickly recharged inside the appliance.

Compared to the lead gel battery in the 417, the 416 Li has a lithium-ion battery, and a capacity of 20 rather than 18 litres. Last but not least, the sprayers include a lightweight, 50 to 90 cm telescopic wand made from carbon.



SOLO's new battery-operated sprayer technology in the COMFORT class

-111

The SOLO 442 battery-operated backpack sprayer for professional plant protection combines user comfort with modern battery technology. The microcontroller of the digital control system regulates the selected pressure by active, calibrated pressure measurement. This ensures a highly efficient and precise application of the spray medium, regardless of the nozzle used. An extensive range of accessories makes the sprayer even more versatile to use.



The light, compact, powerful 18 V battery is housed in the base, making it easy to remove. You can work for up to 3.4 hours with one battery charge. The supplied charger ensures the battery is full in just a fraction over an hour. For even longer working periods and shorter charging times, an express charger and a 5.0 Ah battery are available as accessories (see page 39).


The pump pressure can be set to one of four

The 16-litre tank is ergonomically shaped to the body and together with the adjustable, padded carrying system, ensures fatigue-free operation even during long periods of use. The stable base ensures a secure position on uneven and sloping surfaces. It also safely houses the nozzle when the spray wand is in the retainer for transport or storage.



BATTERY-OPERATED SPRAYERS





- 1 1.5 In long reinforced hose
- 02 Robust manual valve with vibrationdampened pressure gauge
- 03 Seals resistant to all approved spray liquids
- 04 Large filling and cleaning aperture (with quick-action closure on the 416 Li)
- 05 Integrated tank fill level scale
- 06 Ergonomically shaped tank made from UV-resistant plastic material with comfortable padded backpack frame, wide shoulder straps and waist strap (416 Li)
- 07 Almost unbreakable plastic spray wand or carbon telescopic spray wand (416 Li)
- **08** Robust electric pump in impact-resistant enclosure; two settings for pressure and spray volume
- **09** Flat spray nozzle 03-F80, compliant with ISO standard (with ball valve filter for the 416 Li)
- 10 Powerful, maintenance-free, lithium-ion battery with high quality brand-name cells (model 417: lead gel battery)

BATTERY-OPERATED SPRAYERS

SOLO 441

The entry level model for battery-operated plant protection equipment. The dry weight is a mere 3.7 kg. Rechargeable lithium-ion battery for up to 170 minutes of continuous operation and just two hours' charging time. The powerful and durable electric pump delivers 2.5 bar operating pressure. The 16 l tank and base are designed to suit the anatomy of the human spine. Lithium-ion battery 11.1 V/2.5 Ah, 16 l, 3.8 kg Part no. 44101



SOLO 417

The powerful lead gel battery in the SOLO 417 provides up to 3.7 hours of operation and takes 8 hours to recharge. The lightweight, transparent plastic tank can hold 18 l. A 50 cm plastic spray wand with high quality nozzle and pressure gauge are included as standard. Lead gel battery 12 V/7.2 Ah, 18 l, 7.6 kg Part no. 41701

SOLO 416 Li

For professional use in commercial nurseries and greenhouses, or for everyday horticulture and landscaping tasks. The powerful lithium-ion battery ensures up to 5.9 hours of continuous operation and recharges in just 5.5 hours.

Additional features of the 416 Li:

- + Heavy duty lithium-ion battery with up to 5.9 h runtime
- + Large tank lid with quick-acting closure + Removable stainless steel filling
- strainer + 50 - 90 cm telescopic carbon spray
- wand + Space saving vertical spray wand
- retainer

+ Low inherent weight Lithium-ion battery 11.1 V/7.8 Ah, 20 l, 5.2 kg Part no. 41601



Expand your application options with matching accessories from SOLO Reach tall plants with ease using an longer spray wand – available in plastic, brass or even ultra-lightweight carbon versions. The latter has a reach of up to 230 cm. Choosing the right nozzle is also important. The flat spray nozzle is the first choice for treating large areas, whereas herbicide can be applied with pinpoint accuracy using deflector or full cone nozzles, plus drift guards to prevent the media drifting into adjacent areas. Detailed descriptions of SOLO's comprehensive range of accessories can be found from page 32 onwards.

Variable spray pattern with the universal spray wand A broader spray angle with small droplets, or concentrated with a longer distribution distance: you will need one or the other – or a stage somewhere in between – depending on the application range. No problem with the universal spray wand, available as an accessory. The nozzle can be infinitely adjusted with pinpoint accuracy. The standard delivery includes two different diameters, allowing you to work even more precisely and apply the spray media more accurately. 

POWER SPRAYER

Our 433 power sprayer is characterised by its high efficiency over larger areas. This combination is applicable for very tall plantings such as trees and large shrubs, areas containing crops, or in professional horticulture and landscaping. The power is supplied by a 4-stroke HONDA engine, which has special bearings to protect against vibrations, as well as being easy to start and simple to service. The controllable operating pressure of the push-pull piston pump reaches up to 30 bar. Long working stretches without refilling are ensured by the nominal capacity of 20 litres.

01

A practical drain connector underneath the tank enables complete draining of any leftover liquid. The SOLO 433 is equipped with a 50 cm stainless steel spray wand and a pressure gauge on the sturdy manual valve, which allows the pressure to be adjusted for any application. Supplied with a high quality twin nozzle, with stainless steel nozzle discs. With the right accessories (see page 37), you can discover the versatility and all the advantages of this power sprayer. For example, increase the reach with the proper spray wand. Or adjust the spray pattern with the universal spray wand.

SOLO 433 4-stroke HONDA engine, 25 cm³ Stainless steel spray wand with twin nozzle 02 and pressure gauge 20 l, 9.8 kg Part no. 43303 03 05 04 07 08 POWERED by HONDA Robust manual valve with silicone-dampened Twin nozzle 06

- 50 cm stainless steel spray wand
- 03 Large filling and cleaning aperture
- 04 Spray wand retainer

06

09

01

02

- Ergonomically designed tank made from 05 transparent, UV-resistant plastic material with comfortable, padded backpack frame and wide shoulder straps
- pressure gauge. Hose connection with swivel coupling for flexible operation.
- 07 Powerful 4-stroke HONDA engine
- 08 Anti-vibration dampers
- Long high pressure hose for stress-free 09 arm movements



MISTERS



SOLO misters are amongst the most popular in the world. They are right at home and have become indispensable in agriculture, horticulture, woodland maintenance, public parks and green areas, amongst fruit and vine growers and in coffee and cocoa plantations in Africa and South America. The success of SOLO misters is based on their high spray performance combined with low weight. These characteristics make them the environmentally responsible choice for the economical protection of all crops and plantings anywhere in the world. Furthermore, SOLO misters are remarkably robust and easy to handle. Thanks to all these benefits, they have been helping to bring about high yields around the globe for many years. In this, advanced engine technology from SOLO ensures


low fuel consumption, reduced exhaust gas emissions and high performance over long periods – even under adverse warm conditions.

In addition to plant protection, these sprayers can also be used for disinfection and parasite control in the fields of logistics, agriculture and animal husbandry. The range of accessories (see page 38) makes both SOLO misters – the new, inexpensive MASTER 452 and the powerful, proven PORT 423 – even more versatile. For example, a dusting attachment turns the PORT 423 into a brilliant dusting machine. A liquid booster pump ensures uniform application when spraying upwards and when using longer spray wands. The practical twin nozzle makes it possible to treat two rows at the same time.





MISTERS



MISTERS

Solo Master 452 (121)

Powerful mister with quiet 66.5 cm³ 2-stroke SOLO engine. Advanced engine technology ensures low noise and exhaust gas emissions.

A diaphragm carburettor and comfortable backpack carrying system ensure optimum working conditions. One of the lightest and most compact in its class worldwide.

66.5 cm³, 2.1 kW/2.9 hp, 1400 m³/h, 12 l, 9.7 kg Part no. 45201 (not available in the EU) Part no. 45203 (EU)



Solo Master 452 (151)


As per the 45201, but with 15 I tank capacity. 66.5 cm³, 2.1 kW/2.9 hp, 1400 m³/h, 15 l, 9.7 kg Part no. 45202 (not available in the EU)



SOLO PORT 423

Throughout the world, the SOLO PORT 423 is the epitome of a robust and reliable mister. The powerful 72.3 cm³ 2-stroke SOLO engine delivers 3 kW. This durable mister has proven easy to service over many years.

72.3 cm3, 3.0 kW/4.1 hp, 1400 m3/h, 10 l, 11 kg Part no. 42311 (not available in the EU)



The standard delivery includes a long reach nozzle as well as a wide spray grille and a nozzle with interchangeable deflectors.

The long reach nozzle directs the spray medium over a distance of up to 12 metres (PORT 423). The spray width increases with the wide spray grille. The nozzle with single sided deflector makes it easier to spray rows of crops and also enables you to reach underneath leaves. The double sided deflector allows you to efficiently treat two rows at a time.





GRANULATE SPREADERS



Seed, fertiliser, e.g. after scarifying, gritting salt, oil absorbers, cleaning agents, pelletised lime, bird seed, stock feed, sand ... The SOLO granulate spreader 421 is designed to be used all year round.

A manual crank drives the rotating spreader disc to guarantee precise distribution of the granulate onto the area to be treated. The integral agitator ensures that the material in the tank is mixed thoroughly. Up to 9 litres of granulated matter can be applied where specifically required, even on difficult terrain – for example where a wheeled appliance would be unsuitable. The direction in which the material is spread can be adjusted just as easily as the delivery rate.

The spreader is carried in front of the body by means of an adjustable strap. The large filling aperture makes filling easy, whilst the large screw top protects users from harmful dust.

Large filling and cleaning aperture with tightly fitting dust cap – prevents the ingress of dust
 Padded shoulder strap

Large 9 l tank

03

- 04 Smooth-running manual crank drive
 - 05 Robust integral agitator: Hermetically sealed, gearbox with angular metal gears
 - 06 Spreader disc with large fins for even application

Also suitable for winter grit (salt, etc.)

9 l, 2.5 kg • Part no. 42101






Adjustable distribution direction (1), agitator (2)



Enclosed worm drive with angular metal gears





Comfortable strap

Secure base and ergonomic moulding

BLOWER



01 Robust carrying handle
02 Clean combustion engine with aluminium crankcase
03 Large starter handle
04 Single hand operating handle

06 Stable base

07


Anti-vibration system effectively reduces vibrations at body contact points Padded back support

66.5 cm³, 2.1 kW/2.9 hp, 1400 m³/h, 8.4 kg Part no. 46801 The compact SOLO 468 blower combines very low weight with high performance, low consumption and low emissions. The SOLO 468 is characterised in particular by its high blower output, taking into account the interests of the environment and the immediate surroundings. Last but not least, the price/performance ratio is one of the most convincing selling points of this new SOLO 468 blower.



SPECIFICATION

Model Part no.	403 40301	404 40401	401 40101	402 40201	460 Li 46001
Battery	-	-	-	-	3.7 V / 1.4 Ah
Piston pump	•	•	•	•	•
Nominal capacity I	1.25	2.0	1.0	2.0	1.0
Spray pressure bar max.	2	2	2.5	2.5	-
Safety valve	•	•	•	•	-
Dry weight kg	0.5	0.6	0.4	0.5	0.3






Model Part no.	453 45301
Piston pump	•
Nominal capacity l	11
Spray pressure bar max.	2
Dry weight kg	3.5
Transport wheels	Yes
Hose length m	2.5 (spiral hose)
Spray wand	Plastic, 40 cm
Nozzle	SOLO universal hollow cone nozzle, adjustable

•)	1	1		l J		
soto	Solo	84	E-9	66	ente Ente	enio esp	era
1	Log	- FRA		Line	L-1	Ling 1	ternt

Model Part no.	NOVA 424 42422	473 D Classic 47321	425 Classic 42521	435 Classic 43521	475 Classic 47521	425 Comfort 42531	475 Comfort 47531	425 Pro 42541
Pump type – piston/diaphragm	• / -	-/ •	• / -	• / -	-/ •	• / -	-/ •	• / -
Nominal capacity I	16	10	15	20	15	15	15	15
Max. spray pressure bar	4	4	4	4	4	4 / 6*	4	4 / 6*
Spray wand length cm	50	50	50	50	50	50	50	50 - 90, adjustable
Manual spray pressure adjustment	-	-	-	-	-	•	•	•
Pump lever adjustable	-	-	-	-	-	•	•	•
FKM seals ("Viton®")	-	-	-	-	-	•	•	•
Telescopic carbon spray wand	-	-	-	-	-	-	-	•
Pressure gauge	-	-	-	-	-	-	-	•
Dry weight kg	5.1	4.2	4.4	5.0	4.6	4.5	4.7	5.2
4140.1								

* With plugs

SPECIFICATION





		Available from mid-2021		
Model Part no.	441 44101	442 44201	417 41701	416 Li 41601
Battery V/Ah	Lithium-ion 11.1 / 2.5	Lithium-ion 18 / 2.0	Lead gel 12 / 7.2	Lithium-ion 11.1 / 7.8
Nominal capacity I	16	16	18	20
Nozzle	Univ. hollow cone, adjustable	Univ. hollow cone, adjustable Flat spray nozzle	Flat spray nozzle	Flat spray nozzle
Spray pressure settings / bar	1/2.5	4 / 1-4	2 / 2.5; 4.3	2 / 2.5; 4.3
Spray volume l/min (setting) with standard nozzle	0.6-1.16	0.68 (1) / 0.97 (2) 1.19 (3) / 1.37 (4)	1.07 1.42	1.07 1.42
Operating time h	2.9	3.4	l: 3.7 ; l l: 2.3	l: 5.9 ; l l: 3.7
Charging time h	approx. 2	approx. 1.1	approx. 8	approx. 5.5
Dry weight inc. battery kg	3.8	4.5	7.6	5.2
Spray wand	Plastic, 50 cm	Plastic, 50 cm	Plastic, 50 cm	Adjustable, 50 - 90 cm, carbon
Standard delivery	Battery, charger	Battery, charger	Battery, charger, pressure gauge	Battery, charger, pressure gauge, waist belt
Sound pressure level dB(A)(1)	< 70	< 70	< 70	< 70
Sound power level guaranteed dB(A) ⁽¹⁾	< 70	< 70	< 70	< 70
Vibration value m/s ^{2 (2)}	≤ 2.0	≤ 2.0	≤ 2.0	≤ 2.0

Model	433
Part no.	43303
Engine	4-stroke Honda GX 25
Capacity cm ³	25
Nominal capacity I	20
Stainless steel twin nozzle	•
Max. adjustable spray pressure bar	up to 30
	1.0 l at 5 bar
Spray volume l/min with standard	1.5 l at 10 bar
nozzle	2.0 l at 20 bar
	2.4 l at 30 bar
Dry weight kg	9.8
Pressure gauge	•
Standard delivery	Stainless steel spray wand
Sound pressure level dB(A) ⁽¹⁾	82
Sound power level dB(A) ⁽¹⁾	95
Vibration value m/s ^{2 (2)}	≤ 2.0








÷ *

Model Part no.	MASTER 452 45201** / 45203 (EU)	MASTER 452-02 45202**	PORT 423 42311**
Engine	2-stroke SOLO	2-stroke SOLO	2-stroke SOLO
Capacity cm ³	66.5	66.5	72.3
Power kW/hp	2.1 / 2.9	2.1 / 2.9	3.0 / 4.1
Tank capacity (nominal) l	12 (10)	15 (13)	12 (10)
Air flow rate max. m3/h*	1400	1400	1400
Horizontal reach in m	11.0	11.0	12
Dry weight kg	9.6 (45201) / 9.7 (45203)	9.7	11.0
Standard delivery	SOLO special misting nozzle with	4 settings, long reach nozzle, wide spray grille, single	sided and double sided deflector
Sound pressure level dB(A) ⁽¹⁾	96	96	97
Sound power level L _{WAeq} dB(A) ⁽¹⁾	110	110	110
Vibration value m/s ^{2 (2)}	≤ 2.5	≤ 2.5	≤ 6.3
*Excl. blower ** Not for the EU			



≤ 2.5

	soate
Model	421
Part no.	42101
Fill capacity I	9
Tank filling aperture diameter cm	14.5
Dry weight kg	2.5
Dimensions excl. crank W x D x H, cm	29 x 26 x 49
Distribution range subject to material, cm	Granulate approx. 300 - 400 Grass seed approx. 180 - 200
Distribution width subject to material, cm	Granulate approx. 180 - 200 Grass seed approx. 150 - 170
Gearbox	Hermetically sealed worm drive with angular metal gears
Transmission ratio	1 : 7.5


Vibration value m/s²

Engine

Spray wands for pressure and backpack sprayers

٠	Recomme	nded	•	Suitable	•		Not red	commei	nded		-	Unsuita	ble / do	oes not	fit
Pos.	Designation	Description an	ıd re	commended application	Par	't no.		403 404	408 409 453	401 402	461 462	456 457 458	424 425 435	473 D 475	416 Li 417 441 442
1	Telescopic wand 25 - 50 cm	extended to u nozzle and sm makes it easier further away of head can be pi convenient and affected leave plastic, impact-r	p to all d to re or co ivoto effects. Th resist	and, can be continuously 50 cm, with adjustable universal rift guard. The telescopic function ach parts of plants that are ncealed. For example, the nozzle ed through 180°, making it tive to treat the underside of e telescopic wand consists of a cant, profiled outer tube and a high ess steel inner tube.	490	628		-	-	•	-	-	-	-	-
2	Spray wand 50 cm with flat spray nozzle	head, high grad union nut for at is flexible and al plastic material t	de fla ttach mos that o	50 cm, including angled nozzle at spray nozzle, filter strainer and ment to the manual valve. Spray wand t unbreakable thanks to high quality can withstand extreme loads. Suitable iany plant protection applications.	494	439		-	•	-	•	•	•	•	• 441: •
3	Extension wand 50 cm	that simply red connection nut SOLO spray war sprayers with a	quire with nds, f nom hank	extension wand for all applications an extended reach. It includes a seal ring to attach to all standard or pressure sprayers and backpack inal capacity of 5 I or more. Almost s to high quality plastic material that ne loads.	49!	513		-	•	-	•	•	•	•	•
4	Brass spray wand, 50 cm	applications the We also recommendation accessories survey 50 cm brass spra	nat r nend ch a ay w ete w	intensive and professional equire robust, rigid spray wands. it for working with SOLO s spray booms or drift guards. The and has a diameter of 8 mm and is vith union nut for attachment to the	49!	519		-	•	-	•	•	•	•	•
5	Universal spray wand, 50 cm		nufac	backpack sprayers from SOLO and turers. Including adjustable universal nozzle.	-	610		-	•	-	•	•	•	•	•
6	Brass spray wand, 75 cm	that require ro long spray wand	o <mark>bus</mark> d car	ve and professional applications t, rigid spray wands. The 75 cm be optimally supplemented with ch as drift guards.	494	428		-	•	-	•	•	•	•	•
7	Brass telescopic spray wand 57 - 100 cm	can be continuo in any position. challenging or extended reach recommended guards. The teles	usly It ca com or t for v scopi	escopic spray wand made from brass extended up to 100 cm and locked in be put to various uses for any mercial application, to enable an o treat ground level areas. Also vorking with spray booms or drift c spray wand is supplied complete with tent to the SOLO manual valve.		478		-	•	-	•	•	•	•	•
	Brass tree spray wand, 150 cm	applications the extended reach plants, e.g. for s The brass tube co	at re n. We prayi onsis	and is ideal for all challenging quire a robust, rigid wand with an also recommend it for treating taller ng espaliered trees or bushes. ts of two 75 cm threaded spray wands er, including two union nuts and seals		528		-	•	-	•	•	•	•	•
9	Carbon tree spray wand 120 cm	The 120 cm long spray wand made from carbon fibre materia weighs just 100 g. It can be used for all challenging applications that require rigid and extremely lightweig wands – even with an extended reach. Thanks to its very low weight, it protects the operator's joints and is suital for longer working periods. Supplied complete with unior nut for attachment to the SOLO manual valve.				449		-	•	-	•	•	•	•	•
	Carbon telescopic spray wand 60 - 120 cm	ultra-light carb recommend this that require a r with adjustable working with a guards. Long wo wrists are no pro	telescopic spray wand made from bre material weighs just 95 g. We on for all challenging applications and extremely lightweight wand ch. It is also recommended for sories such as spray booms or drift g periods with minimal strain on the I. The standard delivery includes the tent to the SOLO manual valve.	494	457		-	•	-	•	•	•	•	•	

Pos.	Designation	Description and recommended application	Part no.	403 404	408 409 453	401 402	461 462	456 457 458	424 425 435	473 D 475	416 Li 417 441 442
11	Carbon telescopic spray wand 120 - 230 cm	The telescopic spray wand made from ultra-light carbon fibre material weighs just 160 g and is continuously adjustable in length from 120 - 230 cm. It can be used for all challenging applications that require rigid and extremely lightweight wands with a very long reach. The low weight greatly facilitates the work and protects the operator's joints, enabling long periods of use. Supplied complete with union nut for attachment to the SOLO manual valve.	49445	-	•	-	•	•	•	•	•
12	Spray wand extension, flexible, 15 cm	Flexible and ideally suitable for treating inaccessible areas and places that are not easily visible or are difficult to reach, including use in pest control, for example. With the pliable spray wand section that can be bent by up to 180°, the jet can be sprayed in any direction. Including connection nut for fastening to an existing spray wand end piece, without nozzles. Can be combined with all SOLO spray wands and spray nozzles; the union nut for attachment is included.	49450	-	•	-	•	•	•	•	•
13	Flexible double spray head 60 cm	The double spray head has many possible applications, e.g. for treating a plant or row of plants from two sides at once, or for spraying two rows at the same time. With its twin nozzles, it can be used for treating single plants and to apply repellent spray to protect against browsing animals. With its two flexible spray wands, the double spray head has a total operating width of 60 cm. It comes complete with nuts to connect to each spray wand, preinstalled hollow cone spray nozzles and two further sizes of hollow cone nozzle. Other types of nozzle in different sizes can also be fitted if preferred.	49411	-	•	_	•	•	•	•	441:
	Spray boom 60 cm NEW: Now with extended nozzle set in 3 sizes	The 60 cm wide spray boom has two nozzles in three different sizes and is ideal for treating two rows at a time or spraying large areas. Made from special, almost unbreakable plastic material, supplied with two ball valve nozzle filters to prevent dripping and a union nut for attachment to an existing spray wand. We recommend combining it with the SOLO short, rigid, brass or carbon fibre spray wands.	49514	-	•	-	•	•	•	•	•
15	Aluminium spray boom 120 cm NEW: Now with extended nozzle set in 3 sizes	For treating larger areas, we recommend twice the spraying width with the 120 cm wide, light, aluminium spray boom. Four flat spray nozzles and four ball valve nozzle filters to prevent dripping are preinstalled; two further sets of four nozzles are included. It can be ideally combined with the SOLO short, rigid, brass or carbon fibre spray wands. The union nut for attachment to the spray wand is provided.	49299	-	•	-	•	•	•	•	• 441: •




Nozzles and drift guards for pressure and backpack sprayers

٠	Recommer	nded	•	Suitable	•		Not reco	ommen	ded	-	U	nsuitat	ole / do	es not f	it
Pos.	Designation	Description an	nd re	commended application	Par	t no.		403 404	408 409 453	401 402	461 462	456 457 458	424 425 435	473 D 475	416 Li 417 441 442
1	Full nozzle set	application are different, high hollow cone ne Four flat spray spraying rows. V 015, 02, 03 and Two deflector herbicides: for low pressure rar like spray patter DT 2.5. Three hollow c shrubs and lar, directions, esp The three match 1.4 and 1.8 mm required swirl pl	eas. grad ozzle r noz With a 04. nozz treat nge v rn. Th cone ge so becia ning r n, and late. nclud	et for all the most important The set contains a total of nine de flat spray, deflector and es. zles for treating large areas and a ribbon-like spray pattern in sizes cles especially for applying ing large areas and working in the with a coarse droplet size and ribbon- te nozzles come in sizes DT 1.0 and nozzles for treating single plants, cale plantings that extend in all lly for insecticides and fungicides. nozzle caps have hole sizes of 1.0, l are used in combination with the les a nozzle head with preinstalled		574			•	-	•	•	•	•	•
2	Universal plastic nozzle, adjustable	especially suitab be adjusted fror	ole wl m fin	cone nozzle made from plastic is hen treating single plants. It can le droplets with a hollow cone- rn, right through to a point jet.	49!	525		-	•	-	•	•	•	•	•
3	Universal brass nozzle, adjustable	especially suitab extend in all di	ole wl irect	cone nozzle made from brass is hen treating single plants that ions . It can be variably adjusted from through to a point jet .	492	206		-	•	-	•	•	•	•	•
4	Oval drift guard 30 x 11.5 cm	herbicide over spraying in ed fine droplets u areas containi equipped with spray pattern the umbrella sh section has beer visibility of the	r larg ge a inint ng ci a fla and i ape. n red e are nbini	guard should be used for applying yer areas and for precision reas. The drift guard helps prevent entionally drifting into adjacent rops or bodies of water. It is t spray nozzle for a ribbon-like s effectively limited at the sides by The transparent design of the guard lesigned to give users optimum ea to be treated whilst working. We ng it with a 75 cm brass spray wand oray wands.	494	430		-	•	-	•	•	•	•	•
5	Round drift guard Ø 15 cm	protection for ta and for use on full cone nozzle The guard effect prevent fine dr adjacent areas The round drift g	arget vari e ens tively rople con guard	ound drift guard with UV light ed, accurate herbicide application ous smaller plots. Its preinstalled sures a circular spray pattern. restricts the spraying range to help ets unintentionally drifting into taining crops or bodies of water. I is also made from transparent, ptimum visibility of the area to be		580		-	•	-	•	٠	•	•	•

Pos.	Designation	Description and recommended application	Part no.		403 404	408 409 453	401 402	461 462	456 457 458	424 425 435	473 D 475	416 Li 417 441 442
-	Dual nozzle with nozzle set	With its two pivoting nozzle heads, the dual nozzle is suitable for a diverse range of applications. In conjunction with telescopic or extension wands, it enables users to treat two rows of plants at once or spray at an angle, e.g. to treat the underside of leaves or to reach awkward places. Each of the nozzle heads can be pivoted through approx. 270°. The standard delivery includes two preinstalled hollow cone nozzles for large scale plantings and two flat spray nozzles for treating large areas. The set also contains dummy plugs to allow one nozzle to be closed off. Using the knurled screw, the dual nozzle can be attached to existing spray wands without the need for tools.			-	•	-	•	•	•	•	441:
			•	4				5	,			6 0

Sets of seals for pressure and backpack sprayers

•	Recommen	nded	•	Suitable	•	Ν	lot reco	ommen	ded	-	U	nsuitab	le / do	es not f	it
Pos.	Designation	Description a	nd re	commended application	Pa	rt no.		403 404	408 409 453	401 402	461 462	456 457 458	424 425 435	473 D 475	416 Li 417 441 442
1	Standard set of seals	Contains all sta models 461 an		rd seals for SOLO pressure sprayer 2 .	49	551		-	-	-	٠	-	-	-	-
2	Standard set of seals	Contains all sta models 456, 45		d seals for SOLO pressure sprayer d 458 .	49	441		-	-	-	-	•	-	-	-
3	Standard set of seals			rd seals for SOLO backpack sprayer 5 with piston pump.	49	442		-	-	-	-	-	٠	-	-
4	FKM set of seals	456, 457 and	Contains all seals for SOLO pressure sprayer models ISG, 457 and 458. Made from highly resistant FKM naterial ("Viton®").					-	-	-	-	•	-	-	-
5	FKM set of seals	425 and 435 v resistant FKM	with mat	SOLO backpack sprayer models piston pump. Made from highly erial ("Viton [®] "). Standard all SOLO backpack sprayer models in categories.	49	578		-	-	-	-	-	•	-	-
6	Standard set of seals	models 475 an	d 47. diap	d seals for SOLO backpack sprayer 3 D Classic with diaphragm pump. hragms made from special, highly naterial (TPV).	49	443		-	-	-	-	-	-	•	-
7	FKM set of seals	and 473 D Cla highly resistar diaphragms ma	ssic v nt FKI de fro ment	SOLO backpack sprayer models 475 vith diaphragm pump. Made from M material ("Viton®"). Including m special, highly resistant Tivilon® level for SOLO 475 Comfort and		579		-	-	-	-	-	-	•	-



Other accessories

•	Recomme	nded	•	Suitable	•	Not rec	ommen	ded	-	U	Insuitat	ole / do	es not f	it
Pos.	Designation	Description a	nd re	commended application	Part no.		403 404	408 409 453	401 402	461 462	456 457 458	424 425 435	473 D 475	416 Li 417 441 442
1	Manual valve set	made from spec and connection	cial p for i	al valve. Robust, ergonomic design lastic material. With childproof lock Istalling a pressure gauge (optional). Icessary for installation.	49440		-	•	-	•	•	•	•	•
2	Pressure gauge	highly accurat with permane readable displ (0 - 90 psi) in pressure gaug handling, it is o	te me nt sp lay ra 0.2 k je ag equip ïle. Th	professional pressure gauge for easurements and readings, used aray pressure control. The easily ange extends from 0 to 6 bar ar increments. To protect the ainst any impact and to ensure safe ped with a large, removable rubber e standard delivery includes union	49356		-	•	-	•	•	•	•	-
3	Ball valve filter	shut off, we re stainless steel spray wands ar below the spray Standard equip	comr I filte re use y noz ment	g after the manual valve has been nend using the ball valve filter with r insert – especially when telescopic d. Straightforward insertion zle, instead of the standard filter. level for SOLO spray booms 49514 pressure 0.3 bar. Mesh size 50 mesh,	49539		-	•	-	•	•	•	•	•
4	Pro backpack carrying system	makes safe and sprayers easier of with the help of it offers maxim distribution of High quality m padding and vo integral waist to that of a mod fits all SOLO ba capacities (incl	The comfortable, professional backpack carrying system makes safe and tireless working with SOLO backpack sprayers easier over longer operating periods. Developed with the help of experts from the outdoor sports sector, it offers maximum user comfort thanks to the balanced distribution of weight over the shoulders and hips. High quality materials, wide straps with comfortable padding and ventilation of the shoulder straps and integral waist belt ensure perfect wearing comfort, akin to that of a modern hiking rucksack. The carrying system fits all SOLO backpack sprayers with 12 I and 15 I tank capacities (including older models) and is standard equipment for the latest SOLO PRO backpack sprayer models				-	-	-	-	-	•1)	•	-
5	Compressed air connection valve	having to pun cushion of air t working perio spray pattern connection va air supply to b an integral, aut	uild-up of pressure saves you anually. Allows a large pressurised ld up quickly and easily for longer /hilst maintaining a professional pivoting compressed air enables an external compressed onnected to the sprayer and has tic overpressure valve. It fits SOLO dels 456, 457 and 458.	49590		-	-	-	-	•	-	-	-	
6	Wheel set	traction whee and movement	wheel set, comprising large, high cl. axle and a handle for easy tilting enables the pressure sprayer 458 comfortably, without having to be	49211		-	-	-	-	•2)	-	-	-	



36

Accessories for backpack power sprayers

٠	Recommended	•	Suitable	٠	Not recommended	- Un	suitable / d	oes not fit
Pos.	Designation	Descri	ption			Part no.		433
1	Extension wand, 120 cm stainless steel	that re ensure attache	ommend the 120 cm extension wand m quire a considerably extended react safe handling, it is equipped with an ex ed to the existing manual valve. Can als ard stainless steel spray wand from t	n, e. asy g o be	grip plastic sleeve and can be simply used in combination with the	49183		•
2	Spray wand, 120 cm with shut-off tap and stainless steel changeover nozzle	is suita recomm sprayin exchan reach o turning a short greate	iversal spray wand made from stainless st able for all professional assignments to nend this wand for high precision spray ng trees in orchards and other horticu ige of standard spray wand and manu can be adjusted using the rotating selecto the selector changes the spray pattern fr t reach and fine droplets, to a narrow r reach. Including handle and two chang e, the spray wand can be used for cleani	hat ring ltura al v r at f om t full eove	require an extended reach. We also and single plant treatment, e.g. al applications. Straightforward alve. Flow rate, spray pattern and the handheld end of the spray wand: the initial broad hollow cone with cone and then to a full jet with a er nozzles in different sizes. At higher	49185		•
3	Telescopic extension wand, 120 - 230 cm Stainless steel	that re The ler the larg	ommend the telescopic spray wand ma quire a considerably extended react ngth can be variably adjusted betwee ge fixing nut made from stainless steel. to attach to the existing manual valve.	n, e. en	g. for very tall, lignified plants. 120 and 230 cm and is locked using	49189		•
4	Spray boom with 4 nozzles Stainless steel	plants	rdy, stainless steel spray boom is suitab . Four preinstalled nozzles, one 75 cm s r attachment to the existing manual va	tainl	ess steel spray wand and the wing	49300		•
5	Twin nozzle Stainless steel	the SO materia	in nozzle is suitable for universal use a LO 433 backpack power sprayer. The no al; the two individual preinstalled nozzle nt blockages .	zzle	retainer is made from robust plastic	49182		•
6	Extension hose 10 m with retaining bracket	– even to rem extensi	mended for all spraying applications when working at moderate heights tain on the ground. A bonus for comf on hose is 10 m long. The retaining brac and can be neatly rolled up and stored	who ort ket f	ere the power sprayer itself has and safety. The robust, high pressure fits the filling aperture of the SOLO 433	49191		•



Accessories for power misters

	Recommended	•	Suitable	•	Not recommended	-	Unsuitable / d	loes not	fit
Pos.	Designation	Descrip	otion			Part no).	423	452
1	Dusting attachment	dusting granula such as	ting attachment allows the SOLO Port a machine. This makes it possible to a ate or powder form. The standard del the corrugated supply hose, ventilatior ow with dusting metering lever.	ivery	y plant protection medium in / includes all of the necessary parts,	49233		•	-
2	ULV nozzle with metering device NEW!	the ULV droplet with the to the a flow ra in all pa	e new SOLO ULV nozzle , spray liquids (ultra low volume) process and pes ts. For droplet sizes between 40 and 51 e WHO standard. The very fine mist is sp ir flow from the blower in the mister. Th tes via a setting wheel. This ULV noz rts of the world, i.e. for use against car armful insects.	49480		•	•		
3	Twin nozzle	and en separate 90° wit while m jet to c for exar attachm	e aid of the twin nozzle, the spray pat larged . The amount of spray liquid sup ely. The angle between the two misting thout using tools , i.e. the spray patter isisting. This makes it suitable for very very completely separating it to be able mple when treating two rows at the nents enlarge the jets, which can be ber ng, for example.	plied noz n ca ersat to sj sam	d can be regulated at each nozzle zles can be adjusted from 0° to n be altered from parallel to 90° even ile applications, from enlarging the pray in two different directions, the time. The removable broad spray	49137		•	•
4	Extension wand	extend a SOLO	ne 60 cm extension wand, the jet can ed, which is helpful when spraying liquid booster pump (accessory) is high on wand, in order to ensure a reliable s ly.	49333		•	•		
5	Liquid booster pump	planting reach . l	ommend using the liquid booster pump gs that predominantly require an up It enables a reliable supply of spray liqu xtension wand 49333.	49117		٠	٠		



Two-stroke oil and mixing container

•	Recommended	•	Suitable	•	Not recom	mended	-	Unsuita	able / do	oes not	fit
	Designation	Descri	ption			Part no.		433	423	452	468
1	SOLO Profi 2T engine oil 1 l (for 50 l of two-stroke fuel mixture)	Contai for mix water- contai - Preve - Enabl periods - Prote - Keeps - Excel grade Specific	synthetic universal engine oil with ins cleaning and corrosion-inhibiti acture lubrication and separate lub cooled two-stroke engines. The di ns ensure automatic and even mix nts the fuel mixture ageing es trouble-free engine start even after strouble-free engine start even after the fuel system clean lent ignition capability 2 years; even fuel is used cations: JASO FD, ISO-L-EGD, API TC, C ratio 1:50 (observe instructions from	ng ad ricat ssolv (ing v r stan n lon 6LOB/	dditives. Suitable ion of all air and ring agents it with the fuel. ding for long ger when high AL GD	49104		-	•	•	•
2	Mixing container 1 l	withou mixtur The fur narrow be inse screw o 2-strok	cal, compact mixing container for ut spills or drips, and practical mi re (petrol/oil). Including funnel an nuel makes it easier to fill the tank, e v filler necks. Hard to lose: when nor erted into the mixing container and h cap. The cap can also help to achieve re fuel: 1 cap full of two-stroke oil to ratio of 1:50.	49278		-	•	•	•		



Batteries and chargers

	Recommended	•	Suitable	Not recommended	-	Uns	uitable /	does not	t fit	
	Designation	Desc	ription			Pa	rt no.		441	442
1	Lithium-ion battery 11.1 V 2.5 Ah	Com	pact 11.1 V lithium-ion battery. In	49485			٠			
2	Standard charger 1.5 A		pact charger for external charging ery. Charging current 1.5 A Include	49	486		•	-		
3	Lithium-ion battery 18 V 2.0 Ah	Com	pact 18 V lithium-ion battery. Inclu	Ided \	vith model 442.	49	481		-	•
4	Lithium-ion battery 18 V 5.0 Ah		pact 18 V lithium-ion battery with h. Enables longer periods of use.	high	capacity of 5 Ah, power capacity	49	482		1	•
5	Standard charger 2 A		pact charger for external charging ging current 2 A Included with mod	49	483		-	٠		
6	4 A express charger	Com With	pact express charger for external cl increased 4 A charging current for	g of SOLO 18 V lithium-ion batteries. rter charging times.	49	484		1	•	



German quality worldwide



SOLO Kleinmotoren GmbH was founded in Stuttgart in 1948 and to this day is still a leading global manufacturer of high grade sprayers and misters, blowers and cut-off machines – all featuring the high German quality standards you have come to expect from us.

In addition to our head office in the south German town of Sindelfingen, we have partners and subsidiaries around the world, ensuring we meet our customers' requirements. Quality and proximity to customers are the reasons why SOLO products are used in almost every country in the world.

Are you looking for sprayers or foam sprayers specially designed for cleaning? Request our new **CLEANLine** brochure and ask your local SOLO partner.

We are happy to advise you:





German quality sprayers and cut-off machines

SOLO Kleinmotoren GmbH Postfach 60 01 52 D-71050 Sindelfingen Telephone + 49 70 31 / 301 - 0 Fax + 49 70 31 / 301 - 202 Email: info@solo-germany.com www.solo.global

Subject to technical modifications. 70 253 1/2021

