







CONTENT

03
05
07
09
11
13
17
21
23
25
27
31
35
37
39
43
45
49
53
55
57
61
63
65
66

-LEDLENSER -ABOUT US.

Many revolutionary products first saw the light of day in a garage. This was also the case with the first Ledlenser. When Harald and Rainer Opolka founded the company Zweibrüder Optoelectronics in 1993, they really didn have much more than a garage, an old Atari computer, a set of tools, a sketchpad and around 1,000 Deutschmarks in seed capital.

Today, the former garage company is an international torch and headlamp manufacturer that remains globally unmatched. With over 1,000 employees worldwide, we share the aim of improving a little every day – in everything we do. We are therefore continually expanding our product range, scrutinising even tried and tested ideas and increasingly relying on sustainable energy sources.

- One of the global market leaders in LED torches and headlamps
- Over 1,000 employees worldwide
- Annual sales of roughly £85 million
- Independent research and development
- Independent production and quality assurance
- More than 15 years of experience and know-how
- Well over 100 patents, utility models, designs and brands
- Roughly 200 awards, distinctions and test ratings for more than
 70 of our torches and headlamps



5 — LEDLENSER YEAR WARRANTY⁴

-LEDLENSER QUALITY GUARANTEED.

To us, "engineered in Germany" is not just an empty phrase - it represents the highest standards in innovation, materials, technology, processing and sustainability. Since we are confident in the quality of our products, all of our products are covered by a 5-year warranty⁴ - but there's more: Customers can register their product to extend the warranty to 7 years⁴.

All original Ledlenser products include a product registration card. Customers can simply scan the QR code with a smartphone or enter the URL into the browser of their laptop or PC to register. They will be redirected to a one-time product registration page where they can enter the required information into the form. After the registration is completed, the QR code and the matching URL expire.









This helps protect our products from cheap counterfeits and piracy.

LEDLENSER 360° MARKETING COMMUNICATIONS

You can count on a well-thought-out marketing plan with attractive and versatile marketing measures and substantial sales support.



CUSTOMER COMMUNICATION


- 01 End-consumer brochures
- 02 Advertisements in special-interest publications
- 03 360° Campaigns
- 04 Social media
- 05 Online advertising



POS COMMUNICATION

Our in-store displays bring the Ledlenser experience to life at the POS.

Strong branding on elegant eye-catching displays that feature the required product information all combine to





SALES SUPPORT

- 01 Retailer information
- 02 Sales promotions
- 03 Training / instruction



TRADE SHOWS AND EVENTS

We attend many shows and events to increase visibility of the Ledlenser brand.

We are happy to hear your suggestions on other partnership opportunities.



THE LEDLENSER DISPLAY SERIES

01 - S211 04 - S155 02 - S175 05 - S195 03 - S170 06 - S190 Representative. Available whilst stocks last.









LEDLENSER TECHNOLOGIES.

Prominence means having the technical edge. From innovative lenses to pioneering batteries – we work tirelessly to advance our technological edge. Which is why we already have over 100 patents, utility models, designs and brands. And the next 100 are sure to come. The highlights of our technology:



WIDE BEAM

Our wide beam format takes into account that the human field of vision is around 180° degrees horizontally and only around 130° degrees vertically. The oval shape of the light and the wide beam technology make things twice as safe: You don't only see more, but are also seen from every angle.



SAFETY YTRION CELL

This battery technology is predominantly found in electric vehicles. But it's also perfect for Ledlensers. A Safety Ytrion Cell is considerably lighter than a nickel-metal hydride battery and can be charged up to five times faster than a lithium-ion battery. Plus it olders more than 5,000 charge cycles with virtually zero capacity loss.



ADVANCED FOCUS SYSTEM

Galileo swore by the power of lenses,
Newton swore by redectors. We have simply
combined the two technologies – only
better than anyone before. The result:
our patented³ Advanced Focus System
(AFS), which allows a seamless transition
from homogeneous ②ood beam to sharply
focused spot beam. The e② ciency of the
AFS even has experts thrilled.



SMART LIGHT TECHNOLOGY

This innovation makes your Ledlenser a personal lighting tool: A micro-controller allows you to program your individual range of functions with dierent touch and switch combinations. So you always have the perfect light mode at hand.



TEMPERATURE CONTROL

Hard work leaves our lights cold: Thanks to the intelligent and completely automatic temperature control, a Ledlenser never gets too hot, no matter how much you use it. This protects you from burns and the LED from overheating.



RAPID FOCUS

When you focus and defocus a torch or headlamp, the redector lens moves in relation to the LED. With conventional mechanical systems this is done, for example, by turning the head of the torch. Since we found this technology too slow and impractical, we developed Rapid Focus: a single-hand mechanism used to change the light beam lightning fast – using one hand.



X-LENS TECHNOLOGY

This technology is an enhancement of the Advanced Focus System (AFS). It can merge virtually any number of redector lenses and synchronizes its individual light beams into one perfect ray. The result is a high-grade, homogeneous doodlight in unfocused mode and our most sharply focused high beam to date.



OPTISENSE TECHNOLOGY

Whether it dusky, shaded, dim or pitch-black: With Optisense technology, your Ledlenser will automatically adapt to the current light conditions. The innovative technology controls the luminosity based on the redection of its own light, prevents annoying glare and potentially extends run time.



FLOATING CHARGE SYSTEM

Charge weightlessly and without a cable: With the Floating Charge System, which can be wall-mounted, and its magnetic charging cable, the lamp seems to ②oat in its mount and can be put into action at a ②ick of the wrist. In addition to charging the system via USB, with an adapter they can be plugged into standard outlets or car outlets.



EMERGENCY LIGHT

Turns your torch into an emergency light: If the power goes out while your Ledlenser is in the charging base, it will automatically turn on. So the light helps you locate it so that you can use it to find, for example, the fuse box.

LEDLENSER LIGHT MODES.



BOOST

A temporary burst of light.



STROBE

Quick ②ashes of light with a confusing blinding e②ect for emergency situations.



POWER

Bright light for any situation.



BLINK

Automatically emits light pulses at regular intervals.



MID POWER

Sull cient light output for extended battery life.



POSITION

Regular light pulses at long intervals for position marking.



LOW POWER

Economical light for long battery life, glare-free reading and working.



S.0.S.

The light emits an SOS distress signal in Morse code (3 x short, $3 \times long$, $3 \times short$)





HUNT DOWN THE DARKNESS.







SPEED CHARGING⁵

It only takes 4 hours to reach 80% of the charging capacity.

- **01** Staying power thanks to the front switch, the light can be set down and used as room lighting.
- **02** Eco-friendly and convenient cutting-edge battery technology for the fastest charging time via USB 3.0 in any situation.
- **03** Intelligent controls all SLT functions can easily be selected with your thumb via soft touch.
- **04** Keep an eye on everything battery status and charge indicator are located inside the front switch.
- **05** Easy to operate fast switching and focusing with only one hand!
- **06** Easy on the eyes gentle increase and decrease of brightness.
- **07** X-Lens technology the light emitted by 3 Xtrem LEDs is bundled into one very bright beam.
- **08** Transportation lock light will not accidentally switch on in your bag.

LED

SWITCH

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY ¹ [lm]	_	3000	600	30
LIGHTING RANGE ¹ [m]	_	540	260	80
RUN TIME ¹ [h]	_	5	9	96
LED CONFIGURATION	3 x Xtrem	LEDs		

FEATURES

		Т
		- 1

FRONT SWITCH

TRANSPORTATION LOCK

WEIGHT (INCLUDING BATTERY) 620 g

SIZE AND WEIGHT

171 mm

86 mm

LENGTH (DEFOCUSED)

HEAD DIAMETER

LIGHT MODES

- POWER, MID POWER, LOW POWER, STROBE		

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING, CONSTANT CURRENT CHARGE INDICATOR, BATTERY INDICATOR

TECHNOLOGIES











BATTERY AND CASING

BATTERY	Rechargeable lithium-ion, 3.7 V		
BATTERY CAPACITY ²	10,200 mAh		
RECHARGEABLE	Yes		
CHARGE TIME	8 h		
WATER RESISTANCE	IPX4		
OPERATING TEMPERATURE RANGE -20 °C to +40 °C			





PACKAGING

	BOX
ITEM NUMBER	500847
GTIN	4058205008174
PACKAGING DIMENSIONS (W x H x D)	260 x 105 x 200 mm
PACKAGING WEIGHT	1,560 g
INCLUDES	Rechargeable battery pack, USB cable, adapter, adapter cable, wrist strap, user manual

ITEM NO.	ITEM	ITEM NO. ITEM
501507	Colour Filter Blue	
501508	Colour Filter Red	
501509	Colour Filter Green	
501510	Colour Filter Yellow	
0386	Car Charger	

21 — OUTDOOR ÆRIES

LED

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY¹ [lm]	_	1000	200	10
LIGHTING RANGE ¹ [m]	_	320	120	30
RUN TIME ¹ [h]	_	9	20	192
LED CONFIGURATION 1 x Xtrem LED				

SWITCH

FRONT SWITCH		

SIZE AND WEIGHT

LENGTH (DEFOCUSED)	151 mm
HEAD DIAMETER	39 mm
WEIGHT (INCLUDING BATTERY)	253 g

FEATURES

TRANSPORTATION LOCK
FOCUS LOCK

LIGHT MODES

- POWER, MID POWER, LOW POWER, STROBE		

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING, CONSTANT CURRENT CHARGE INDICATOR, BATTERY INDICATOR

TECHNOLOGIES









BATTERY AND CASING

BATTERY	Rechargeable lithium-ion, 3.7 V	
BATTERY CAPACITY ²	4,900 mAh	
RECHARGEABLE	Yes	
CHARGE TIME	8 h	
WATER RESISTANCE	IPX4	
OPERATING TEMPERATURE RANGE -20 °C to +40 °C		



GREAT RUN TIME AND BEAM DISTANCE

22



PACKAGING

	GIFT BOX
ITEM NUMBER	500844
GTIN	4058205007535
PACKAGING DIMENSIONS (W \times H \times D)	200 x 85 x 130 mm
PACKAGING WEIGHT	643 g
INCLUDES	Rechargeable battery, USB cable, pouch, wrist strap, user manual

ITEM NO.	ITEM	ITEM NO. ITEM
501039	Colour Filter Set	
501025	Remote Switch Type E	
501033	Magnetic Mount	
501034	GoPro Adapter Set Type A	
501027	Leather Pouch Type B	

LED

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY¹ [lm]	_	1000	200	10
LIGHTING RANGE ¹ [m]	_	180	100	20
RUN TIME ¹ [h]	_	6	15	144
LED CONFIGURATION 1 x Xtrem LED				

SWITCH

FRONT SWITCH	

SIZE AND WEIGHT

LENGTH (DEFOCUSED)	128 mm
HEAD DIAMETER	32 mm
WEIGHT (INCLUDING BATTERY)	156 g

FEATURES

TD A NICDODTATION LOCK	
TRANSPORTATION LOCK	

LIGHT MODES

	l de la companya de	
- POWER, MID POWER, LOW POWER, STROBE		

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING, CONSTANT CURRENT CHARGE INDICATOR, BATTERY INDICATOR

TECHNOLOGIES









BATTERY AND CASING

BATTERY	Recharg. lithium-ion, 18650, 3.7 V	
BATTERY CAPACITY ²	3,400 mAh	
RECHARGEABLE	Yes	
CHARGE TIME	6 h	
WATER RESISTANCE	IPX4	
OPERATING TEMPERATURE RANGE -20 °C to +40 °C		



THE POWER WITHIN. REVEALED.





PACKAGING

	GIFT BOX
ITEM NUMBER	500843
GTIN	4058205007504
PACKAGING DIMENSIONS (W x H x D)	200 x 85 x 130 mm
PACKAGING WEIGHT	502 g
INCLUDES	Rechargeable battery, USB cable, pouch, wrist strap, user manual

ITEM NO.	ITEM	ITEM NO.	ITEM
501038	Colour Filter Set		
501024	Remote Switch Type D		
501033	Magnetic Mount		
501034	GoPro Adapter Set Type A		
501026	Leather Pouch Type A		

25 — OUTDOOR ŒRIES

MT6

LED

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY¹ [lm]	_	600	200	10
LIGHTING RANGE ¹ [m]	_	260	120	30
RUN TIME ¹ [h]	_	8	15	192
LED CONFIGURATION 1 x Xtrem LED				

SWITCH

FRONT SWITCH		

SIZE AND WEIGHT

LENGTH (DEFOCUSED)	141 mm
HEAD DIAMETER	42 mm
WEIGHT (INCLUDING BATTERY)	250 g

FEATURES

TRANSPORTATION LOCK	

LIGHT MODES

- POWER, MID POWER, LOW POWER, STROBE	

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING, CONSTANT CURRENT BATTERY INDICATOR

TECHNOLOGIES









BATTERY AND CASING

V
1
40 °C

FOR GREAT ADVENTURES.



PACKAGING

IFT BOX
00845
058205007566
00 x 85 x 130 mm
48 g
et of batteries, pouch, wrist strap, user manual
0

ITEM NO.	ITEM	ITEM NO.	ITEM
501028	Leather Pouch Type C		
501035	GoPro Adapter Set Type B		
		-	
		-	

^{1, 2} Information on page 66.

27 — OUTDOOR-RANGE

MH10

ELEGANT, FEATURE RICH, HANDS-FREE LIGHTING.





600 lm¹ 150 m¹ 120 h¹



SPEED CHARGING⁵

It only takes 3 hours to reach 80% of the charging capacity.

- **01** Eco-friendly and convenient cutting-edge battery technology for the fastest charging time via USB in any situation.
- 02 Extra safety red rear light.
- 03 Removable and washable head strap.
- **04** Comfortable best weight-to-lumen ratio of all Ledlenser headlamps.
- **05** Easy to operate one switch, three light modes (Power, Mid Power, Low Power, Blink).
- **06** Keep an eye on everything pivoting head.
- 07 Enhanced close-range and distance visibility variable focus feature.
- 08 One white Power LED.

MH10

LED

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY ¹ [lm]	_	600	250	10
LIGHTING RANGE ¹ [m]	-	150	100	20
RUN TIME ¹ [h]	_	10	15	120
LED CONFIGURATION	1 x Xtrem	LED		

FEATURES

SIZE AND WEIGHT

WEIGHT (INCLUDING BATTERY) 158 g

HEAD DIAMETER

TRANSPORTATION LOCK
REAR LIGHT (RED)

36 mm

LIGHT MODES

SWITCH

FRONT SWITCH

POWER, MID POWER, LOW POWER	

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING
LOW BATTERY WARNING, CHARGE INDICATOR

TECHNOLOGIES









BATTERY AND CASING

Recharg. lithium-ion,18650, 3.7 V
3,400 mAh
Yes
6 h
IPX4
E-20 °C to +40 °C





PACKAGING


GIFT BOX
500856
4058205007290
0) 150 x 85 x 130 mm
500 g
Rechargeable battery, USB cable, pouch, filter caps, user manual

ITEM NO.	ITEM	ITEM NO.	ITEM
501506	Colour Filter Set		

31 — OUTDOOR-RANGE

MH₆

LIGHTWEIGHT AND POWERFUL.





- **01** Rechargeable battery with USB charging cable friendlier on the planet and your pocket with fewer replacement batteries needed.
- 02 Keep an eye on everything pivoting head.
- 03 Easy operation one switch, three light modes (Power, Mid Power, Low Power, Blink).
- 04 Well informed charge indicator and low battery warning.
- 05 Glare-free red LED with strobe function.
- 06 One white Power LED.
- **07** Enhanced close-range and distance visibility variable focus feature.
- 08 Removable and washable head strap.

MH6

LED

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY ¹ [lm]	_	200	_	20
LIGHTING RANGE ¹ [m]	_	120	_	40
RUN TIME ¹ [h]	_	5	_	20
LED CONFIGURATION 1 x Xtrem LED				

HEAD DIAMETER	29 mm
WEIGHT (INCLUDING BATTERY)	93 g

SWITCH

FRONT SWITCH		
-		

FEATURES

SIZE AND WEIGHT

TRANSPORTATION LOCK, DIMMABLE	
GLARE-FREE RED LIGHT	

LIGHT MODES

BOOST, LOW POWER, BLINK		

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING
LOW BATTERY WARNING, CHARGE INDICATOR

TECHNOLOGIES









BATTERY AND CASING

BATTERY	Rechargeable lithium-ion, 3.7 V		
BATTERY CAPACITY ²	880 mAh		
RECHARGEABLE	Yes		
CHARGE TIME	4 h		
WATER RESISTANCE	IPX6		
OPERATING TEMPERATURE RANGE -20 °C to +40 °C			





PACKAGING

GIFT BOX
501502
4058205008334
) 85 x 130 x 100 mm
315 g
Rechargeable battery, USB cable, user manual

ITEM NO.	ITEM
0359	Helmet Band Fixing Clips (4x)
0368	Helmet Connecting Kit Type B
0380	USB Car Charger
0384	Power Supply 5 V
0389	USB Power Supply 5 V and Adapter Cable
7784	Lithium-ion Rechargeable Battery 3.7 V / 880 mAh

ITEM NO.	IIEM
0374	Elastic Reflecting Headband Type A (Gray)

35 — OUTDOOR ŒRIES

MH₂

LED

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY ¹ [lm]	_	100	-	15
LIGHTING RANGE ¹ [m]	_	100	_	30
RUN TIME ¹ [h]	_	10	_	40
LED CONFIGURATION	1 x Xtrem	LED		

SWITCH FEATU

FRONT SWITCH		

SIZE AND WEIGHT

HEAD DIAMETER	29 mm
WEIGHT (INCLUDING BATTERY)	105 g

FEATURES

TRANSPORTATION LOCK	
GLARE-FREE RED LIGHT	

LIGHT MODES

BOOST, LOW POWER, BLINK		

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING

TECHNOLOGIES







BATTERY AND CASING

BATTERY	3 x AAA, 1.5 V	
BATTERY CAPACITY ²	1,250 mAh	
RECHARGEABLE	No	
CHARGE TIME	-	
WATER RESISTANCE	IPX6	
OPERATING TEMPERATURE RANGE -20 °C to +40 °C		

LEADING BY EXAMPLE.



PACKAGING

GIFT BOX
501503
4058205008365
0) 85 x 130 x 100 mm
303.5 g
Set of batteries, user manual

ITEM	ITEM NO.	ITEM
Helmet Band Fixing Clips (4x)	7784	Lithium-ior
Helmet Connecting Kit Type B	0380	USB Car Ch
Elastic Reflecting Headband Type A (Gray)	0384	Power Sup
	0389	USB Power
	Helmet Band Fixing Clips (4x) Helmet Connecting Kit Type B	Helmet Band Fixing Clips (4x) Helmet Connecting Kit Type B Clips (4x) Elastic Reflecting Headband Type A (Gray) O384

7784	Lithium-ion Rechargeable Battery 3.7 V / 880 mAh
0380	USB Car Charger*
0384	Power Supply 5 V*
0389	USB Power Supply*

 $^{^* \, \}text{Additional accessories must be purchased for use (Item no. \, 7784 \, rechargeable \, lithium-ion \, battery)!}$

^{1,2} Information on page 66.

FOR WHEN YOU NEED MORE THAN A WHITE LIGHT. THE LEDLENSER P7QC | T2QC



39 — SPECIAL

RED | GREEN | BLUE | WHITE

LET LETSER @ P7c

SHOW YOUR COLOURS. EVEN AT NIGHT.



- 01 Prismatic diffusion lens for optimum light and colour performance.
- **02** Simply twist to select desired light colour.
- 03 Lightweight aircraft-grade aluminium housing.
- **04** P7QC IPX7 | T²QC IPX6 protected from splashing water.
- 05 Easy to operate one end cap switch.

APPLICATION

Reading maps, maintaining night vision

GREEN

Observing game and wildlife, green light is almost invisible to animals

Tracking, shows 🛮 uids General illumination in higher contrast

WHITE

41 — SPECIAL 42

-P7QC | T²QC RED | GREEN | BLUE | WHITE

LED

BOOST/POWER/MID POWER/LOW POWER	P7QC	T ² QC
LUMINOSITY ¹ [lm]	-/220/-/40	-/140/-/-
LIGHTING RANGE ¹ [m]	-/60/-/20	-/25/-/-
RUN TIME ¹ [h]	-/3/-/25	-/4/-/-
LED CONFIGURATION	1 x Power LED	

SIZE AND WEIGHT

3 mm	97 mm
mm	30.5 mm
'5 g	106 g
	mm

P7QC | T2QC SWITCH

END CAP SWITCH		

P7QC | T2QC FEATURES

,,,	RED, GREEN, BLUE, WHITE LIGHT INSTANTLY
-----	---

LIGHT MODES

P7QC	T ² QC
POWER, LOW POWER, BLINK	POWER



BATTERY AND CASING

	P7QC	T ² QC
BATTERY	4 x AAA Alkaline, 1.5 V	3 x AAA Alkaline, 1.5 V
RECHARGEABLE	No	No
CHARGE TIME	-	-
WATER RESISTANCE	IPX7	IPX6
OPERATING TEMPERATURE RANGE	-20 °C to +40 °C	-20 °C to +40 °C

PACKAGING

	P7QC GIFT BOX	P7QC TEST-IT PACK	T ² QC TEST-IT PACK
ITEM NUMBER	9407Q	9407QTP	9802QCTP
GTIN	4029113940764	4029113960786	4029113990288
PACKAGING DIMENSIONS (W x H x D)	153 x 73 x 73 mm	280 x 105 x 150 mm	280 x 78 x 150 mm
PACKAGING WEIGHT	320 g	400 g	345 g
INCLUDES	Set of batteries, user manual		

TACKLE THE DARKNESS. THE LEDLENSER SPORT SERIES.







From A for alpine skier to Z for zorbing fan: Action and extreme sports enthusiasts who sometimes also like to venture out at night must be able to face the dark. The best way is with a light from our wide range of products in the Sport Series. All athletes will 2nd a model that perfect for them - and their sport.

45 — SPORT SERIES

XEO19R

TAILORED TO THE EXTREME.





- 01 4 hours of battery life in Boost mode, 20 hours in Low-Power mode. 2
- 02 Optisense Technology controls luminosity based on reflecting light.
- 03 Easiest to operate 5-way switch with 2 ve light modes: Boost, Power, Low Power, Blink and Emergency Light.
- 04 No more "tunnel vision" perfect spill and hot spot light.
- 05 Optimum light distribution two individually adjustable LED canons!
- **06** Multi-functional combine with casings and holders for a variety of applications.
- 07 Flexible use can be clipped to pants or a belt.
- 08 The PowerBox can also be used separately as a powerful and convenient power bank.









STYLISH AWARD WINNER (RED DOT AWARD, IF AWARD 2016)

XFO19R

LED

	BOOST	POWER	MID POWER	LOW POWER
LUMINOSITY ¹ [lm]	2000	1000	-	200
LIGHTING RANGE ¹ [m]	300	220	_	100
RUN TIME ¹ [h]	4	8	_	20
LED CONFIGURATION	2 x Xtrem	LED		

SWITCH

FRONT SWITCH		

SIZE AND WEIGHT

HEAD DIAMETER	38.2 mm
WEIGHT (INCLUDING BATTERY)	478 g
WEIGHT WITHOUT BATTERY	193 g

FEATURES

TRANSPORTATION	I LOCK

LIGHT MODES

BOOST, POWER, LOW POWER, BLINK, EMERGENCY LIGHT	

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING
BATTERY INDICATOR, CHARGE INDICATOR

TECHNOLOGIES















BATTERY AND CASING

BATTERY	Lithium-ion PowerBox, 7.4 V		
BATTERY CAPACITY ²	5,200 mAh		
RECHARGEABLE	Yes		
CHARGE TIME	8 h		
WATER RESISTANCE	IPX6		
OPERATING TEMPERATURE RANGE -10 °C to +50 °C			





PACKAGING

	SOFT CASE			
COLOUR	BLACK	GREEN	WHITE	
ITEM NUMBER	7219-R	7219-RG	7219-RW	
GTIN	4029113721905	4029113721967	4029113721936	
PACKAGING DIMENSIONS (W x H x D)	257 x 183 x 119 mm			
PACKAGING WEIGHT	1272 g			
	PowerBox, power adapter, adapter cable, extension cable, neoprene pouch for PowerE			
INCLUDES bike mount for PowerBox, bike connector, helmet clip, adapter for GoPro access			adapter for GoPro accessories, tripod	
	adapter, belt clip for PowerBox, cleaning brush, cleaning cloth, user manual			

ITEM NO.	ITEM	ITEM NO.	ITEM
0386	Car Charger	500831	XEO PowerBox including bag
0400	GoPro Mount		
0401	Tripod Mount		
0402	Helmet Connecting Kit Type C		
0404	Bike Mounting Bracket Type A		
0405	Waist Clip for PowerBox		

49 — SPORT SERIES

SE07R

AS UNIQUE AS THOSE WHO WEAR THEM.













- **01** Rechargeable battery with USB charging cable eco-friendly, functional, no need for expensive disposable batteries.
- **02** Easy operation one switch, three light modes (Power, Mid Power, Low Power, Blink).
- 03 Keep an eye on everything pivoting head.
- 04 Glare-free red LED with strobe function.
- 05 One white Power LED.
- **06** Optisense Technology controls luminosity based on reflecting light.
- **07** Enhanced close-range and distance visibility variable focus feature.
- 08 Removable and washable head straps.

STYLISH AWARD WINNER (GD SPECIAL MENTION 2015, IF AWARD 2016)

51 — SPORT ÆRIES

-SEO7R

LED

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY ¹ [lm]	_	220	_	20
LIGHTING RANGE ¹ [m]	_	130	_	40
RUN TIME ¹ [h]	_	5	_	20
LED CONFIGURATION	1 x Xtrem	LED		_

SWITCH

FRONT SWITCH		

SIZE AND WEIGHT

HEAD DIAMETER	29 mm
WEIGHT (INCLUDING BATTERY)	93 g

FEATURES

TRANSPORTATION LOCK, DIMMABLE
GLARE-FREE RED LIGHT
ALSO WORKS WITH AAA ALKALINE BATTERIES (NOT SUPPLIED)

LIGHT MODES

BOOST, LOW POWER, BLINK		

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING, CONSTANT CURRENT LOW BATTERY WARNING, CHARGE INDICATOR

TECHNOLOGIES













BATTERY AND CASING

BATTERY	Rechargeable lithium-ion, 3.7 V	
BATTERY CAPACITY ²	880 mAh	
RECHARGEABLE	Yes	
CHARGE TIME	6 h	
WATER RESISTANCE	IPX6	
OPERATING TEMPERATURE RANGE -20 °C to +40 °C		



POWERFUL. RECHARGEABLE.



PACKAGING

		TEST-IT PACK	
COLOUR	BLACK	BLUE	
ITEM NUMBER	6107-RB	6107-R	
GTIN	4029113610735	4029113610759	
PACKAGING DIMENSIONS (W x H x D)	132 x 240 x 66 mm		
PACKAGING WEIGHT	246.8 g		
INCLUDES	Set of batteries, 1 rechargeable battery, USB cable, user manual		

ITEM NO.	ITEM
0359	Helmet Band Fixing Clips (4x)
0368	Helmet Connecting Kit Type B
0373	Elastic Headband Green
0375	Elastic Headband Gray
0376	Elastic Headband Red
0377	Elastic Headband Blue

0380	USB Car Charger
0384	Power Supply 5 V
0389	USB Power Supply

^{1,2} Information on page 66.

53 — SPORT ŒRIES

SE05

LED

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY ¹ [lm]	_	180	_	20
LIGHTING RANGE ¹ [m]	_	120	_	40
RUN TIME ¹ [h]	_	7	_	25
LED CONFIGURATION 1 x Xtrem LED				

SIZE AND WEIGHT

HEAD DIAMETER	29 mm
WEIGHT (INCLUDING BATTERY)	105 g

SWITCH

FRONT SWITCH	

FEATURES

TRANSPORTATION LOCK, DIMMABLE	
GLARE-FREE RED LIGHT	

LIGHT MODES

BOOST, LOW POWER, BLINK		

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING
LOW BATTERY WARNING

TECHNOLOGIES







BATTERY AND CASING

BATTERY	3 x AAA, 1.5 V
BATTERY CAPACITY ²	1,250 mAh
RECHARGEABLE	No
CHARGE TIME	-
WATER RESISTANCE	IPX6
OPERATING TEMPERATURE F	RANGE -20 °C to +40 °C

^{1,2} Information on page 66.

EXTEND THE DAY.



PACKAGING

		TEST-IT PACK	
COLOUR	GRAY	RED	
ITEM NUMBER	6105	6106	
GTIN	4029113610551	4029113610650	
PACKAGING DIMENSIONS (W x H x D)	132 x 240 x 66 mm		
PACKAGING WEIGHT	246.8 g		
INCLUDES	Set of batteries, user manual		

ITEM NO.	ITEM
0359	Helmet Band Fixing Clips (4x)
0368	Helmet Connecting Kit Type B
0373	Elastic Headband Green
0375	Elastic Headband Gray
0376	Elastic Headband Red
0377	Elastic Headband Blue

0380	USB Car Charger*
0384	Power Supply 5 V*
0389	USB Power Supply*

^{*} Additional accessories must be purchased for use (Item no. 7784 rechargeable lithium-ion battery)!

55 — SPORT ŒRIES

SEO3

LED

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY ¹ [lm]	_	100	-	15
LIGHTING RANGE ¹ [m]	_	100	_	30
RUN TIME ¹ [h]	_	10	_	40
LED CONFIGURATION	1 x Xtrem	LED		

SWITCH

FRONT SWITCH		

SIZE AND WEIGHT

HEAD DIAMETER	29 mm
WEIGHT (INCLUDING BATTERY)	93 g

FEATURES

TRANSPORTATION LOCK	
GLARE-FREE RED LIGHT	

LIGHT MODES

BOOST, LOW POWER, BLINK	

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING

TECHNOLOGIES







BATTERY AND CASING

BATTERY	3 x AAA, 1.5 V
BATTERY CAPACITY ²	1,250 mAh
RECHARGEABLE	No
CHARGE TIME	_
WATER RESISTANCE	IPX6
OPERATING TEMPERATURE RANG	E-20 °C to +40 °C

^{1,2} Information on page 66.

WITH YOU ALL THE WAY.



PACKAGING

		TEST-IT PACK	
COLOUR	GREEN	ORANGE	
ITEM NUMBER	6103	6104	
GTIN	4029113610353	4029113610452	
PACKAGING DIMENSIONS (W x H x D)	132 x 240 x 66 mm		
PACKAGING WEIGHT	246.8 g		
INCLUDES	Set of batteries, user manual		

ITEM NO.	ITEM
0359	Helmet Band Fixing Clips (4x)
0368	Helmet Connecting Kit Type B
0373	Elastic Headband Green
0375	Elastic Headband Gray
0376	Elastic Headband Red
0377	Elastic Headband Blue


0380	USB Car Charger*
0384	Power Supply 5 V*
0389	USB Power Supply*

^{*} Additional accessories must be purchased for use (Item no. 7784 rechargeable lithium-ion battery)!

57 — SPORT SERIES

NEO

SEE AND BE SEEN. EVEN IN THE DARK.









- 01 Easy operation one switch, three light modes.
- **02** Optimum close-range illumination in Power mode; glare-free reading in Low Power mode and great visibility in Blink mode, e.g. in tra2 c.
- **03** Visible, safe and super bright thanks to wide beam technology oval light shape with illumination achieved by an extremely wide beam (16:9).
- **04** Be seen blinking red rear light built into the battery compartment.
- **05** Lightweight very comfortable to carry.
- **06** For trendsetters and individualists ②ve bright neon colours that attract attention.



59 — SPORT ŒRIES

NEO

LED

	B00ST	POWER	MID POWER	LOW POWER
LUMINOSITY ¹ [lm]	_	90	_	20
LIGHTING RANGE ¹ [m]	_	10	_	10
RUN TIME ¹ [h]	_	10	_	40
LED CONFIGURATION	1 x Xtrem	LED		

SWITCH

FRONT SWITCH		

SIZE AND WEIGHT

HEAD DIAMETER	65 mm	
WEIGHT (INCLUDING BATTERY)	88 g	

FEATURES

WIDE BEAM (16:9)		
REAR LIGHT (RED)		

LIGHT MODES

POWER, LOW POWER, BLINK	

ENERGY MANAGEMENT SYSTEM

ENERGY SAVING

TECHNOLOGIES



BATTERY AND CASING

BATTERY	3 x AAA, 1.5 V	
BATTERY CAPACITY ²	1,250 mAh	
RECHARGEABLE	No	
CHARGE TIME	_	
WATER RESISTANCE	IPX4	
OPERATING TEMPERATURE RANGE -20 °C to +40 °C		



PACKAGING

COLOUR	BLUE	GREEN	PINK	ORANGE	YELLOW
ITEM NUMBER	6110	6111	6112	6113	6114
GTIN	4029113611053	4029113611152	4029113611251	4029113611350	4029113611459
PACKAGING DIMENSIONS (W \times H \times D)	132 x 114 x 59 mm				
PACKAGING WEIGHT	155 g				
INCLUDES	Set of batteries, u	iser manual		<u> </u>	<u> </u>

ITEM NO. ITEM	ITEM NO. ITEM
No accessories available	

^{1,2} Information on page 66.



63 — DIVING

—D14.2 | D14 DAYLIGHT

LED

D14.2 D14 DAYLIGHT SIZE AND WEIGHT

	POWER	LOW POWER	POWER	LOW POWER
LUMINOSITY ¹ [lm]	400	60	300	60
LIGHTING RANGE ¹ [m]	200	80	200	80
RUN TIME ¹ [h]	2	15	2	15
LED CONFIGURATION	1 x High P	ower LED	1 x High P	ower LED

LENGTH (DEFOCUSED)	161.5 mm
HEAD DIAMETER	42 mm
WEIGHT (INCLUDING BATTERY)	233 g

SWITCH

MAGNETIC FRONT SWITCH -For left-handed and right-handed users

FEATURES

D14 DAYLIGHT - Warm White LED 4000-5000 K and CRI 80 D14.2 6000-8000 K and CRI 70

LIGHT MODES

POWER, LOW POWER

ENERGY MANAGEMENT SYSTEM

CONSTANT CURRENT

LOW BATTERY WARNING

TECHNOLOGIES



BATTERY AND CASING

BATTERY	4 x AA, 1.5 V	
BATTERY CAPACITY ²	2,800 mAh	
RECHARGEABLE	No	
CHARGE TIME	-	
WATER RESISTANCE	IPX8, up to 60 m diving depth	
OPERATING TEMPERATURE RANGE -20 °C to +40 °C		

SHINES LONGER THAN THE LONGEST DIVE.



PACKAGING

	D14.2	D14 DAYLIGHT
	GIFT BOX	GIFT BOX
ITEM NUMBER	9114	9114-W
GTIN	4029113911405	4029113911436
$\overline{\text{PACKAGING DIMENSIONS} \left(W \times H \times D \right)}$	245 x 95 x 45 mm	245 x 95 x 45 mm
PACKAGING WEIGHT	378 g	378 g
INCLUDES	Set of batteries, wrist strap, user manual	

ITEM
Signal Cone Type F



^{1,2} Information on page 66.

LEDLENSER HAPPY TO BE IN TOUCH.

Our service is proven to be direct, competent and comprehensive. Even if we receive nothing but positive feedback, we always seek to improve the quality of our services. We greatly appreciate your feedback. Tell us or send us your thoughts.

NOTES

The information regarding package contents, appearance, performance, dimensions and weight corresponds to the knowledge available at the time of publication. In the interest of product improvements, we reserve the right to change package contents, appearance, design and colour without prior notice. Product images may vary from the actual products and may show optional accessories, which can be purchased separately.

- 1) Measurements per ANSI FL1 on the respective setting. If no setting is explicitly indicated, the values refer to Luminosity (lumens/lm) and lighting range (meters/m) on the highest setting and to battery duration (hours/hrs/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light has dierent energy modes, measurement is based on "energy saving mode."
- 2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.
- 3) EP Patent 1880139; US Patent 7,461,960
- 4) Five year warranty from the date of purchase, seven years with online product registration through our website. The warranty applies worldwide; legal warranty rights also apply. It covers defects in materials and workmanship. A warranty period of 24 months applies to the proper function of rechargeable batteries, for the "ATEX" and "i-Series" product series with online registration only. Defects in batteries, holsters, pouches, remote switches, colour filters, imprints or surface coatings are generally excluded from the warranty. For additional product warranty information please visit: ledlenser.com/warranty.
- 5) Charging time varies by hardware used.