

HDS 5/12 C

Unique eco!efficiency mode, simple one-button operation, integrated tanks, on-board practical hose/cable storage, accessory compartment, large wheels and swivel castor – welcome to the hot water compact class!

















1 Efficiency

- ecolefficiency mode economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO2 emissions by 20%.

2 Ease of use

- Intuitive operation with large single-button selector switch.
- Large tank opening with filling chute.

3 Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Storage hooks for power cord and high-pressure hose.

4 Mobility

- Jogger principle with large wheels and steering roller.
- Large integrated handles in the chassis.

TECHNICAL DATA AND EQUIPMENT.





HDS 5/12 C

■ Economical eco!efficiency mode

Technical data		
Order Number		1.272-902.0
EAN code		4054278168845
Current type	Ph / V / Hz	1 / 240 / 50
Flow rate	I/h	500
Pressure	bar / MPa	120 / 12
Max. temperature	°C	80
Power rating	kW	2,9
Consumption fuel oil	kg/h	3,2
Fuel tank	1	15
Weight	kg	93,4
Dimensions (L x W x H)	mm	1060 × 650 × 920

Equipment		
Trigger gun		EASY!Force Advanced
High-pressure hose	m	10 / ID 6, 250 bar
Spray lance	mm	840
SDS system		I
ANTI!Twist		1
Pressure switch control		i
Integral fuel and detergent tank		1
Servo Control		-

■ Included in delivery.





























		Order Number	ID.	Max. working	Longth		Duise	Description
		Order Nulliber	עו	pressure	Length		Price	Description
Standard with unions on both sides	1		l	Love		ı		40 111 4400 450 31111
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m			10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m			15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m			20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 30 m DN 8, including rotary coupling	4	6.110-014.0	ID 8	315 bar	30 m			With rotary coupling, 2 x M 22 x 1.5
High-pressure hose, 15 m DN 10, 220 bar, extension	5	6.110-042.0	ID 10	220 bar	15 m			15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.
High-pressure hose, 20 m DN 10, 220 bar, extension	6	6.110-043.0	ID 10	220 bar	20 m			with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar
High-pressure hose, 25 m DN 10, extension, not rotatable	7	6.110-044.0	ID 10	220 bar	25 m			_
Hose assembly premium DN10 22MPa 40m	8	6.110-045.0	ID 10	220 bar	40 m			4
Hose assembly premium DN12 21MPa 15m	9	6.110-059.0	ID 12	210 bar	15 m			High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 x 1.5 with anti-kink
Hose assembly premium DN12 21MPa 40m	10	6.110-060.0	ID 12	210 bar	40 m			protection.
Hose assembly TR DN10 22MPa 10m	11	6.110-041.0	ID 10	220 bar	10 m			
High-pressure hose, 10 m DN 6,	12	6.110-034.0	ID 6	250 bar	10 m			10 m high-pressure hose (M 22 x 1.5) with kink protection.
AVS trigger gun connector	13	6.110-035.0	ID 6	250 bar	10 m			With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.
High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connec- tion	14	6.110-056.0	ID 6	300 bar	10 m			With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar
Longlife 400 with unions on both s	ides							
High-pressure hose Longlife 400, 30 m DN 8, including rotary coup- ling	15	6.110-023.0	ID 8	400 bar	30 m			With rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 20 m, DN 8, extension	16	6.110-027.0	ID 8	400 bar	20 m			with rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coup- ling	17	6.110-029.0	ID 8	400 bar	15 m			With rotary coupling, 2 x M 22 x 1.5
High-pressure hose 1.5 m, DN 8, including connectors	18	6.110-024.0	ID 8	400 bar	1,5 m			1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22×1.5).
	19	6.110-069.0	ID 8	400 bar	1,5 m			
Food industry version with unions	on bot	h sides	1					
High-pressure hose, 10 m ID 8, suitable for food industry, extension piece	20	6.110-051.0	ID 8	250 bar	10 m			10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.

[■] Included in delivery.

Available accessories.

Extension hose.











		Order Number	ID	Max. working pressure	Length	Pric	ce	Description	
High-pressure hose, 20 m ID 8, suitable for food industry, extension piece	21	6.110-052.0	ID 8	250 bar	20 m			20 m high-pressure hose (DN 8) with swivel coupling. Non- discolouring outer layer for use in the food industry. Con- nectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	A
High-pressure hose 15 m ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey	22	6.110-063.0	ID 6	250 bar	15 m			15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.	
Longlife food industry version with	unior	s on both sides					•		
High pressure hose food DN 8 / 10 m	23	6.110-053.0	ID 8	400 bar	10 m			Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With rotary coupling, 2 x M 22 x 1,5	A
High-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun con- nection	24	6.110-054.0	ID 8	400 bar	20 m			Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With patented AVS connection in the pistol (pivot moun- ted)	

[■] Included in delivery.

Available accessories.

Extension hose.









	I							\neg
		Order Number	Flow rate			Price	Description	
Trigger guns								
EASY!Force Advanced	1	4.118-005.0					Effortless, not energy-sapping: the EASY!Force high-pressure	_
							gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	
Quick connect	1	I .			l			
Quick-fitting pipe union coupler	2	2.115-000.0						П
trapezo								긔
Quick-fitting pipe union plug nipp-	3	2.115-001.0						
le tra					l			

[■] Included in delivery.

Available accessories.

Extension hose.







		Order Number	Max. working pressure	Nozzle size		Price	Description	
Triple nozzles								
Triple nozzle 034	1	4.117-029.0	300 bar	34			Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.	•
Dirt blaster, large								
Dirt blaster - without changeover function	2	4.114-040.0	300 bar	35			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	

[■] Included in delivery.

Available accessories.

Extension hose.































			i				
			Max. working				
		Order Number	_	Length		Price	Description
Rotating spray lances		<u>I</u>	<u>I</u>				
ance 850 mm, rotatable, ergono-	1	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergono-
mic							mic handle for ease of use and protection. Rotatable 360°
lozzle light	2	2.680-002.0		125 mm			under pressure.
ance 250 mm, non-rotatable	3	4.112-027.0	300 bar	250 mm			
550 mm lance, non-rotatable	4	4.112-024.0	300 bar	400 mm			
Rotatable lance, 600 mm, ergono-	5	4.112-007.0	300 bar	600 mm			600 mm stainless steel lance (manual coupling) with ergono-
nic	3	4.112 007.0	300 Bai	000 11111			mic handle for ease of use and protection. Rotatable 360° under pressure.
.050 mm lance, rotatable, ergono-	6	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo-
nic							nomic handle for ease of use and protection. Rotatable 360° under pressure.
ance 1550 mm, rotatable, ergo-	7	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo-
nomic							nomic handle for ease of use and protection. Rotatable 360° under pressure.
ance 2050 mm, rotatable, ergo-	8	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergo-
nomic							nomic handle for ease of use and protection. Rotatable 360° under pressure.
let pipe extension TR 1000 mm	9	4.112-048.0	300 bar	1000 mm			
Double lance		1	1		1		I
Double lance 960 mm	10	2.112-016.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).
Angular spray lance					'		
WC and gutter lance	11	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Spe-
							cially shaped for effective and hygienic cleaning of gutters and toilets.
Flexible spray lance		ſ	ľ				
Flexible lance 1050 mm	12	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.
Articulated joint TR 20	13	4.112-057.0	300 bar				
elescopic spray lance				1			1
elescopic jet pipe	14	4.112-037.0	225 bar	5400 mm			
Restraint belt for telescopic jet pipe	15	6.373-987.0					Convenient strap for relief when working with the telesco- pic spray lance (6.394-690). The burden is optimally distri- buted on the body and longer periods of use are possible.
Gutter cleaner				<u> </u>			botca on the body and longer periods of osc are possible.
Gutter cleaning lance	16	2.112-015.0		960 mm			The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter
							can be cleaned without removing the cover plates.
Indercarriage spray lance	47	4 4 4 2 6 2 2 2		700			Ctainless steel lease for effective and annual sub-
Jnderbody lance	17	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.
Additional handle							
	18	4.321-380.0					
PowerControl spray lance	10	4 112 O4E O					
Pressure regulating jet pipe pa- ckaged Po	19	4.112-045.0					
	21. 1.1						1

[■] Included in delivery.

Available accessories.

Extension hose.









					_		
		Order Number			Price	Description	
Crane lifting kit	•						
Add-on kit suspension crane HDS C	1	2.642-638.0					
Flame monitoring attachment kit							
ABS flame monitor for HDS C	2	2.642-711.0					
Y distributor							
Y distributor	3	4.111-024.0					

[■] Included in delivery.

Available accessories.

Extension hose.

















		Order Number	Flow rate	Nozzle size	Diame- ter	Price	Description
Hard Surface Cleaner FRV 30							
Add-on kit hose attachment	1	2.642-528.0					
Add-on kit dirt trap	2	2.642-532.0					
Hard surface cleaner FR 30 ME							
FR 30 ME surface cleaner	3	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.
Machine-specific nozzle kit for FR							
Nozzle kit for surface cleaners (type-specific) 450 - 500 l/h	4	2.640-482.0	450-500 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h).
Machine-specific nozzle kits for FI	RV						
Nozzle kit 035 for FRV 30	5	2.642-430.0		35			
Hard surface cleaner FRV 30 Me							
Suction hose FRV 30 me	6	4.441-040.0					
FRV 30 ME	7	2.111-012.0					Surface cleaner with integrated waste water pick-up

[■] Included in delivery.

Available accessories.

Extension hose.































			1	1				_
		Order Number				Price	Description	
Nozzle union								Ė
Protection part TR only for replacement	1	4.112-011.0						[
Rotary coupling								
Rotary coupling	2	4.111-021.0					Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	[
Coupling								
Coupler -2xM22x1,5	3	4.111-037.0					Brass double connector for connecting and extending high- pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	
Connector								
Nozzle connector/screw connector	4	4.111-022.0					Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1 \times 1.5 \times $	
	5	4.111-038.0						
Adapter EASY!Lock								
Adapter 1 M22AG-TR22AG	6	4.111-029.0						[
Adapter 2 M22IG-TR22AG	7	4.111-030.0						[
Adapter 3 M22IG-TR22AG	8	4.111-031.0						
Adapter M22 - Swivel	9	4.111-032.0					M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	
Adapter 5 TR22IG-M22AG	10	4.111-033.0						
Adapter 6 TR22IG-M22AG	11	4.111-034.0						[
Adapter 7 M18IG-TR20AG	12	4.111-035.0						[
Adapter 8 TR20IG-M18AG	13	4.111-036.0						[
ADAPTER for replacement TR22IG-	14	4.111-046.0						
M22AG Er								
Flue pipe								
Flue gas adapter	15	4.656-149.0					Flue gas adapter with draught damper for flue pipe connec-	
	16	4.656-080.0					tion (adapter for HDS burners for connection to a stack	
HP detergent injector							system).	Ŧ
Detergent injector for high and low pressure (without nozzles)	17	4.637-032.0					Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Detergent injector for high pressu- re	18	4.637-033.0					Cleaning agent dosage at high pressure 3 - 5 %	[
Machine-specific nozzle kit with or	der no	. 3.637-170			1	1	·	Ė
Nozzle insert trapezoidal thread HDS-GER	19	4.769-009.0						
Nozzle insert with order no. 3.637-	001							Ť
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	20	4.769-003.0					Nozzle insert for detergent injector 3.637-001 for high- pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to 1100 l/h	21	4.769-001.0					For low pressure with machines up to 1.100 l/h	[





		Order Number	Nozzle size		Price	Description
HP nozzle spray angle 0°				<u> </u>		
High-pressure nozzle spray angle °0	1	2.113-001.0	40			High-pressure nozzle with powerful jet for extremely stubborn dirt. $\hfill\Box$
Power nozzle spray angle 15°						
Power nozzle 15034	2	2.113-042.0	34			
Power nozzle spray angle 25°						
Power nozzle spray angle 25°	3	2.113-000.0	34			Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
Nozzle chemical TR for replace- ment 25250	4	2.113-020.0	250			
Power nozzle spray angle 40°						
Power nozzle spray angle 40°	5	2.113-003.0	40			Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.

[■] Included in delivery.

Available accessories.

Extension hose.











	г				I	T	
		Order Number	Nozzle size			Price	Description
Wet blasting attachment (without r	nozzle)			1			<u> </u>
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0					Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0					Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.
Nozzle pack for wet blasting attach	ment						
Nozzle pack TR wet jet set 0035	3	2.112-021.0	35				
Nozzle kit for wet blasting attachment 035	4	2.638-526.0	30				Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.
Boron carbide nozzle							
Boron carbide nozzle, for machines as of 1000 l/h	5	6.415-084.0	6 mm				In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

[■] Included in delivery.

Available accessories.

Extension hose.



















		r	r	T	_	ı		
		Order Number	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Pipe cleaning hose, ID 6								
Hose assembly TR pipe cleaning DN6 max.2	1	6.110-046.0	250 bar					
Pipe cleaning hose, DN 6, 20 m, 220 bar	2	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	3	6.110-047.0	250 bar					
Pipe cleaning nozzle								
Dirt blaster pipe cleaning D21/040	4	4.765-001.0		40	21 mm			
Dirt blaster pipe cleaning D30/040	5	4.765-004.0		40	30 mm			
Nozzle pipe cleaning size 120	6	5.763-089.0		120	24 mm		Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	7	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various je	t 🗆
	8	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.	
	9	5.763-017.0		50	30 mm		30 mm pipe cleaning nozzle with internal thread. Various je directions for environmentally-friendly cleaning of blocked drains and pipes.	
Rotating pipe cleaning nozzle	10	6.415-428.0		50	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	
Drain cleaning dirt blaster D 25/040	11	6.415-944.0		40	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the	
Drain cleaning dirt blaster D 30/040	12	6.415-946.0		40	30 mm		necessary forward movement, as well as convenient hand- ling.	
Drain cleaning dirt blaster D 35/040	13	6.415-948.0		40	35 mm			

[■] Included in delivery.

Available accessories.

Extension hose.





















		Order Number	Flow rate			Price	Description
Cup foam lance		I		1	I.		
Foam lance TR	1	4.112-053.0	350-600 l/h				
Packing complete for 6.394-969.0	2	2.112-018.0					
Tank grey only for replacement 1L	3	6.414-050.0					
Inno Foam Set							
Inno foam kit with detergent injec-	4	2.112-000.0					High-pressure foam system with double lance (foam nozzle
tor							and high-pressure jet for rinsing). For use with mobile and
Inno foam kit	5	2.112-008.0					stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set							
Easy Foam Set with RM injector	6	2.112-010.0					HP foam system for use with. HD/HDS units for cleaning and \Box
Easy foam set	7	2.112-011.0					disinfecting. Foam nozzle for connection to lance and HP
							chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set				1	I.		machine specific fields in this to be ordered separately.
Nozzle kit 055 z. Inno/Easy Set	8	2.111-009.0	500-600 l/h				Optimal adaptation to different machine outputs for econo-
500 - 600 l/h							mic use.
Foam nozzle mounting kit							
Foam nozzle kit	9	2.112-013.0					Foaming agent kit. The foam nozzle is ideal for use in sani-
							tary areas and the food industry and wherever long applica- \Box
				1			tion times are necessary.

[■] Included in delivery.

Available accessories.

Extension hose.

























		Order Number	Length		Price	Description
Hose reel add-on kit						
Hose reel kit, plastic, for HDS 5/12 C - HDS 8/18-4 C	1	2.110-010.0	20 m			
Automatic, self-winding hose reels						
Add-on kit hose reel plastics	2	6.392-074.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.
Add-on kit hose reel	3	6.392-083.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.
Hose reel, automatic, 20 m, painted	4	6.392-106.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.
	5	6.392-105.0	20 m			
Hose reel, automatic, 20 m, stain- less steel	6	6.392-076.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.
ABS hose reel stainless steel	7	6.392-122.0	20 m			High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.
Add-on kit hose reel TR 40m	8	6.392-442.0	40 m			
Swivel holder	9	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.
ABS wall fastening stainless steel	10	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.
Anbausatz Schlauchtrommel autom	atik			•	•	-
Add-on kit automatic hose reel HDS-C	11	2.110-012.0				
Add-on kit hose reel	12	2.110-013.0				

[■] Included in delivery. □ Available accessories. ▲ Extension hose.











		Order Number	Flow rate		Price	Description	
Push-on washing brush							
Push-on washing brush	1	4.762-497.0				With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles.	
Push-on wash brush, M 18 x 1.5	2	4.113-001.0				Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	
Rotating washing brush							
	3	4.113-004.0	500-800 l/h				
	4	4.113-003.0	500-800 l/h				

[■] Included in delivery.

Available accessories.

Extension hose.



















		Order Number	Length	Diameter		Price	Description	
Geka coupling								
With hose nozzle, R 1/2"	1	6.388-461.0					with hose liner	
With hose nozzle, R 3/4"	2	6.388-455.0						
With hose nozzle, R 1"	3	6.388-465.0						
Hose coupling	4	6.388-458.0					with female thread	
Suction filter								
Water filter	5	6.414-956.0						
Suction filter with check valve	6	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Fine-mesh water filter								
Fine-mesh water filter with adapter	7	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	
Fine-mesh water filter, 100 $\mu m,R$ 1"	8	2.638-270.0					Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	
Water supply hose			1					
Water supply hose	9	4.440-038.0	7,5 m				NW 13 R1" / R 3/4", up to 30 °C	
	10	4.440-207.0	7,5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	

[■] Included in delivery.

Available accessories.

Extension hose.