



HD 9/23 De

For independent use in areas with poor infrastructure: the HD 9/23 De diesel-powered, mobile cold water high-pressure cleaner with 230 bar pressure for high cleaning performance.









1 Maximum independence

- Fitted with a reliable Honda or Yanmar motor for use without an external power supply.
- Can suck up water e.g. from lakes or ponds and use it for cleaning.

2 Optimum ease of use

- The ergonomic frame concept makes transport on uneven ground easier.
- Storage options for all accessory parts directly on the machine.



3 Highly versatile

- Optional cage frame with eyelets for crane loading and reliable protection of the machines.
- Hose reel attachment kit for shorter set-up available as an optional extra.

4 For the toughest jobs

- Robust basic frame for daily use in tough conditions.
- Large water filter to protect the pump.

TECHNICAL DATA AND EQUIPMENT.

KARCHER



HD 9/23 De

- Economical diesel engine with a convenient electro start
- Servo Control function on the high pressure lance allows
- variable water pressure and water flow Automatic speed reduction

| 1 |
|---|
| |
| |
| |
| |
| |
| |
| |
| |

HD 9/23 De, 1.187-907.0, 2018-03-02



| | | Order Number | ID | Max. working pressure | Length | Price | Description |
|--|-------|------------------|------|--------------------------|--------|-------|---|
| Standard with unions on both sides | | | | 1 | II | | |
| High-pressure hose, 10 m DN 8, AVS trigger gun connector | 1 | 6.110-031.0 | ID 8 | 315 bar | 10 m | | 10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar. |
| High-pressure hose, 20 m DN 8, AVS trigger gun connector | 2 | 6.110-032.0 | ID 8 | 315 bar | 20 m | | 20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar. |
| High-pressure hose, 15 m DN 8, AVS trigger gun connector | 3 | 6.110-030.0 | ID 8 | 315 bar | 15 m | | 15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar. |
| onglife 400 with unions on both si. | des | | | | | | |
| High-pressure hose Longlife 400, 30 m DN 8, including rotary coup- ing | 4 | 6.110-023.0 | ID 8 | 400 bar | 30 m | | With rotary coupling, 2 x M 22 x 1.5 |
| High-pressure hose Longlife 400, 20 m, DN 8, extension | 5 | 6.110-027.0 | ID 8 | 400 bar | 20 m | | with rotary coupling, 2 x M 22 x 1.5 |
| High-pressure hose Longlife 400, 15 m, DN 8, including rotary coup- ling | 6 | 6.110-029.0 | ID 8 | 400 bar | 15 m | | With rotary coupling, 2 x M 22 x 1.5 |
| High-pressure hose 1.5 m, DN 8, ncluding connectors | 7 | 6.110-024.0 | ID 8 | 400 bar | 1,5 m | | 1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink pro- tection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22×1.5). |
| | 8 | 6.110-069.0 | ID 8 | 400 bar | 1,5 m | | |
| High-pressure hose packaged | 9 | 6.110-038.0 | ID 8 | 400 bar | 10 m | | |
| onglife food industry version with | unior | is on both sides | | | | | |
| High pressure hose food DN 8 / 10 m | 10 | 6.110-053.0 | ID 8 | 400 bar | 10 m | | Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With rotary coupling, 2 x M 22 x 1,5 |

Included in delivery. □ Available accessories.

Extension hose.

KARCHER

| MISSING PICTURE: | MISSING PICTURE: | MISSING PICTURE: | MISSING PICTURE: |
|-------------------|-------------------|-------------------|-------------------|
| M:\print\4118005_ | M:\print\4118007_ | M:\print\2115000_ | M:\print\2115001_ |
| std_13_75631_acc. | std_1_70000_acc. | std_2_77783_acc. | std_1_77787_acc. |
| tif | tif | tif | tif |
| 1 | 2 | 3 | 4 |

| | | Order Number | Flow rate | | | Price | Description |
|---|---|--------------|--------------|--|---|-------|--|
| Trigger guns | | <u>I</u> | <u>I</u> | | 1 | 1 | |
| Extended easy press trigger gun | 1 | 4.118-005.0 | | | | | Extended easy press high-pressure trigger gun for high- pressure hoses with rotating connector. |
| Servo Control | | | | | | | |
| Servo control | 2 | 4.118-008.0 | 750-1100 l/h | | | | |
| Quick connect | | | | | | | |
| Quick-fitting pipe union coupler trapezo | 3 | 2.115-000.0 | | | | | C |
| Quick-fitting pipe union plug nipp- le tra | 4 | 2.115-001.0 | | | | | E |

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill A$ Extension hose.

MISSING PICTURE: M:\print\2113000_ std_1_74150_acc. tif 1-4

| | | Order Number | Nozzle size | | | Price | Description |
|---|---|--------------|-------------|---|--|-------|--|
| Power nozzle spray angle 25° | | 1 | Ľ | Ľ | | | · · · · · · |
| | 1 | 2.113-010.0 | 48 | | | | 1 |
| Nozzle chemical TR for replace- ment 25250 | 2 | 2.113-020.0 | 250 | | | | |
| HP nozzle spray angle 0° | | | | | | | |
| High-pressure nozzle spray angle °0 | 3 | 2.113-034.0 | 50 | | | | High-pressure nozzle with powerful jet for extremely stub- born dirt. |
| Power nozzle spray angle 40° | | | | | | | |
| Power nozzle spray angle 40° | 4 | 2.113-054.0 | 50 | | | | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. |

| MISSING PICTURE: MISSIN M:\print\4112000_ M:\print std_1_75368_acc. std_1_ tif tif 1 2 MISSING PICTURE: MISSING M:\print\4112048_ MISSING std_1_87270_acc. dd_1_2 tif 9 | | t\411 78299 G PIC t\476 | 2027_ M: 9_acc. sto tif 3 TURE: | S. | . M:\print std_1_7 tif 4 MISSING M:\print | std_1_75345_acc. tif 4 MISSING PICTURE: M:\print\2642305_ std_2_28415_acc. tif | | | CTURE: 12006_ :3_acc. CTURE: 60245_ 6_acc. | MISSING PICTURE: M:\print\4112018_ std_1_78288_acc. tif 6 MISSING PICTURE: M:\print\4321380_ std_1_75124_acc. tif 13 | MISSING PICTURE M:\print\4112021 std_1_78295_acc tif 7 | _ |
|---|-----------|----------------------------------|---|-----------------------------|--|---|--|-------|---|---|---|----|
| | | | Order Numb | Max. working er pressure | Length | | | Price | Descrip | tion | | |
| Rotating spray lances | | | 1 | | | | | | 1 | | | |
| 1050 mm lance, rotatable, mic | , ergono- | 1 | 4.112-000.0 | 300 bar | 1050 mm | | | | | m stainless steel lance (mar andle for ease of use and p ressure. | | |
| Lance 250 mm, non-rotata | able | 2 | 4.112-027.0 | 300 bar | 250 mm | | | | | | | |
| 550 mm lance, non-rotata | ble | 3 | 4.112-024.0 | 300 bar | 400 mm | | | | | | | |
| Rotatable lance, 600 mm, mic | ergono- | 4 | 4.112-007.0 | 300 bar | 600 mm | | | | | stainless steel lance (manu dle for ease of use and pro- ressure. | |)- |
| Lance 850 mm, rotatable, mic | ergono- | 5 | 4.112-006.0 | 300 bar | 840 mm | | | | 850 mm | stainless steel lance (manu dle for ease of use and pro | |)- |
| Lance 1550 mm, rotatable nomic | e, ergo- | 6 | 4.112-018.0 | 300 bar | 1550 mm | | | | 1550 m | m stainless steel lance (mar andle for ease of use and p | | |
| Lance 2050 mm, rotatable nomic | e, ergo- | 7 | 4.112-021.0 | 300 bar | 2050 mm | | | | 2050 m | m stainless steel lance (mar andle for ease of use and p | | |
| Jet pipe extension TR 100 |)0 mm | 8 | 4.112-048.0 | 300 bar | 1000 mm | | | | under pi | C3501C. | | |
| Angular spray lance | | | 1 | | | | | | | | | _ |
| WC and gutter lance | | 9 | 4.112-029.0 | | | | | | | s steel lance WC and gutter aped for effective and hyg ets. | | |
| Telescopic spray lance | | | | | | | | | | | | |
| Restraint belt for telescop pipe | ic jet | 10 | 6.373-987.0 | | | | | | pic spra | ent strap for relief when w y lance (6.394-690). The bu n the body and longer perio | urden is optimally distri- | |
| Gutter cleaner | | | | | 1 | | | | | | | |
| Gutter cleaning lance | | 11 | 2.112-015.0 | | 960 mm | | | | of the sh | e is suited for cleaning of a nape of the lance and the s leaned without removing t | pecial nozzle the gutter | |
| Undercarriage spray lance | 2 | | | | | | | · | | | | |
| Underbody lance | | 12 | 4.112-032.0 | | 700 mm | | | | | s steel lance for effective a rch cleaning. Without high- | | |
| Additional handle | | 10 | 4 224 200 0 | | | | | | 1 | | | |
| Included in delivery. | | | 4.321-380.0 e accessories. | ▲ Extension h | 950 | | | | 1 | | | |

KARCHER

| MISSING PICTURE: M:\print\4405048_ dd_1_21605_acc.tif | MISSING PICTURE: M:\print\2637008_ std_1_79626_acc. tif |
|---|--|
| 1 | 2 |

| | | Order Number | | | | Price | Description | |
|------------------------------|---------|----------------|----------------|------|--|-------|-------------|--|
| Y distributor | | | | | | | | |
| Y distributor | 1 | 4.111-024.0 | | | | | | |
| Cage frame attachment kit | | | | | | | | |
| Add-on kit frame Cage breit | 2 | 2.637-007.0 | | | | | | |
| ■ Included in delivery. □ Av | ailable | e accessories. | ▲ Extension ho | ose. | | | | |

| MISSING PICTURE: M:\print\Suction- hose_plast_ID27_ dd_1_11015_acc.tif 2, 10 MISSING PICTURE: M:\print\2642430_ std_1_33539_acc. tif | \print\Suction- M:\print\2642528 se_plast_ID27_ std_1_34382_acc _1_11015_acc.tif tif 10 3 SSING PICTURE: MISSING PICTURE: \print\2642430_ M:\print\2111012 1_1_33539_acc. tif | | | M:\p std_ tif 4 MISS M:\p | 5ING PICTURE print\2642532 1_34388_acc 5ING PICTURE print\2111024 1_75353_acc | 2_ M:\print' std_1_7 tif 5 | PICTURE: \2111010_ 5357_acc. | M:\p | 5ING PIC print\21 1_7538 | 11013_ | MISSING PICTURE: M:\print\2111023_ std_1_75355_acc. tif 7 | MISSING PICTURE M:\print\2640442 dd_1_20652_acc | 2_ |
|---|---|---------|------------|--|--|-------------------------------------|------------------------------------|------|--------------------------------|-----------------------|--|---|----|
| 9 | 11 | | | 12 | | | | | | | | | |
| | | | | | | | | | | 1 | | | |
| | | | Order N | umber | Flow rate | Nozzle size | Diame- ter | | Price | Descript | tion | | |
| Hard Surface Cleaner FR | V 30 | | | | | | | | | | | | |
| Add-on kit rubber lip | | 1 | 2.642-91 | .0.0 | | | | | | suction p amount o | oth floors indoors. The sque performance of the FRV 30 of water remaining. This m w minutes. | and minimises the | |
| Extension hose 5 m | | 2 | 4.440-93 | 9.0 | | | | | | 5m exter | nsion hose for FRV 30. Con | nection sleeve included. | |
| Add-on kit hose attachm | nent | 3 | 2.642-52 | 8.0 | | | | | | | | | |
| Add-on kit dirt trap | | 4 | 2.642-53 | | | | | | | | | | |
| FRV 30 | | 5 | 2.111-01 | 0.0 | | | | | | Surface of | cleaner with integrated was | ste water pick-up | |
| Hard surface cleaner FR FR 30 ME surface cleane | | 6 | 2.111-01 | .3.0 | | | 300 mm | | | double c | er resistant stainless steel s eramic bearings, non-mark nose connection. Ideal for in | ing swivel castors and | |
| Hard Surface Cleaner FR | 50 | | | | | | | | | | | | |
| FR 50 surface cleaner | | 7 | 2.111-02 | .3.0 | | | 500 mm | | | mm worl mic bear | er resistant stainless steel s king width. Ideal for large a ings, push handle, non-mai it dosing system. | areas.With double cera- | |
| Machine-specific nozzle | 1 | | | 1 | | 1 | 1 1 | 1 | | 1 | | | |
| Nozzle kit for surface cle (type-specific) 850 - 110 | 00 l/h | 8 | 2.640-44 | 2.0 | 850-1100 l/h | | | | | | it includes power nozzles a cleaners (850 to 1100 l/h). | and unions. For Kärcher | |
| Machine-specific nozzle | | | 2642 42 | 20 | | 50 | 1 1 | 1 | | 1 | | | |
| Nozzle kit 050 for FRV 3 | | 9 | 2.642-43 | 3.0 | | 50 | | | | | | | |
| Suction hose FRV 30 me | | 10 | 4.441-04 | 0.0 | | | | | | 1 | | | |
| FRV 30 ME | | 10 | 2.111-01 | | | | | | | Surface | cleaner with integrated was | ste water pick-un | |
| Surface Cleaner FR 50 M | e | 11 | | | I | 1 | | | | 30.1000 0 | inter inter integrated wa | ere mater preit op | |
| | | 12 | 2.111-02 | 4.0 | | | | | | | | | |
| Included in delivery | /. □ AV | ailable | e accessor | ies. | ▲ Extension h | ose. | | | | | | | |



| M:\print\4112011_ M:\printstd_1_77654_acc. tif tif 1 2 MISSING PICTURE: MISSIN M:\print\4111031_ M:\printstime | | ISSING PICTURE: :\print\4111032_ d_1_72041_acc. | | | A111021_ M:\print\4111037_ 301_acc. std_1_72044_acc. tif 3 PICTURE: MISSING PICTURE: 111032_ M:\print\4111033_ | | MISSING PICTURE: M:\print\4111022_ std_1_77657_acc. tif 4 MISSING PICTURE: M:\print\4111034_ std_1_72036_acc. tif 11 | | | CTURE: 11038_ ;7_acc. CTURE: 11035_ ;1_acc. | MISSING PICTURE: M:\print\4111029_ std_1_72030_acc. tif 6 MISSING PICTURE: M:\print\4111036_ std_1_72049_acc. tif 13 | MISSING PICTURE: M:\print\4111030_ std_1_72021_acc. tif 7 MISSING PICTURE: M:\print\4111046_ std_1_81511_acc. tif 14 | |
|--|------------|---|------------------------------|-------|--|--|---|--|-------|--|---|---|-------|
| | | | Order N | umber | | | | | Price | Descrip | tion | | |
| Nozzle union Protection part TR only t | for ropla | 1 | 4.112-0 | 11.0 | | | | | 1 | Ì | | | |
| cement | or repid- | 1 | 4.112-0 | 1 I.U | | | | | | | | | |
| Rotary coupling Rotary coupling Coupling | | 2 | 4.111-0 | 21.0 | | | | | | high-pre | rotary coupling prevents to ssure hoses for ease of use grip protection. | | 5 |
| Coupling | | | I | | | | <u> </u> | | 1 | | | | |
| Coupler -2xM22x1,5 | | 3 | 4.111-03 | 37.0 | | | | | | | uble connector for connect hoses. With rubber protec | | |
| Connector | | | | | L | | | | | 1 x 2.0 m | | | |
| Nozzle connector/screw | connector | 4 | 4.111-03 | 22.0 | | | | | | pressure ger gun | onnector/screw connector e nozzles and accessories to (with nozzle connector). Co M 18 x 1.5. | the high-pressure trig- | |
| | | 5 | 4.111-0 | 38.0 | | | | | | und Int | 10 x 1.0. | | |
| Adapter EASY!Lock | | | I | | | | 1 1 | | 1 | 1 | | | |
| Adapter 1 M22AG-TR22 | | 6 7 | | | | | | | | - | | | |
| Adapter 3 M22IG-TR22A | | 8 | 4.111-0 | | | | | | | + | | | |
| Adapter M22 - Swivel | | 9 | 4.111-03 | | | | | | | high-pre | ,5female and swivel conne ssure hoses with AVS conn ic lance with a high-pressu | ection or for usage of th | the r |
| Adapter 5 TR22IG-M22A | | 10 | | | | | | | | | | | |
| Adapter 6 TR22IG-M22A | | 11 | 4.111-0 | | | | | | | _ | | | |
| Adapter 7 M18IG-TR20A | | 12 | 4.111-0 | | | | + | | | - | | | |
| Adapter 8 TR20IG-M18A ADAPTER for replacement M22AG Er | | 13 14 | 4.111-0 | | | | | | | 1 | | | |
| HP detergent injector | | | | | L | | | | | | | | |
| Detergent injector for hi | ozzles) | 15 | 4.637-0 | | | | | | | dosage. | nt injector for independent Maximum dosage about 15 | %. | |
| Detergent injector for hi re | gn pressu- | 16 | 4.637-03 | 33.0 | | | | | | Cleaning | agent dosage at high pres | sure 3 - 5 % | |
| Machine-specific nozzle Nozzle insert trapezoida HDS-GER | 1 | der no 17 | . 3.637-17 4.769-0 | | | | | | | | | | |
| Nozzle insert with order | no. 3.637- | 001 | 1 | | | | | | 1 | | | | |
| Nozzle insert for Order I 001, high-pressure for n | No. 3.637- | 18 | 4.769-0 | 03.0 | | | | | | pressure | nsert for detergent injector detergent application. For | high-pressure cleaners | s E |
| up to 1100 l/h. | ated up to | 19 | 4.769-0 | 24.0 | | | + | | | | vater flow rate up to 1100 pressure with machines up | | + |

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.

KARCHER

| MISSING PICTURE: | MISSING PICTURE: | MISSING PICTURE: |
|-------------------|-------------------|-------------------|
| M:\print\4117023_ | M:\print\4113006_ | M:\print\4114027_ |
| std_1_68531_acc. | std_1_10496_acc. | std_1_68527_acc. |
| tif | tif | tif |
| | | |
| | | |
| 1 | 2 | 3 |

| | | Order Number | Max. working pressure | Nozzle size | | Price | Description | |
|--|---|--------------|--------------------------|-------------|--|-------|--|--|
| Triple nozzles | | | | | | | | |
| Triple nozzle 050 | 1 | 4.117-037.0 | 300 bar | 50 | | | Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5. | |
| Angle vario nozzle 0°-90° | | | | | | | | |
| Spezial nozzle 0005 | 2 | 4.113-007.0 | | 50 | | | Variable angle nozzle for spray angle adjustment from 0° to 90° . For easy adjustment to all kinds of soiling and surfaces. | |
| Dirt blaster, large | | | | | | | | |
| Dirt blaster - without changeover function | 3 | 4.114-027.0 | 300 bar | 50 | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. | |

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.

| MISSING PICTURE: | MISSING PICTURE: |
|-------------------|--------------------|
| M:\print\4762010_ | M:\print\6415084_ |
| dd_1_3615_acc.tif | dd_1_21363_acc.tif |
| 1-2 | 3 |

| | | Order Number | Nozzle size | | | Price | Description |
|---|---------|----------------|----------------|------|--|-------|---|
| Wet blasting attachment (without r | nozzle) | | | | | | |
| Wet blasting attachment with flow control (without nozzles) | 1 | 4.115-000.0 | | | | | Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet. |
| Wet blasting attachment without flow control (nozzles not included) | 2 | 4.115-006.0 | | | | | Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet. Without flow control. |
| Boron carbide nozzle | | | | | | | |
| Boron carbide nozzle, for machi- nes as of 1000 l/h | 3 | 6.415-084.0 | 6 mm | | | | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. |
| ■ Included in delivery. □ Av | ailable | e accessories. | ▲ Extension ho | ose. | | | |

KARCHER



MISSING PICTURE: M:\print\6415944_ . std_1_46839_acc.

MISSING PICTURE: M:\print\5763015_ dd_1_88507_acc.tif dd_1_6394_acc.tif

7-8

MISSING PICTURE: M:\print\5763017_

9



| | | Order Number | Max. working pressure | Nozzle size | Diame- ter | Price | Description | | |
|---|----|--------------|-----------------------|-------------|---------------|-------|--|-----|--|
| Pipe cleaning hose, ID 6 | | | | | | | | | |
| Hose assembly TR pipe cleaning DN6 max.2 | 1 | 6.110-046.0 | 250 bar | | | | | | |
| Pipe cleaning hose, DN 6, 20 m, 220 bar | 2 | 6.110-008.0 | 250 bar | | | | 20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle). | | |
| Hose assembly TR pipe cleaning DN6 max.2 | 3 | 6.110-047.0 | 250 bar | | | | | | |
| Pipe cleaning nozzle | | | | | | | | | |
| Drain cleaning dirt blaster D 25/060 | 4 | 6.415-945.0 | | 60 | 25 mm | | The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the | | |
| Drain cleaning dirt blaster D 30/060 | 5 | 6.415-947.0 | | 60 | 30 mm | | necessary forward movement, as well as convenient hand- ling. | | |
| Drain cleaning dirt blaster D 35/060 | 6 | 6.415-949.0 | | 60 | 35 mm | | | | |
| Pipe cleaning nozzle | 7 | 5.763-015.0 | | 55 | 16 mm | | 16 mm pipe cleaning nozzle with internal thread. Various je | t 🗆 | |
| | 8 | 5.763-016.0 | | 60 | 16 mm | | directions for environmentally-friendly cleaning of blocked drains and pipes. | | |
| | 9 | 5.763-017.0 | | 50 | 30 mm | | 30 mm pipe cleaning nozzle with internal thread. Various je directions for environmentally-friendly cleaning of blocked drains and pipes. | | |
| Rotating pipe cleaning nozzle | 10 | 6.415-428.0 | | 50 | 16 mm | | Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blo- cked drains and pipes. | | |



| | | Order Number | Flow rate | | Price | Description |
|--|---|--------------|--------------|--|-------|---|
| Cup foam lance | | | | | | · · · · · |
| Foam lance TR | 1 | 4.112-055.0 | 900-2500 l/h | | | [|
| Packing complete for 6.394-968.0 | 2 | 2.112-017.0 | | | | [|
| Tank grey only for replacement 1L | 3 | 6.414-050.0 | | | | |
| Tank 1L | 4 | 6.414-954.0 | | | | |
| Inno Foam Set | | | | | | |
| Inno foam kit with detergent injector | 5 | 2.112-000.0 | | | | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection. |
| Easy Foam Set | | | | | | |
| Easy Foam Set with RM injector | 6 | 2.112-010.0 | | | | HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. |
| Nozzle kits for Inno/Easy Foam Set | | | | | | |
| Nozzle kit 090 Inno/Easy kit 700 - 1000 I/h | 7 | 2.111-019.0 | 700-1000 l/h | | | Nozzle kit contains Kärcher power nozzles and nozzle in- serts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance. |
| Foam nozzle mounting kit | | | | | | |
| Foam nozzle kit | 8 | 2.112-013.0 | | | | Foaming agent kit. The foam nozzle is ideal for use in sani- tary areas and the food industry and wherever long applica- tion times are necessary. |



| M:\print\1187907 std_4_79605_acc. tif 1 MISSING PICTURE: / M:\print\6392442 / std_1_81488_acc. tif | MISSINC M:\print std_1_4 tif 2 MISSINC M:\print dd_1_1: 9-10 | 1639 1695 G PIC | 02975_ M: 5_acc. stc tif 3 TURE: | SSING PICTURE: .print\6392965_ [_2_41697_acc. | MISSING F M:\print\2 dd_2_104 4 | M:\p | SING PIC orint\63 1_7829 | 92105_ | MISSING PICTURE: M:\print\6391421_ std_1_63694_acc. tif 6 | MISSING PICTURE M:\print\2641866 dd_1_21600_acc.1 | _ |
|---|--|-----------------------|---|---|---|----------|--------------------------------|-----------------------|---|---|---|
| | | | Order Numbe | er Length | | | Price | Descrip | tion | | |
| Hose reel add-on kit | | | | | | | | | | | - |
| Add-on kit hose reel | | 1 | 2.110-004.0 | 30 m | | | | | | | |
| Automatic, self-winding ho | se reels | | | | | | | | | | |
| Add-on kit hose reel plastic | CS | 2 | 6.392-074.0 | 20 m | | | | | tic hose reel for 20 m high hade from powder-coated stric. | | |
| Add-on kit hose reel | | 3 | 6.392-083.0 | 20 m | | | | | tic hose reel for 20 m high sists of stainless steel, the | | |
| Hose reel, automatic, 20 m ted | , pain- | 4 | 6.392-106.0 | 20 m | | | | | ic hose reel of durable pla for 20 m high-pressure ho | | |
| | | 5 | 6.392-105.0 | 20 m | | | | | | | |
| Hose reel, automatic, 20 m less steel | , stain- | 6 | 6.392-076.0 | 20 m | | | | | tic stainless steel hose reel for 20 m high-pressure ho | | |
| ABS hose reel stainless ste | el | 7 | 6.392-122.0 | 20 m | | | | use in th a corros | ade, automatic steel hose r ne food industry. The mate sion-resistant, watertight o ion for HP hoses with nipp | rial and finish provide for capsuled sprong drive. | |
| Add-on kit hose reel TR 40 | m | 8 | 6.392-442.0 | 40 m | | | | | | | |
| Swivel holder | | 9 | 2.639-931.0 | | | | | maximu Rotatabl | older for automatic hose r m action radius and flexibi e 120°. Galvanised steel. | ility of high-pressure hose | |
| ABS wall fastening stainles | s steel | 10 | 2.641-867.0 | | | | | 866). Th | ng wall bracket made of hi is makes maximum flexibi when working with the H | lity and convenience | |



| MISSING PICTURE: | MISSING PICTURE: | MISSING PICTURE: | MISSING PICTURE: |
|-------------------|-------------------|-------------------|-------------------|
| M:\print\4107052_ | M:\print\4107053_ | M:\print\4107054_ | M:\print\6390030_ |
| std_1_43071_acc. | std_1_43068_acc. | std_1_43065_acc. | std_1_24645_acc. |
| tif | tif | tif | tif |
| | | | |
| | | | |
| 1 | 2-3 | 4 | 5-7 |

| | | Order Number | Flow rate | Water feed temperature | Length | Length | Price | Description | |
|------------------------------------|---|--------------|-----------|---------------------------|--------|--------|-------|--|---|
| Solar cleaning - telescopic lances | | | | 1 | | | | | |
| Telescopic rod complete 14m | 1 | 4.110-002.0 | | 60 °C | | | | Full carbon telescopic rod for maximum rigidity with mini- mal weight. With 14 m max. reach and practical quick- release couplings for easy extension and retraction. | |
| Telescopic rod complete 10m CFK | 2 | 4.110-007.0 | | 60 °C | | | | | |
| Telescopic rod complete 10m | 3 | 4.110-003.0 | | 60 °C | | | | Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 10 m max. reach and practical quick-release couplings for easy extensi- on and retraction. | _ |
| iSolar TL 7 H (without hose) | 4 | 4.110-004.0 | | 60 °C | | | | Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 7.2 m max. reach and practical quick-release couplings for easy extensi- on and retraction. | |
| Hose solar | 5 | 6.392-978.0 | | 155 °C | | | | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod | |
| | 6 | 6.392-977.0 | | 155 ℃ | | | | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod | |
| | 7 | 6.392-976.0 | | 155 ℃ | | | | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod | |

| MISSING PICTURE: | MISSING PICTURE: | MISSING PICTURE: |
|--------------------|-------------------|-------------------|
| M:\print\Push_ | M:\print\4113002_ | M:\print\4113003_ |
| on_wash_brush_ | std_2_10461_acc. | std_1_77677_acc. |
| dd_1_10476_acc.tif | tif | tif |
| | | |
| | | |
| 1 | 2 | 3 |

| | | Order Number | Flow rate | | | Price | Description | |
|--------------------------------|---------|----------------|----------------|------|--|-------|---|--|
| Push-on washing brush | | | | | | | | |
| Push-on wash brush, M 18 x 1.5 | 1 | 4.113-001.0 | | | | | Push-on wash brush for universal use. Simply push on to lance. Connector: M 18×1.6 . | |
| Rotating washing brush | | | | | | | | |
| | 2 | 4.113-002.0 | 800-1300 l/h | | | | | |
| | 3 | 4.113-005.0 | 800-1300 l/h | | | | | |
| ■ Included in delivery. □ Av | ailable | e accessories. | ▲ Extension ho | ose. | | | | |

KARCHER



MISSING PICTURE: M:\print\6414956_ std_1_27849_acc.

| MISSING PICTURE: |
|-------------------|
| M:\print\4730012_ |
| dd_1_5368_acc.tif |
| |
| |

4

MISSING PICTURE: M:\print\4730102_ dd_1_20693_acc.tif std_1_27790_acc. tif

5

MISSING PICTURE: M:\print\4440038_

6



| | | Order Number | Length | Diameter | | Price | Description | |
|--|---|--------------|--------|----------|---|-------|--|---|
| Geka coupling | | | | | 1 | | | - |
| With hose nozzle, R 3/4" | 1 | 6.388-455.0 | | | | | with hose liner | |
| Hose coupling | 2 | 6.388-458.0 | | | | | with female thread | |
| Suction filter | | | | | | | | |
| Water filter | 3 | 6.414-956.0 | | | | | | |
| Suction filter with check valve | 4 | 4.730-012.0 | | | | | Brass suction filter suitable for ponds, storage tanks, etc. With check valve. | |
| Fine-mesh water filter | | | | | | | | |
| Fine-mesh water filter with adap- ter | 5 | 4.730-102.0 | | | | | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contai ned in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1". | |
| Water supply hose | | | | | | | | |
| Water supply hose | 6 | 4.440-038.0 | 7,5 m | | | | NW 13 R1" / R 3/4", up to 30 °C | |
| Backflow check valve | | | | | | | | |
| Backflow preventer | 7 | 2.641-374.0 | | | | | To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection | |