



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

Copydex Adhesive

SDS No. : 194625  
V003.0

Revision: 20.04.2020

printing date: 17.04.2021

Replaces version from: 19.12.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Copydex Adhesive

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Adhesive

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Respiratory sensitizer	Category 1
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

#### 2.2. Label elements

##### Label elements (CLP):

**Hazard pictogram:**

Contains

Rubber, natural

**Signal word:**

Danger

**Hazard statement:**

H317 May cause an allergic skin reaction.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H412 Harmful to aquatic life with long lasting effects.

**Supplemental information**

Contains preservative(s): 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

**Precautionary statement:**

P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.

**Precautionary statement:  
Prevention**

P261 Avoid breathing mist/vapours.  
 P273 Avoid release to the environment.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves.

**Precautionary statement:  
Response**

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

**Precautionary statement:  
Disposal**

P501 Dispose of contents/container in accordance with national regulation.

**2.3. Other hazards**

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## SECTION 3: Composition/information on ingredients

**3.2. Mixtures****General chemical description:**

Adhesive

**Base substances of preparation:**

Natural rubber

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Rubber, natural 9006-04-6	232-689-0	40- 60 %	Skin Sens. 1 H317 Resp. Sens. 1 H334
ammonia, aqueous solution 1336-21-6	215-647-6 01-2119488876-14	0,1- < 1 %	Met. Corr. 1 H290 Skin Corr. 1B H314 Aquatic Acute 1 H400 Aquatic Chronic 2 H411 Eye Dam. 1 H318 STOT SE 3 H335 Acute Tox. 4; Oral H302
thiram 137-26-8	205-286-2 01-2119492301-45	0,01- < 0,1 %	Acute Tox. 4; Inhalation H332 Acute Tox. 4; Oral H302 STOT RE 2 H373 Eye Irrit. 2 H319 Skin Sens. 1 H317 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 Skin Irrit. 2 H315 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10
2-methylisothiazol-3(2H)-one 2682-20-4	220-239-6 01-2120764690-50	0,0001- < 0,0015 % ( 1 ppm- < 15 ppm)	Aquatic Chronic 1 H410 Skin Sens. 1A H317 Acute Tox. 2; Inhalation H330 Acute Tox. 3; Oral H301 Acute Tox. 3; Dermal H311 Eye Dam. 1 H318 Aquatic Acute 1 H400 Skin Corr. 1B H314 M factor (Acute Aquat Tox): 10

**For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.**

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

**Inhalation:**

Move to fresh air, consult doctor if complaint persists.  
Delayed effects possible after inhalation.

**Skin contact:**

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

**Eye contact:**

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

**Ingestion:**

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

May cause an allergic skin reaction.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

**5.2. Special hazards arising from the substance or mixture**

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO<sub>2</sub>) can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus.

Wear protective equipment.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Danger of slipping on spilled product.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Ensure that workrooms are adequately ventilated.

Avoid skin and eye contact.

Hygiene measures:

- Do not eat, drink or smoke while working.
- Wash hands before work breaks and after finishing work.

**7.2. Conditions for safe storage, including any incompatibilities**

- Store only in the original container.
- Keep container tightly sealed.
- Store frost-free.
- Temperatures between + 5 °C and + 30 °C
- Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

**7.3. Specific end use(s)**

Adhesive

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational Exposure Limits**

Valid for  
Great Britain

None

**Occupational Exposure Limits**

Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Rubber, natural 9006-04-6 [NATURAL RUBBER LATEX (AS INHALABLE ALLERGENIC PROTEINS)]		0,0001	Time Weighted Average (TWA):		IR_OEL
Thiram 137-26-8 [THIRAM (ISO) (INHALABLE FRACTION AND VAPOUR)]		0,05	Time Weighted Average (TWA):		IR_OEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
ammonia, aqueous solution 1336-21-6	aqua (freshwater)		0,001 mg/l				
ammonia, aqueous solution 1336-21-6	aqua (marine water)		0,001 mg/l				
ammonia, aqueous solution 1336-21-6	aqua (intermittent releases)		0,0068 mg/l				
thiram 137-26-8	aqua (freshwater)		0,00046 mg/l				
thiram 137-26-8	sediment (freshwater)				0,047 mg/kg		
thiram 137-26-8	aqua (marine water)		0,000046 mg/l				
thiram 137-26-8	sediment (marine water)				0,0047 mg/kg		
thiram 137-26-8	Soil				0,00912 mg/kg		
thiram 137-26-8	sewage treatment plant (STP)		0,0311 mg/l				
thiram 137-26-8	oral				0,59 mg/kg		
thiram 137-26-8	aqua (intermittent releases)		0 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	aqua (freshwater)		0,0039 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	aqua (marine water)		0,0039 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	sewage treatment plant (STP)		0,23 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	Soil				0,047 mg/kg		
2-methylisothiazol-3(2H)-one 2682-20-4	aqua (intermittent releases)		0,0039 mg/l				

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
ammonia, aqueous solution 1336-21-6	Workers	dermal	Acute/short term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	Workers	dermal	Long term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Acute/short term exposure - systemic effects		47,6 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Acute/short term exposure - local effects		36 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Long term exposure - systemic effects		47,6 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Long term exposure - local effects		14 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	dermal	Acute/short term exposure - systemic effects		68 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	dermal	Long term exposure - systemic effects		68 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Acute/short term exposure - systemic effects		23,8 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Acute/short term exposure - local effects		7,2 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Long term exposure - systemic effects		23,8 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Long term exposure - local effects		2,8 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	oral	Acute/short term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	oral	Long term exposure - systemic effects		6,8 mg/kg	
thiram 137-26-8	Workers	inhalation	Long term exposure - systemic effects		0,118 mg/m <sup>3</sup>	
thiram 137-26-8	Workers	inhalation	Acute/short term exposure - systemic effects		0,564 mg/m <sup>3</sup>	
thiram 137-26-8	Workers	dermal	Long term exposure - systemic effects		1,6 mg/kg	
thiram 137-26-8	Workers	dermal	Acute/short term exposure - systemic effects		10 mg/kg	
2-methylisothiazol-3(2H)-one 2682-20-4	Workers	inhalation	Long term exposure - local effects		0,021 mg/m <sup>3</sup>	
2-methylisothiazol-3(2H)-one 2682-20-4	Workers	inhalation	Acute/short term exposure - local effects		0,043 mg/m <sup>3</sup>	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	inhalation	Long term exposure - local effects		0,021 mg/m <sup>3</sup>	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	oral	Long term exposure - systemic effects		0,027 mg/kg	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	oral	Acute/short term exposure - systemic effects		0,053 mg/kg	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	inhalation	Acute/short term exposure - local		0,043 mg/m <sup>3</sup>	

effects

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Respiratory protection:

Ensure adequate ventilation.

Hand protection:

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

material thickness &gt; 0.1 mm

Perforation time &gt; 10 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

Appearance	liquid viscous white
Odor	characteristic, ammoniacal
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	0,94 - 0,96 g/cm <sup>3</sup>
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (23 °C (73.4 °F); Solvent: Water)	Partially soluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity (Brookfield; 20 °C (68 °F))	7.000 - 10.000 mPa.s



Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

**9.2. Other information**

No data available / Not applicable

**SECTION 10: Stability and reactivity****10.1. Reactivity**

None if used for intended purpose.

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

See section reactivity

**10.4. Conditions to avoid**

None if used for intended purpose.

**10.5. Incompatible materials**

None if used properly.

**10.6. Hazardous decomposition products**

None known.

**SECTION 11: Toxicological information****General toxicological information:**

An allergic reaction cannot be excluded after repeated skin contact.

**11.1. Information on toxicological effects****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Rubber, natural 9006-04-6	LD50	2.043 - 2.210 mg/kg	rat	not specified
ammonia, aqueous solution 1336-21-6	LD50	350 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
thiram 137-26-8	LD50	1.800 mg/kg	rat	not specified
2-methylisothiazol-3(2H)- one 2682-20-4	LD50	120 mg/kg	rat	EPA OPPTS 870.1100 (Acute Oral Toxicity)

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
thiram 137-26-8	LD50	> 2.000 mg/kg	rabbit	EPA OPP 81-2 (Acute Dermal Toxicity)
2-methylisothiazol-3(2H)- one 2682-20-4	LD50	242 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
thiram 137-26-8	LC50	4,42 mg/l	dust/mist	4 h	rat	EPA OPP 81-3 (Acute inhalation toxicity)
2-methylisothiazol-3(2H)-one 2682-20-4	LC50	0,11 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-methylisothiazol-3(2H)-one 2682-20-4	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	corrosive			not specified
thiram 137-26-8	irritating		rabbit	EPA OPP 81-4 (Acute Eye Irritation)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
ammonia, aqueous solution 1336-21-6	not sensitising	not specified	guinea pig	not specified
thiram 137-26-8	sensitising	Split adjuvant test	guinea pig	EPA OPP 81-6 (Skin Sensitisation)
2-methylisothiazol-3(2H)-one 2682-20-4	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	negative	bacterial reverse mutation assay (e.g Ames test)	not specified		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
thiram 137-26-8	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		EPA OPP 84-2 (Mutagenicity Testing)
thiram 137-26-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
thiram 137-26-8	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2-methylisothiazol-3(2H)- one 2682-20-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-methylisothiazol-3(2H)- one 2682-20-4	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-methylisothiazol-3(2H)- one 2682-20-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
ammonia, aqueous solution 1336-21-6	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
thiram 137-26-8	negative	oral: gavage		mouse	EU Method B.24 (Mouse Spot Test)
thiram 137-26-8	negative	oral: gavage		mouse	OECD Guideline 483 (Mammalian Spermatogonial Chromosome Aberration Test)
thiram 137-26-8	negative	intraperitoneal		mouse	EPA OPP 84-2 (Mutagenicity Testing)
2-methylisothiazol-3(2H)- one 2682-20-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2-methylisothiazol-3(2H)- one 2682-20-4	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
ammonia, aqueous solution 1336-21-6	not carcinogenic	oral: feed	104 w daily	rat		OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
ammonia, aqueous solution 1336-21-6	NOAEL P 408 mg/kg	screening	oral: unspecified	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-methylisothiazol-3(2H)- one 2682-20-4	NOAEL P 200 ppm NOAEL F1 200 ppm NOAEL F2 200 ppm	Two generation study	oral: drinking water	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure::**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
thiram 137-26-8	NOAEL 3,5 - 4 mg/kg	oral: feed	90 d daily	rat	EU Method B.26 (Sub- Chronic Oral Toxicity Test: Repeated Dose 90- Day Oral Toxicity Study in Rodents)
2-methylisothiazol-3(2H)- one 2682-20-4	NOAEL 60 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

**Aspiration hazard:**

No data available.

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains, soil or bodies of water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Rubber, natural 9006-04-6	LC50	> 10.000 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
ammonia, aqueous solution 1336-21-6	LC50	0,16 - 1,1 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
ammonia, aqueous solution 1336-21-6	NOEC	< 0,048 mg/l	31 d	Channel catfish	OECD Guideline 215 (Fish, Juvenile Growth Test)
thiram 137-26-8	LC50	0,046 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
thiram 137-26-8	NOEC	0,0046 mg/l	33 d	Pimephales promelas	OECD Guideline 210 (fish early lite stage toxicity test)
2-methylisothiazol-3(2H)-one 2682-20-4	LC50	4,77 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	EC50	25,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
thiram 137-26-8	EC50	0,21 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-methylisothiazol-3(2H)-one 2682-20-4	EC50	0,93 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	NOEC	0,79 mg/l	96 h	Daphnia magna	EPA OPPTS 850.1300 (Daphnid Chronic Toxicity Test)
thiram 137-26-8	NOEC	0,04 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2-methylisothiazol-3(2H)-one 2682-20-4	NOEC	0,04 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	EC50	> 1.000 mg/l	72 h	Skeletonema costatum	ISO 10253 (Water quality)
ammonia, aqueous solution 1336-21-6	NOEC	1.000 mg/l	72 h	Skeletonema costatum	ISO 10253 (Water quality)
thiram 137-26-8	EC50	1 mg/l	96 h	Chlorella pyrenoidosa	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-methylisothiazol-3(2H)-one 2682-20-4	NOEC	0,03 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-methylisothiazol-3(2H)-one 2682-20-4	EC50	0,22 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Rubber, natural 9006-04-6	EC 50	> 10.000 mg/l			OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
thiram 137-26-8	EC0	> 200 mg/l			not specified
2-methylisothiazol-3(2H)-one 2682-20-4	EC 50	41 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

### 12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
thiram 137-26-8		aerobic	20 - 40 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
2-methylisothiazol-3(2H)-one 2682-20-4	inherently biodegradable	aerobic	97 %	48 h	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
2-methylisothiazol-3(2H)-one 2682-20-4	readily biodegradable	aerobic	> 70 %	28 d	OECD Guideline 309 (Aerobic Mineralisation in Surface WaterSimulation Biodegradation Test)

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
ammonia, aqueous solution 1336-21-6	-1,14		EU Method A.8 (Partition Coefficient)
thiram 137-26-8	1,73	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2-methylisothiazol-3(2H)-one 2682-20-4	-0,5		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
ammonia, aqueous solution 1336-21-6	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
thiram 137-26-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-methylisothiazol-3(2H)-one 2682-20-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080409

## SECTION 14: Transport information

- 14.1. UN number**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**  
not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content 0,0 %  
(VOCV 814.018 VOC regulation  
CH)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H290 May be corrosive to metals.  
H301 Toxic if swallowed.  
H302 Harmful if swallowed.  
H311 Toxic in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**