



SAFETY DATA SHEET

Plumberfix Part A Resin

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Plumberfix Part A Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive. Sealant.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Sylglas
Winn & Coales (Denso) Ltd
Denso House
Chapel Road
West Norwood
SE27 0TR
mail@sylglas.com
+44 (0)208 670 7511

1.4. Emergency telephone number

Emergency telephone +44 (0)208 670 7511 (M-F, 8-5 GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Plumberfix Part A Resin

Precautionary statements	<p>P261 Avoid breathing dust.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	EUH205 Contains epoxy constituents. May produce an allergic reaction.
Contains	Reaction product: bisphenol-A-(epichlorhydrin), bis-[4-(2,3-epoxipropoxi)phenyl]propane

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrous Magnesium Silicate 30-60% CAS number: 14807-96-6
Classification Not Classified
Reaction product: bisphenol-A-(epichlorhydrin) 10-30% CAS number: 25068-38-6 EC number: 500-033-5
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411
bis-[4-(2,3-epoxipropoxi)phenyl]propane 10-30% CAS number: 1675-54-3 EC number: 216-823-5
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
----------------------------	--

Plumberfix Part A Resin

Inhalation	Remove affected person from source of contamination. Get medical attention.
Ingestion	Rinse mouth thoroughly with water. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Do not use organic solvents.
Eye contact	Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May be a choking hazard. Wheezing/breathing difficulties.
Ingestion	May cause irritation. Sore throat. Redness. May cause stomach pain or vomiting.
Skin contact	May cause irritation.
Eye contact	May irritate eyes. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products	Toxic gases or vapours.
--------------------------------------	-------------------------

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	For personal protection, see Section 8.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Place waste in labelled, sealed containers.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Wear protective gloves. Use only in well-ventilated areas. Avoid generation and spreading of dust.
--------------------------	--

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in a cool and well-ventilated place. Keep container tightly closed.
----------------------------	---

7.3. Specific end use(s)

Plumberfix Part A Resin

Specific end use(s) No data available.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Hydrous Magnesium Silicate

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³ respirable dust

WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering controls	Provide adequate ventilation.
Eye/face protection	No specific eye protection required during normal use.
Hand protection	Wear protective gloves.
Respiratory protection	Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Solid. Putty.
Colour	Light (or pale). Grey.
Odour	Slight.
Odour threshold	No specific test data are available.
Melting point	No specific test data are available.
Initial boiling point and range	No specific test data are available.
Flash point	No specific test data are available.
Evaporation rate	No specific test data are available.
Evaporation factor	No specific test data are available.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Other flammability	No specific test data are available.
Vapour pressure	No specific test data are available.
Vapour density	No specific test data are available.
Bulk density	No specific test data are available.
Solubility(ies)	No specific test data are available.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	No specific test data are available.
Viscosity	Technically not feasible.
Explosive properties	No specific test data are available.

Plumberfix Part A Resin

Explosive under the influence of a flame Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable under the prescribed storage conditions.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions May generate heat.

10.4. Conditions to avoid

Conditions to avoid Avoid heat.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Coughing, chest tightness, feeling of chest pressure.

Ingestion May cause chemical burns in mouth and throat.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact Redness. Irritating. Profuse watering of the eyes.

SECTION 12: Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Toxicity Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential Potentially bioaccumulating.

Partition coefficient No specific test data are available.

12.4. Mobility in soil

Mobility The product hardens to a solid, immobile substance. Insoluble in water.

Plumberfix Part A Resin

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Dispose of waste product or used containers in accordance with local regulations

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UFI UFI: CV23-8U4W-0S0V-KXGJ

National regulations Health and Safety at Work etc. Act 1974 (as amended).
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EH40/2005 Workplace exposure limits.

Plumberfix Part A Resin

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.

IATA: International Air Transport Association.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service.

ATE: Acute Toxicity Estimate.

LC₅₀: Lethal Concentration to 50 % of a test population.

LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).

EC₅₀: 50% of maximal Effective Concentration.

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations and acronyms

Eye Irrit. = Eye irritation

Skin Irrit. = Skin irritation

Skin Sens. = Skin sensitisation

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Classification procedures according to Regulation (EC) 1272/2008

Skin Irrit. 2 - H315: Eye Irrit. 2 - H319: Skin Sens. 1 - H317: : Calculation method. Aquatic

Chronic 2 - H411: : Calculation method.

Revision date

27/10/2020

Revision

2

Supersedes date

07/02/2020

SDS number

5318

Hazard statements in full

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Plumberfix Part A Resin

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



SAFETY DATA SHEET

Plumberfix Part B Hardener

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Plumberfix Part B Hardener

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive. Sealant.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Sylglas
Winn & Coales (Denso) Ltd
Denso House
Chapel Road
West Norwood
SE27 0TR
mail@sylglas.com
+44 (0)208 670 7511

1.4. Emergency telephone number

Emergency telephone +44 (0)208 670 7511 (M-F, 8-5 GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

Supplementary information Contains epoxy constituents. May produce an allergic reaction.

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Plumberfix Part B Hardener

Precautionary statements	<p>P261 Avoid breathing dust.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 Immediately call a POISON CENTER/ doctor.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	EUH205 Contains epoxy constituents. May produce an allergic reaction.
Contains	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine bis-[4-(2,3-epoxipropoxi)phenyl] propane, bis-[4-(2,3-epoxipropoxi)phenyl]propane, 3,6-diazaoctanethylenediamin, N,N'-bis(3-aminopropyl) ethylenediamine

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrous Magnesium Silicate CAS number: 14807-96-6	30-60%
Classification Not Classified	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine bis-[4-(2,3-epoxipropoxi)phenyl] propane CAS number: 68082-29-1	10-30%
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1A - H317 Aquatic Chronic 2 - H411	
bis-[4-(2,3-epoxipropoxi)phenyl]propane CAS number: 1675-54-3 EC number: 216-823-5	5-10%
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317	

Plumberfix Part B Hardener

2,4,6-tris(dimethylaminomethyl)phenol	1-5%
CAS number: 90-72-2	EC number: 202-013-9
Classification	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
3,6-diazaoctanethylenediamin	<1%
CAS number: 112-24-3	EC number: 203-950-6
Classification	
Acute Tox. 4 - H312	
Skin Corr. 1B - H314	
Skin Sens. 1 - H317	
Aquatic Chronic 3 - H412	
N,N'-bis(3-aminopropyl) ethylenediamine	<1%
CAS number: 10563-26-5	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 2 - H310	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Skin Sens. 1A - H317	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Do not use organic solvents.
Eye contact	Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May be a choking hazard. Wheezing/breathing difficulties.
Ingestion	May cause irritation. Sore throat. Redness. May cause stomach pain or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.
-----------------------------	--

SECTION 5: Firefighting measures

Plumberfix Part B Hardener

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products Toxic gases or vapours.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Place waste in labelled, sealed containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective gloves. Use only in well-ventilated areas. Avoid generation and spreading of dust.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s) No data available.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Hydrous Magnesium Silicate

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³ respirable dust

WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering controls Provide adequate ventilation.

Eye/face protection No specific eye protection required during normal use.

Hand protection Wear protective gloves.

Respiratory protection Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

Plumberfix Part B Hardener

9.1. Information on basic physical and chemical properties

Appearance	Solid. Putty.
Colour	Dark. Grey.
Odour	Slight.
Melting point	No specific test data are available.
Flash point	No specific test data are available.
Evaporation rate	No specific test data are available.
Evaporation factor	No specific test data are available.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Other flammability	No specific test data are available.
Vapour pressure	No specific test data are available.
Bulk density	No specific test data are available.
Solubility(ies)	No specific test data are available.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	No specific test data are available.
Viscosity	Technically not feasible.
Explosive properties	No specific test data are available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable under the prescribed storage conditions.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur. Reactions with the following materials may generate heat: Acids. Epoxides.

10.4. Conditions to avoid

Conditions to avoid Avoid heat.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Plumberfix Part B Hardener

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 20,000.0

Acute toxicity - dermal

ATE dermal (mg/kg) 66,666.67

Inhalation Coughing, chest tightness, feeling of chest pressure.

Ingestion May cause irritation. Sore throat. Redness.
May cause stomach pain or vomiting.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Redness. Irritating. Profuse watering of the eyes.

SECTION 12: Ecological information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity

Toxicity The product is not believed to present a hazard due to its physical nature.

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely.

Partition coefficient No specific test data are available.

12.4. Mobility in soil

Mobility The product has poor water-solubility.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Dispose of waste product or used containers in accordance with local regulations

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Plumberfix Part B Hardener

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78
and the IBC Code**

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UFI

UFI: WXWY-MD23-808G-F29V

National regulations

Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Plumberfix Part B Hardener

Abbreviations and acronyms used in the safety data sheet	<p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.</p> <p>RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.</p> <p>IATA: International Air Transport Association.</p> <p>ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>CAS: Chemical Abstracts Service.</p> <p>ATE: Acute Toxicity Estimate.</p> <p>LC₅₀: Lethal Concentration to 50 % of a test population.</p> <p>LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>EC₅₀: 50% of maximal Effective Concentration.</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p>
Classification abbreviations and acronyms	<p>Eye Irrit. = Eye irritation</p> <p>Skin Irrit. = Skin irritation</p> <p>Skin Sens. = Skin sensitisation</p> <p>Aquatic Chronic = Hazardous to the aquatic environment (chronic)</p>
Classification procedures according to Regulation (EC) 1272/2008	<p>Skin Irrit. 2 - H315: Eye Irrit. 2 - H319: Skin Sens. 1 - H317: : Calculation method. Aquatic Chronic 3 - H412: : Calculation method.</p>
Training advice	Only trained personnel should use this material.
Revision date	28/10/2020
Revision	2
Supersedes date	07/02/2020
SDS number	5321
Hazard statements in full	<p>H302 Harmful if swallowed.</p> <p>H310 Fatal in contact with skin.</p> <p>H312 Harmful in contact with skin.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H319 Causes serious eye irritation.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.