

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**EVO-STIK EPOXY RAPID - RESIN Supercedes Date:** 15-Nov-2018

Revision Date 15-Nov-2018 Revision Number 1

\_\_\_

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product Identifier

Product Name EVO-STIK EPOXY RAPID - RESIN

Pure substance/mixture Mixture

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Resin.
Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### **Company Name**

Bostik SA Immeuble "Le Jade" 253 Avenue du President Wilson 93211 La Plaine Saint Denis France

Tel: +33 (0)1 55 99 90 00 Fax: +33 (0)1 55 99 90 01

E-mail address SDS.box-EU@bostik.com

# 1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650

**Ireland** +353 (1) 8624900 (Monday- Friday 9am-5pm)

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

### Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

# 2.2. Label Elements

Contains: Bisphenol A diglycidyl ether, Formaldehyde, polymer with (chloromethyl)oxirane and phenol



Signal word Warning

## **Hazard statements**

Supercedes Date: 15-Nov-2018 Revision Number 1

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

**EVO-STIK EPOXY RAPID - RESIN** 

H411 - Toxic to aquatic life with long lasting effects

## **Precautionary statements**

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P337 + P313 - If eye irritation persists: Get medical advice/attention

P391 - Collect spillage

P501 - Dispose of contents/ container to an approved waste disposal plant

#### 2.3. Other Hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

#### PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

# SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable

# 3.2 Mixtures

Chemical Name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Bisphenol A diglycidyl ether	216-823-5	1675-54-3	80 - 100	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	No data available
Formaldehyde, polymer with (chloromethyl)oxirane and phenol	500-006-8	9003-36-5	5 - <10	Skin Irrit. 2 (H315) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)		01-2119454392- 40-XXXX
Glycidoxypropyltrimetho xysilane	219-784-2	2530-83-8	1 - <3	Eye Dam. 1 (H318)		01-2119513212- 58-XXXX

#### Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classifed, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Revision Date 15-Nov-2018

Supercedes Date: 15-Nov-2018 **Revision Number 1** 

## **SECTION 4: First aid measures**

**EVO-STIK EPOXY RAPID - RESIN** 

#### 4.1. Description of first aid measures

Show this safety data sheet to the doctor in attendance. **General advice** 

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

> Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist. Do not rub affected area. Get medical

Revision Date 15-Nov-2018

attention if irritation develops and persists.

Skin contact May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see

a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by

mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** Itching. Rashes. Hives. Burning sensation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

#### 5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Product is or contains a sensitiser. May cause sensitisation by skin contact.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. See section 8 for more information.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

**EVO-STIK EPOXY RAPID - RESIN** Revision Date 15-Nov-2018 Supercedes Date: 15-Nov-2018 **Revision Number** 1

## 6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. **Environmental precautions** 

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Use a non-combustible material like vermiculite, sand or earth to soak up the product

and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

# SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protection recommended in Section 8.

**General hygiene considerations** Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.

#### 7.3. Specific end use(s)

#### Specific Use(s)

This product is a cyanoacrylate-based adhesive. Resin.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Observe technical data sheet. Other information

# **SECTION 8: Exposure controls/Personal protection**

## 8.1. Control parameters

**Exposure Limits** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing

Chemical Name	European Union	Ireland	United Kingdom
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m <sup>3</sup>	TWA: 260 mg/m <sup>3</sup>	TWA: 266 mg/m <sup>3</sup>
	*	STEL: 600 ppm	STEL: 250 ppm
		STEL: 780 mg/m <sup>3</sup>	STEL: 333 mg/m <sup>3</sup>
		Sk*	Sk*

**Derived No Effect Level (DNEL)** No information available

Predicted No Effect Concentration No information available. (PNEC)

**EVO-STIK EPOXY RAPID - RESIN Supercedes Date:** 15-Nov-2018 **Revision Date** 15-Nov-2018 **Revision Number** 1

\_\_\_\_\_

\_\_\_

8.2. Exposure controls

**Engineering controls** Please refer also to Safety Data Sheet of Part B.

**Personal Protective Equipment** 

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves: Nitrile rubber, Butyl rubber. Ensure that the breakthrough time of

the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374.

Not applicable

@ 25 °C

**Skin and body protection** Wear suitable protective clothing.

**Respiratory protection** Ensure adequate ventilation, especially in confined areas.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance No information available

Colour Light yellow Odour Slight

Odour Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

**pH** No data available

Melting point / freezing point

No data available

Poiling point / boiling range

> 200 °C

**Boiling point / boiling range** > 200 °C **Flash Point** 
150 °C

**Evaporation Rate**Flammability (solid, gas)
No data available
No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

**Vapour Pressure** No data available **Vapour Density** No data available **Relative Density** No data available No data available **Water Solubility** No data available Solubility(ies) **Partition coefficient** No data available No data available **Autoignition Temperature Decomposition Temperature** No data available **Kinematic Viscosity** No data available 8000 - 12000 mPas **Dynamic Viscosity** 

Explosive properties No data available

Oxidising properties No data available

No data available

9.2. Other information

Solid content (%)

Softening Point

Molecular Weight

VOC (volatile organic compound)

No information available
No information available
No information available

**Density** 1.15 g/cm<sup>3</sup>

Bulk Density

No information available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

EVO-STIK EPOXY RAPID - RESIN

Supercedes Date: 15-Nov-2018

Revision Date 15-Nov-2018

Revision Number 1

\_\_\_

**Reactivity** No information available.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion Data** 

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

**Hazardous decomposition** 

products

None under normal use conditions. Stable under recommended storage conditions.

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

## Information on likely routes of exposure

Product information

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Irritating to eyes. Causes serious eye irritation.

**Skin contact** May cause sensitisation by skin contact. Specific test data for the substance or mixture

is not available. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons. (based on components). Causes skin irritation.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

**Acute Toxicity** 

The following values are calculated based on chapter 3.1 of the GHS document

**Component Information** 

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
---------------	-----------	-------------	-----------------

EVO-STIK EPOXY RAPID - RESIN
Supercedes Date: 15-Nov-2018
Revision Number 1
Revision Number 1

Bisphenol A diglycidyl ether 1675-54-3	= 11300 μL/kg (Rat)	LD50 >2000 mg/Kg (Rat)	
Formaldehyde, polymer with (chloromethyl)oxirane and phenol 9003-36-5	> 2 g/kg(Rat)	LD50 > 2000 mg/kg ( Rat ) (OECD 402)	
Glycidoxypropyltrimethoxysilan e 2530-83-8	= 8025 mg/kg (rat)	= 4250 mg/kg ( Rabbit )	> 5.3 mg/L (Rat)4 h

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

**Respiratory or skin sensitisation** May cause sensitisation by skin contact.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor
Glycidoxypropyltrimetho xysilane 2530-83-8	-	LC50 (96h) = 55 mg/L (Cyprinus carpio) OECD 203	-	EC50 (48h) =473 mg/L Daphnia magna	-

#### 12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

#### **Component Information**

Chemical Name	Partition coefficient	Bioconcentration factor (BCF)
Formaldehyde, polymer with	3.6	-
(chloromethyl)oxirane and phenol 9003-36-5		

**EVO-STIK EPOXY RAPID - RESIN** Revision Date 15-Nov-2018 Supercedes Date: 15-Nov-2018 **Revision Number** 1

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment . The components in this formulation do not meet the criteria for classification as PBT or

Chemical Name	PBT and vPvB assessment
Bisphenol A diglycidyl ether 1675-54-3	The substance is not PBT / vPvB
Formaldehyde, polymer with (chloromethyl)oxirane and phenol 9003-36-5	The substance is not PBT / vPvB
Glycidoxypropyltrimethoxysilane 2530-83-8	The substance is not PBT / vPvB

#### 12.6. Other adverse effects

Other Adverse Effects No information available.

**Endocrine Disruptor Information** 

Chemical Name	EU - Endocrine Disrupters	EU - Endocrine Disruptors -
	Candidate List	Evaluated Substances
Bisphenol A diglycidyl ether	Group II Chemical	-

## SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/ container to an approved landfill.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the

product itself.

according to EWC / AVV

Waste codes / waste designations Waste codes should be assigned by the user based on the application for which the

product was used.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances

Ш

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

# **SECTION 14: Transport information**

Land transport (ADR/RID)

14.1 UN Number UN3082

Environmentally hazardous substances, liquid, n.o.s (Bisphenol A diglycidyl 14.2 Proper Shipping Name

ether, Formaldehyde, polymer with (chloromethyl) oxirane and phenol)

14.3 Transport hazard class(es) 9 Labels

14.4 Packing Group

Description UN3082, Environmentally hazardous substances, liquid, n.o.s (Bisphenol A diglycidyl

ether, Formaldehyde, polymer with (chloromethyl) oxirane and phenol), 9, III

14.5 Environmental hazards

14.6 Special Provisions 274, 335, 601, 375

EVO-STIK EPOXY RAPID - RESIN
Supercedes Date: 15-Nov-2018
Revision Date 15-Nov-2018
Revision Number 1

Classification Code M6 Limited Quantity (LQ) 5 L ADR Hazard Id (Kemmler 90

Number)

**IMDG** 

**14.1 UN Number** UN3082

14.2 Proper Shipping Name Environmentally hazardous substances, liquid, n.o.s (Bisphenol A diglycidyl

ether, Formaldehyde, polymer with (chloromethyl) oxirane and phenol), Marine Pollutant

14.3 Transport hazard class(es) 9

14.4 Packing Group

**Description** UN3082, Environmentally hazardous substances, liquid, n.o.s (Bisphenol A diglycidyl

ether, Formaldehyde, polymer with (chloromethyl) oxirane and phenol), 9, III, Marine

Pollutant

14.5 Marine Pollutant

**14.6 Special Provisions** 274, 335, 969

Limited Quantity (LQ) 5 L EmS-No. 5-A, S-F

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

Air transport (ICAO-TI / IATA-DGR)

**14.1 UN Number** UN3082

14.2 Proper Shipping Name Environmentally hazardous substances, liquid, n.o.s (Formaldehyde, polymer with

(chloromethyl)oxirane and phenol)

14.3 Transport hazard class(es) 9

14.4 Packing Group

**Description** UN3082, Environmentally hazardous substances, liquid, n.o.s (Formaldehyde, polymer

with (chloromethyl)oxirane and phenol), 9, III

14.5 Environmental hazards

**14.6 Special Provisions** A97, A158, A197

Limited Quantity (LQ) 30 kg G ERG Code 9L

## Section 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

# EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

## EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

EVO-STIK EPOXY RAPID - RESIN
Supercedes Date: 15-Nov-2018

Revision Date 15-Nov-2018
Revision Number 1

\_\_\_\_\_

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

**Persistent Organic Pollutants** 

Not applicable

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

#### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H317 - May cause an allergic skin reaction

H411 - Toxic to aquatic life with long lasting effects

H318 - Causes serious eye damage

Legend

SVHC: Substances of Very High Concern for Authorisation:

**Legend** SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value \* Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 15-Nov-2018

Indication of changes

**Revision note** SDS sections updated: 2, 3, 11, 14.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 15-Nov-2018 Revision Date 15-Nov-2018 Revision Number 1

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**EVO-STIK EPOXY RAPID - HARDENER** 

Supercedes Date: 15-Nov-2018

Revision Date 19-Mar-2019 Revision Number 1.01

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product Identifier

Product Name EVO-STIK EPOXY RAPID - HARDENER

Pure substance/mixture Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Curing chemical. Uses advised against None known

#### 1.3. Details of the supplier of the safety data sheet

## **Company Name**

Bostik SA 420 rue d'Estienne d'Orves 92700 Colombes FRANCE

Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

## 1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650

+353 (1) 8624900 (Monday- Friday 9am-5pm)

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)

#### 2.2. Label Elements

Contains: 1,3-Propanediamine, N'-(3-aminopropyl)-N,N-dimethyl-



#### Signal word WARNING

# **Hazard statements**

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

**EVO-STIK EPOXY RAPID - HARDENER** 

## **Precautionary statements**

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

Supercedes Date: 15-Nov-2018

P280 - Wear protective gloves and eye/face protection

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P337 + P313 - If eye irritation persists: Get medical advice/attention

P501 - Dispose of contents/ container to an approved waste disposal plant

#### **Additional information**

Please refer also to Safety Data Sheet of Part A.

#### 2.3. Other Hazards

No information available

#### PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

# SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical Name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
1,3-Propanediamine, N'-(3-aminopropyl)-N,N- dimethyl-	234-148-4	10563-29-8	1 - <3	Skin Corr. 1A (H314) Eye Dam. 1 (H318) Skin Sens. 1B (H317) Acute Tox. 4 (H302) Acute Tox. 4 (H312)		01-2119970376- 29-XXXX
Pyrimido[1,2-a]azepine, 2,3,4,6,7,8,9,10-octahyd ro-	229-713-7	6674-22-2	0.1 - <1	Skin Corr. 1B (H314) Acute Tox. 3 (H301) Eye Dam. 1 (H318)		01-2119977097- 24-XXXX

### Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classifed, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

Revision Date 19-Mar-2019

**EVO-STIK EPOXY RAPID - HARDENER** 

Supercedes Date: 15-Nov-2018

**General advice** Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist. Do not rub affected area. Get medical

Revision Date 19-Mar-2019

Revision Number 1.01

attention if irritation develops and persists.

Skin contact May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see

a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by

mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** Itching. Rashes. Hives. Burning sensation.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

# SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Product is or contains a sensitiser. May cause sensitisation by skin contact.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. See section 8 for more information.

Other information Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

**EVO-STIK EPOXY RAPID - HARDENER** 

Supercedes Date: 15-Nov-2018 Revision Number 1.01

and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protection recommended in Section 8.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink

or smoke when using this product. Wash thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.

#### 7.3. Specific end use(s)

Specific Use(s)

Hardener. Curing chemical.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

# SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

**Exposure Limits** This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available.

(PNEC)

8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas. Please refer also to Safety

Data Sheet of Part A.

**Personal Protective Equipment** 

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves: Nitrile rubber, Butyl rubber. Ensure that the breakthrough time of

the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374.

**Skin and body protection** Suitable protective clothing.

Revision Date 19-Mar-2019

**EVO-STIK EPOXY RAPID - HARDENER** 

Supercedes Date: 15-Nov-2018

**Respiratory protection** Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance No information available Colour Colourless to yellow

**Odour** Ammonia

Odour Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available
Melting point / freezing point
Boiling point / boiling range > 150 °C
Flash Point 100 °C

**Evaporation Rate**Flammability (solid, gas)
No data available
No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

**Vapour Pressure** No data available No data available **Vapour Density** No data available **Relative Density Water Solubility** No data available Solubility(ies) No data available **Partition coefficient** No data available **Autoignition Temperature** No data available No data available **Decomposition Temperature Kinematic Viscosity** No data available

**Dynamic Viscosity** 10000 - 20000 mPa s @ 25 °C

Explosive properties No data available Oxidising properties No data available

9.2. Other information

Solid content (%)

Softening Point

Molecular Weight

VOC (volatile organic compound)

No information available
No information available
No information available

Density 1.14 g/cm<sup>3</sup>

Bulk Density No information available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** No information available.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion Data** 

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

Revision Date 19-Mar-2019

**EVO-STIK EPOXY RAPID - HARDENER** 

Supercedes Date: 15-Nov-2018 Revision Number 1.01

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

**Conditions to avoid**None known based on information supplied.

10.5. Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Thermal decomposition can lead to release of toxic/corrosive gases and vapours.

Revision Date 19-Mar-2019

Ammonia. Amines.

# SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

### Information on likely routes of exposure

Product information .

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Causes serious eye irritation.

**Skin contact** May cause sensitisation by skin contact. Causes skin irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

**Acute Toxicity** 

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 12,123.00 mg/kg ATEmix (dermal) 36,789.00 mg/kg

### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Pyrimido[1,2-a]azepine,	DL50 >215<681 mg/kg (Rat)		
2,3,4,6,7,8,9,10-octahydro-			
6674-22-2			

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

**EVO-STIK EPOXY RAPID - HARDENER** 

Supercedes Date: 15-Nov-2018

**Respiratory or skin sensitisation** May cause sensitisation by skin contact.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity**Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecotoxicity

Chemical Name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor
	plants		Micro-organisms		
Pyrimido[1,2-a]azepine,	-	100-220 mg/l	-	-	-
2,3,4,6,7,8,9,10-octahyd		(leuciscus idus)			
ro-					
6674-22-2					

### 12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulative potential No information available.

12.4. Mobility in soil

Mobility in soil No information available.

### 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment**The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical Name	PBT and vPvB assessment		
1,3-Propanediamine, N'-(3-aminopropyl)-N,N-dimethyl- 10563-29-8	The substance is not PBT / vPvB		
Pyrimido[1,2-a]azepine, 2,3,4,6,7,8,9,10-octahydro- 6674-22-2	The substance is not PBT / vPvB		

# 12.6. Other adverse effects

Other Adverse Effects No information available.

Revision Date 19-Mar-2019

**EVO-STIK EPOXY RAPID - HARDENER** 

## SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Supercedes Date: 15-Nov-2018

Waste from residues/unused

products

Dispose of contents/ container to an approved landfill.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the

product itself.

according to EWC / AVV

Waste codes / waste designations Waste codes should be assigned by the user based on the application for which the

Revision Date 19-Mar-2019

**Revision Number** 1.01

product was used.

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

# **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1 UN Number Not regulated Not regulated 14.2 Proper Shipping Name 14.3 Transport hazard class(es) Not regulated 14.4 Packing Group Not regulated Not applicable 14.5 Environmental hazards

None 14.6 Special Provisions

### **IMDG**

14.1 UN Number Not regulated Not regulated 14.2 Proper Shipping Name 14.3 Transport hazard class(es) Not regulated 14.4 Packing Group Not regulated 14.5 Marine Pollutant Np

14.6 Special Provisions None 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

# Air transport (ICAO-TI / IATA-DGR)

14.1 UN Number Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Transport hazard class(es) Not regulated Not regulated 14.4 Packing Group 14.5 Environmental hazards Not applicable 14.6 Special Provisions None

## Section 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

## Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

**EVO-STIK EPOXY RAPID - HARDENER** 

Supercedes Date: 15-Nov-2018

## **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

# SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H317 - May cause an allergic skin reaction

H302 - Harmful if swallowed

H312 - Harmful in contact with skin

H301 - Toxic if swallowed

## Legend

SVHC: Substances of Very High Concern for Authorisation:

**Legend** SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value \* Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

#### Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 19-Mar-2019

Indication of changes

**Revision note** SDS sections updated: 2, 3.

Revision Date 19-Mar-2019

EVO-STIK EPOXY RAPID - HARDENER Supercedes Date: 15-Nov-2018

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

Revision Date 19-Mar-2019