

DOVETAIL CUTTERS



TCT
TUNGSTEN
CARBIDE
TIPPED





DOVETAIL CUTTER

For dovetail joints and sliding dovetails. To suit user preference, the table shows angles from the horizontal and the profiles show angles from the vertical.

* For use with Trend Dovetail Jig DJ300.



A Deg.	D mm	D inch	C mm	OL mm	Product Ref.	Shank Diameter 1/4" 1/2"
115°	5.0	-	3.0	61.0	31/10L	£35.46 -
98°	6.0	-	6.9	63.0	S31/11 *	£26.52 + -
102°	9.5	3/8	8.5	54.0	31/22	£36.18 + -
104°	12.7	1/2	10.0	60.0	31/12	- £29.12
103°	13.2	-	13.0	55.0	31/02	£34.14 -
104°	19.1	3/4	19.1	66.0	31/50	- £36.40
104°	25.4	1	25.4	69.0	31/25	- £38.36 4



STAIR HOUSING DOVETAIL CUTTER


Purpose made for stair housing jigs. Ensures tight fit of tread in string on face edge.

Refs. 32/11 and 32/13 are available in left hand (LH) and right hand (RH) rotation. RH cutters are also used with Trend Stair Jigs.





Please state LH or RH when ordering.

Trend Stair Jig Ref. STAIR/A

- Recommended cutters for tread thickness:
- 22mm (7/8") Ref. 32/10X1/2TC
- 25.4mm (1") Ref. 32/11X1/2TC
- 28.5mm (1-1/8") Ref. 32/12X1/2TC
- 32mm (1-1/4") Ref. 32/13X1/2TC



A Deg.	D mm	D inch	C mm	OL mm	Product Ref.	Rotation	Shank Dia. 1/2"
95°	14.0	-	20.0	65.0	32/10	RH	£57.67
95°	16.0	5/8	26.0	65.0	32/11	RH	£57.67
95°	19.0	3/4	25.5	65.0	32/12	RH	£59.81
95°	22.0	7/8	25.5	65.0	32/13	LH	£69.47
95°	22.0	7/8	25.5	65.0	32/13	RH	£59.81
95°	25.4	1	25.4	65.0	32/14	RH	£53.96 +



STAIR JIGS

See page 155 for full details.

Product Ref.

STAIR/A
STAIR/B

