ROUTER TABLE **ACCESSORIES**

ROUTER TABLE INSERT

Large router table insert plates for incorporation into user-made router tables.

- Router plates which can be drilled for various routers.
- Two concentric snap-in rings.
- Three hole sizes of 98mm, 68mm & 32mm diameter.
- · Includes lead-on pin .
- · Will accept screw-on style guide bushes for use as a copy follower.

RTI/PLATE/A (Alloy) £58.30

Drilled for Trend TBC router and T11 guide router. Includes fixing kit. Size: 306 x 229 x 6.35mm

RTI/PLATE (Plastic) £49.38

Moulded with slight crown (0.8mm) for distortion free cuts. Corner clips to clamp to underside of table. Size: 306 x 229 x 9.5mm




8kg Max. router base dia. 200mm 1 x Lead-on pin

OPTIONAL ACCESSORY: Product Ref. Price Insert plate shield (RTI/PLATE only) RTI/SHIELD £17.98 Router fixing kit (csk screws)






A shield is available for use with the Ref. RTI/PLATE when using guided cutters and no backfence



Ref. RTI/PLATE/A



Ref. RTI/PLATE

NO-VOLT RELEASE SWITCHES

Versatile no-volt release switches for the remote switching of power tools such as routers when mounted in a router table. Can be placed in a convenient position. Trips power to the machine should the power be momentarily cut off. Switches must be bolted directly to the router table leg or a user made workboard.

NVRS/2/240V

(13A, 240v max. load 12A) 1.7 metre cable length. £71.32

(16A, 115v max. load 12A) 0.7 metre cable length,





router table

FEATHER BOARD

Vertical or horizontal pressure guard. Prevents the material from being thrown back by the cutter and holds the work down onto the table or against the backfence.

PRESSURE/1 £9.80



PUSHSTICK

Rigid plastic safety pushstick for guiding small sections of timber over a router table. Keeps operators hands away from the cutting tool. 420mm overall length.

PUSHSTICK/1



ROUTER TABLE BACKFENCE

Backfence complete for incorporating into a user-made router table. Includes sliding cheeks, edge planing facility of 1.4mm and 2.4mm, top featherboard pressure, clear safety guard and 57mmØ dust spout.

RT/FENCE/A Length 595mm, table slot centres 408mm




MITRE FENCES & 19MM TRACK

For use with user-made router tables, saw benches and band saws. Heavy duty alloy body with adjustable stops at -45°, 90°, +45°. Scale pitch of 5°. Protractor body 142mm x 48mm high. Spring loaded locater for 90°

with 1° adjustable location centring scale. MITRE/1 £30.56 For PRT. Steel bar 300 x 17 x 7mm

MITRE/3 £30.56 For CRT/MK3 and 19mm track. Alloy bar 351 x 18.9 x 9mm



WP-CRTMK3/38 (600mm) WP-WRT/38 (800mm) £16.39 Mitre fence track extrusion for MITRE/3. T-slot 19.2mm (neck) x 23.9mm (base). T-slot height 9.8mm.



