

JOINTING ACCESSORIES & SEALS

WOODEN BISCUITS

Biscuit jointing has proven to be one of the strongest, fastest, safest and most accurate ways to join hardwoods and softwoods, plywood, composition board etc. Compared to dowelling, biscuit jointing is faster and more precise. The biscuits are made of die-cut beech which expands when in contact with a woodworking adhesive eg. PVA glue.



For certified biscuits see our website.

No.0

For board thickness 8 - 12mm
Size: 47.5 x 15.5 x 4.0mm
BSC/0/100 (qty 100) £7.81
BSC/0/1000 (qty 1000) £31.74

No.10

For board thickness 13 - 18mm
Size: 53 x 19 x 4.0mm
BSC/10/100 (qty 100) £7.81
BSC/10/1000 (qty 1000) £33.09

No.20

For board thickness 19mm+
Size: 60 x 23 x 4.0mm
BSC/20/100 (qty 100) £7.81
BSC/20/1000 (qty 1000) £34.39

No.0, 10 & 20

Qty No.0 x 30, No.10 x 30 & No.20 x 40
BSC/MIX/100 (qty 100) £7.81
Qty No.0 x 250, No.10 x 250 & No.20 x 500
BSC/MIX/1000 (qty 1000) £33.09

100MM BISCUIT JOINTING BLADES

- Six Tungsten Carbide Teeth.
- Anti-kickback tool design for safer use.
- Suitable for natural timbers, particle and MDF boards.
- Standard 100mm diameter x 22mm bore x 4mm kerf.



TCT

CR/BJB100T

£20.76
Thin body for Trend, Freud, Casals & Dewalt DW682. Plate thickness 2.5mm.


CR/BJB100

£31.11
Bossed body, plate thickness 3mm (3.4mm with boss).



WOODEN DOWELS

Multi-grooved kiln dried hardwood dowel pins. Suitable for joining chipboard and MDF panels in the production of cabinet carcasses and doors. The grooves in the dowels allow for gluing up. Three diameters available.



D mm	OL mm	Qty	Product Ref.	Price
6	30	50	DWL/1/50	£2.51
6	30	500	DWL/1/500	£16.67
8	30	50	DWL/2/50	£2.51
8	30	500	DWL/2/500	£20.25
8	40	50	DWL/3/50	£2.51
8	40	500	DWL/3/500	£24.34
10	35	50	DWL/4/50	£3.17
10	35	500	DWL/4/500	£28.58
10	50	50	DWL/5/50	£4.22
10	50	500	DWL/5/500	£32.03



DOWEL CENTRE POINTS

Six pack of metal dowel centres that fit into blind holes to allow lining up of the mating hole for wooden dowels. Pairs of 6mm, 8mm and 10mm diameter dowel centres. Place end of dowel centre into holes drilled in one piece of wood. Place second piece of wood in required position and press to leave centre mark for the hole.

DWL/C/PK1 £3.15


6mm, 8mm & 10mm in diameter.



WEATHERSEALS

AQUA 63 & P6 STYLE STRIP


Strip is fitted into the window frame aperture using four cut lengths. Groove created by Refs. 330, 331, 34/55 and C206. See page 66 and 109.



Colour	Approx. length metres	Product Ref.	Price
White	10	AQ63/W/10	£18.79
White	25	AQ63/W/25	£43.15
Brown	10	AQ63/B/10	£18.79
Brown	25	AQ63/B/25	£43.15

AQUA 21 & A10 STRIP


Strip is fitted into the door frame rebate (head and jambs) as three cut pieces forming a compression or wiping seal. Groove created by Refs. 334, 34/56 and C207. See page 66 and 109.



Colour	Approx. length metres	Product Ref.	Price
White	10	AQ21/W/10	£28.58
White	25	AQ21/W/25	£66.69
Brown	10	AQ21/B/10	£28.58
Brown	25	AQ21/B/25	£66.69

ROUTASEAL STRIP

High grade silicon rubber weatherseal. Will stand temperature of -30° to +200°C. Groove created by Ref. 31/10L. See page 67.



Colour	Approx. length metres	Product Ref.	Price
White	25	RS/W/25	£85.49
Brown	25	RS/B/25	£85.49