FULLY ADJUSTABLE TRADE

For precision fitting of locks into doors. For lock faceplates of lengths up to 250mm.

- Quick and easy to set-up as jig has engraved markings on underside to allow set-up for doors 35mm, 40mm, 44mm and 54mm thick.
- Length of the aperture in the jig can be adjusted from 30mm to 250mm.
- Engraved for 16mm and 19mm lock widths and 22.5mm and 25.4mm faceplate widths.
- Made from 12mm thick laminate with sliding phenolic plastic plates.
- Adjustable datum locking alloy clamping bar with clamping range from 30mm to 80mm.
- Can be used for routing the mortise for 16mm and 19mm lock bodies.
- The jig requires a plunge router with an 80mm plunge fitted with a 30mm guide bush with 10mm long spigot, 12mm diameter long reach cutter and two clamps.

LOCK/JIG/B £106.09

Size: 490mm x 409mm

INCLUDES:						
1	Х	Da	tum	cla	mp	bar

1	Х	Sliding	plate
5	v	Cotting	blooko

2	Х	Set	ting	b	loc	k

RECOMMENDED CUTTERS:	Product Ref.	Price

For faceplate or mortise			
Professional 12mmØ router cutter	3/75X1/2TC	£45.25	
CraftPro 12mmØ router cutter	C172DX1/2TC	£25.79	
115mm overall length. For up to 70mm deep mortise dependant on plunge of router and use of Unibase etc.			

For faceplate	Product Ref.	Price	
Professional 12mmØ router cutter	3/8LX1/4TC	£30.30	
CraftPro 12mmØ router cutter	C019AX1/4TC	£20.25	
70mm overall length. For mortise, deepening of mortise with auger bit required.			

OPTIONAL ACCESSORIE	S:	Product Ref.	Price
1. Guide bush 30mmØ with 10r	nm spigot	GB30/A	£9.80
2. Universal sub-base		UNIBASE	£20.51
3. Clamp (200mm jaw)		FC/200	£16.03
2 Certain makes and models of router will require a Unibase to	3.	1	

VIDEO

WATCH

trend-uk.com/video

COMPATIBILITY www.trend-uk.com/compatibility

> Setting gauge for doors to centre jig & set widths.

trena



Engraved on top for lock width & on underside to allow set-up for 35mm, 40mm, 44mm & 54mm door widths.

EURO CYLINDER LOCK JIG

This jig allows euro cylinder locks to be routed in doors.

- Routs out recess to suit Euro lock cylinder barrel size 33mm x 17mm/10mm.
- Sliding plate allows handle pitch to lock body adjustment from 45mm to 115mm.
- Jig is designed to give a 1mm clearance around the lock barrel.
- Allows 16mm diameter hole for handle spindle to be routed.
- Holes for use with Trend Snappy drill bit guide for marking handle lock plate at 40mm centres.
- Made from 12mm thick High Pressure Laminate for longer life.
- Reversible design with 57mm and 44mm backset.
- · Accessory sliding plates available for small oval and large oval bar
- Requires 12mm cutter and 20mm guide bush.

ECL/JIG £90.18 INCLUDES: 1 x Euro Lock

Size: 490mm x 409mm

1 x Euro Lock sliding plate 2 x Edge guides

Price

RECOMMENDED CUTTERS:	Product Ref.
1/0" Shank outtors	

	Professional 12mmØ router cutter	3/75X1/2TC	£45.25
	CraftPro 12mmØ router cutter	C172DX1/2TC	£25.79
_			
2.	1/4" Shank cutters	Product Ref.	Price
2.	1/4" Shank cutters Professional 12mmØ router cutter	Product Ref. 3/8LX1/4TC	Price £30.30

OPTIONAL ACCESSORIES:	Product Ref.	Price
3. Guide bush 20mm	GB20	£9.14
4. Small oval template accessory (2	7.8mm x 13mm bai	rrel)
	ECL/T/OCS	£16.92
5. Large oval template accessory (3	1.5mm x 17.5mm b	arrel)
	ECL/T/OCL	£16.92
5. Drill bit guide	SNAP/DBG/7	£10.48
7. Universal sub-base	UNIBASE	£20.51
3. Clamp (200mm jaw)	FC/200	£16.03

accept the guide bushes.





Certain makes and models of router will require a Unibase to accept the guide bushes



