

# LOCK/JIG Look-up Chart 1

v7.1

Brand	Levers	Type	Part No.	MORTISE		FACEPLATE		Template Choice
				Width (mm)	Length (mm)	Width (mm)	Length (mm)	
ALLBEES	5	DEAD	65MM	17	76.5	25.4	127	C4
ALLBEES	5	SASH	65MM	17.1	108.7	25.4	152.3	D7
ARROME	3	SASH	-	16	103	22.2	155.5	B1
CHUBB	5	DEAD	3G114	19	70	25.4	133	C5
CHUBB	5	DEAD	3U114	19	70	25.4	144.5	C6
CHUBB	5	DEAD	3U115	16	72	25.4	120.5	A3
CHUBB	5	SASH	3U74	19	110	25.4	176.5	D10
CHUBB	5	SASH	3U75	16	110	25.4	153	B7
CHUBB	7	SASH	3K77	19	108	25.4	153	D7
DOUGLAS	-	LATCH	-	N/A	N/A	25	57.5	11 UPPER
ERA	-	LATCH	-	N/A	N/A	26	56.5	11 LOWER
ERA	5	DEAD	201-31	16	88	25.4	133.5	E5
ERA	5	DEAD	201-32	16.3	87.5	26	134	E5
ERA	5	DEAD	202-32	15.8	109	26	162	B12
ERA	5	SASH	210-31	17	112.6	25.4	162	D12
ERA	5	SASH	310-31	18	111	25.4	162	D12
ERA	-	LATCH	-	23.5	23.5	25.1	57.1	15
ES	5	DEAD	-	18	80	25	127	C4
ES	-	LATCH	-	NA	NA	26	56.5	11 LOWER
ES	-	BED LATCH	-	16	102	22.5	155	B1
JEWSON	3	SASH	LISJK072	16	103	22.2	152	B2
JEWSON	5	SASH	LISJK043	16	108	25.4	156	B8
JEWSON	-	EURO	LISJK100	16	109	25	152.5	B7
KEYSAFE	5	DEAD	-	19	81	25	127.5	C4
LEGG	5	DEAD	P1645	17	77	25.4	133	C5
LEGG	5	SASH	P2645	18	109	25.4	165	D9
LEGG	-	LATCH	P3751	16	102	22.5	152.5	B2
PERKO	-	-	R2 Rect	-	-	25	51	14
SCREWFIX	5	SASH	5854	19	108	25.4	152.5	D7
SCREWFIX	5	DEAD	6559	19	77	25.4	121	C3
TRAVIS PERKINS	3	DEAD	P25	16	73	25	127.5	A4
TRAVIS PERKINS	3	SASH	P19	16	102.5	22.2	152	B2
TRAVIS PERKINS	3	SASH	P20	16	102.5	22.2	152	B2
TRAVIS PERKINS	5	DEAD	P27	16	73	25.4	127.5	A4
TRAVIS PERKINS	5	DEAD	P81	18	77	25.4	133.25	C5
TRAVIS PERKINS	5	SASH	P23	16	107	25.4	156	B8
TRAVIS PERKINS	5	SASH	P80	18	109	25.4	165	D9
TRAVIS PERKINS	3	SASH	P22 (802503)	14.7	98.4	22.3	152	B2
TRAVIS PERKINS	3	DEAD	P26 (802507)	15.4	73	25.2	127.4	A4
TRAVIS PERKINS	2	BATH	P29 (802510)	15.8	102.7	22.5	152	B2
UNION	-	EURO	L99	16	109	25.4	152.5	B7
UNION	3	DEAD	Y2177	14.8	70.4	25.8	120.8	A3
UNION	5	SASH	Y2201	14.8	108.2	25.6	152	B7
UNION	5	SASH	Y2234	18.9	108.4	25.4	176	D10
UNION	3	SASH	Y2277	14.9	108	25.4	152	B7
UNION	2	BATH	Y2294	14.2	101.7	22.4	152	B2
UNION	-	LATCH	2642	15	51	22	95.5	13F
UNION	3	LATCH	2677	14.5	70	25.5	120.5	A3
YALE	3	DEAD	PM322	16	70.4	25.6	121	B3
YALE	3	SASH	PM320	16	108.5	25.5	152.5	B7
YALE	5	SASH	PM560	18.8	108.7	25.5	176.5	D10
YALE	5	SASH	PM550	15.5	108.6	25.5	152.5	B7
YALE	5	DEAD	PM552	15	70.5	25.6	121.1	A3
YALE	2	SASH	PM246	16	101.7	22.4	152.3	B2
SPECIAL	-	-	-	-	-	26	110	16
SPECIAL	-	-	-	-	-	25.6	153	17
SPECIAL	-	-	-	-	-	25.6	60.2	18
SPECIAL	-	-	-	-	-	19	41	G
SPECIAL	-	-	-	-	-	37	59	G

# Template Selection Chart

## Faceplate Dimensions:

Metric	Imperial (Approx.)	Select Template	Not included with LOCK/JIG. Other sizes of template available. Please see website: <a href="http://www.trend-uk.com/downloads">www.trend-uk.com/downloads</a>
22 x 95.5 mm	7/8" x 3-3/4"	13	Ref. WP-LOCK/T/13
22.2 x 156 mm	7/8" x 6-1/8"	1	
22.5 x 152.5 mm	7/8" x 6"	2	
25 x 51mm	Perko® R2 Rectangle	14	Ref. WP-LOCK/T/14
25 x 57.5 mm	1" x 2-1/4"	11 UPPER	
25.1 x 57.1 mm	1" x 2-1/4"	15 LOWER	Ref. WP-LOCK/T/15
25.4 x 121 mm	1" x 4-3/4"	3	
25.4 x 127.5 mm	1" x 5"	4	
25.4 x 133.5 mm	1" x 5-1/4"	5	
25.4 x 145 mm	1" x 5-3/4"	6	
25.4 x 153 mm	1" x 6"	7	
25.4 x 156 mm	1" x 6-1/8"	8	
25.4 x 165.5 mm	1" x 6-1/2"	9	
25.4 x 177 mm	1" x 7"	10	
25.6 x 60.2mm	1" x 2-3/8"	18	Ref. WP-LOCK/T/18
25.6 x 153mm	1" x 6"	17	Ref. WP-LOCK/T/17 (RE)
25.6 x 162 mm	1" x 6-3/8"	12	
26 x 56.5 mm	1" x 2-1/4"	11 LOWER	
26 x 110mm	1" x 4-5/16"	16	Ref. WP-LOCK/T/16

## Mortise Lock Dimensions:

16 x 52*mm	5/8" x 2"	F	Ref. WP-LOCK/T/F
16 x 72*mm	5/8" x 2-7/8"	A	
16 x 90*mm	5/8" x 3-1/2"	E	Ref. WP-LOCK/T/E
16 x 107*mm	5/8" x 4-1/4"	B	
19 x 78*mm	3/4" x 3-1/8"	C	
19 x 109*mm	3/4" x 4-1/4"	D	
23.5 mmØ	15/16"Ø	15 UPPER	Ref. WP-LOCK/T/15
19 x 41mm	3/4" x 1-5/8"	G	Ref. WP-LOCK/T/G
24 x 57mm	15/16" x 2-1/4"		



**Before using faceplate template check template is exactly 18mm larger than the actual lock faceplate.**

\* These are maximum mortise lock case (body) lengths, unless radius ends are squared with a chisel. Actual length of mortise is 7mm longer. Smaller mortise locks can be accommodated depending on the position of their fixing screws.  
(RE) = Rounded ends.



### Trend Machinery & Cutting Tools Ltd.

Odhams Trading Estate St Albans Road  
Watford WD24 7TR England  
Tel: 0044(0)1923 249911  
Fax: 0044(0)1923 236879  
enquiry@trendm.co.uk  
[www.trend-uk.com](http://www.trend-uk.com)



RECYCLABLE



5 027654 522776 >

LEAF/LOCK v7.1