

## SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

Page: 1

Compilation date: 07/01/2015

Revision No: 5

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

**Product code:** CON125/250/750/A5

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC1: Adhesives, sealants.

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND

**Tel:** 0044 113 240 3456

**Fax:** 0044 113 240 0024

**Email:** sds@everbuild.co.uk

#### 1.4. Emergency telephone number

**Emergency tel:** 0044 113 240 3456 (office hours only)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CHIP:** F: R11; Xi: R36/38; N: R51/53; -: R66; -: R67

**Classification under CLP:** Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336

**Most important adverse effects:** Highly flammable. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

#### 2.2. Label elements

##### Label elements under CLP:

**Hazard statements:** H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

## SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

Page: 2

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

GHS09: Environmental



**Precautionary statements:** P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with soap and water.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312: Call a POISON CENTER or doctor if you feel unwell.  
P370+378: In case of fire: Use foam, dry powder or carbon dioxide for extinction.

### Label elements under CHIP:

**Hazard symbols:** Highly flammable.

Irritant.

Dangerous for the environment.



**Risk phrases:** R11: Highly flammable.  
R36/38: Irritating to eyes and skin.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S2: Keep out of the reach of children.  
S29: Do not empty into drains.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

[cont...]

# SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

Page: 3

## Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

EINECS	CAS	CHIP Classification	CLP Classification	Percent
265-151-9	64742-49-0	Xn: R65; F+: R12; Xi: R38; N: R51/53	Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	30-50%

ETHYL ACETATE - REACH registered number(s): 01-2119475103-46-XXXX

205-500-4	141-78-6	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%
-----------	----------	---------------------------------	--	--------

CYCLOHEXANE

203-806-2	110-82-7	F: R11; Xi: R38; Xn: R65; -: R67; N: R50/53	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	10-30%
-----------	----------	---	---	--------

ACETONE

200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---------------------------------	--	-------

ZINC OXIDE

-	1314-13-2	N: R50/53	Aquatic Chronic 1: H410; Aquatic Acute 1: H400	1-10%
---	-----------	-----------	--	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

[cont...]

# SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

Page: 4

## 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers. Do not use water jet.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### 6.4. Reference to other sections

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

**Suitable packaging:** Must only be kept in original packaging.

[cont...]

# SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

Page: 5

## 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**ETHYL ACETATE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	200 ppm	400 ppm	-	-

**CYCLOHEXANE**

UK	350 mg/m <sup>3</sup>	1050 mg/m <sup>3</sup>	-	-
----	-----------------------	------------------------	---	---

**ACETONE**

UK	1210 mg/m <sup>3</sup>	3620 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

**ZINC OXIDE**

UK	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	-	-
----	---------------------	----------------------	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Pale yellow

**Odour:** Aromatic

**Evaporation rate:** Fast

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Insoluble

**Also soluble in:** Most organic solvents.

**Viscosity:** Viscous

**Boiling point/range°C:** 66

**Flammability limits %: lower:** 0.6 vol%

**upper:** 11.5 vol%

[cont...]

# SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

Page: 6

Flash point°C: -29

Part.coeff. n-octanol/water: N/D

Autoflammability°C: 200°C

Relative density: 0.82

pH: N/A

## 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### ETHYL ACETATE

DERMAL	RBT	LD50	>20000	mg/kg
ORAL	RAT	LD50	6100	mg/kg
ORAL	RBT	LD50	4934	mg/kg
VAPOURS	RAT	4H LC50	29.3	ppmV

#### CYCLOHEXANE

ORL	MUS	LD50	813	mg/kg
ORL	RAT	LD50	12705	mg/kg

#### ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg

[cont...]

# SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

Page: 7

ORL	RAT	LD50	5800	mg/kg
-----	-----	------	------	-------

## ZINC OXIDE

IPR	RAT	LD50	240	mg/kg
ORL	MUS	LD50	7950	mg/kg

### Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

## Section 12: Ecological information

### 12.1. Toxicity

#### Hazardous ingredients:

##### ETHYL ACETATE

Daphnia magna	48H EC50	3090	mg/l
Pimephales promelas (Fat-head Minnow)	96H LC50	230	mg/l

##### ACETONE

BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l
--------------------------------	------	------	------

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

[cont...]

# SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

Page: 8

## 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Dispose of according to local or national legislation

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1133

### 14.2. UN proper shipping name

**Shipping name:** ADHESIVES

(LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),  
HYDROTREATED LIGHT)

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** II

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

### 14.6. Special precautions for user

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H224: Extremely flammable liquid and vapour.

[cont...]



## SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

Page: 9

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

R11: Highly flammable.

R12: Extremely flammable.

R36/38: Irritating to eyes and skin.

R36: Irritating to eyes.

R38: Irritating to skin.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

**Legend to abbreviations:** PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

[cont...]

## **SAFETY DATA SHEET**

STICK 2 ALL PURPOSE CONTACT ADHESIVE - ALL SIZES

**Page:** 10

OCC = ocular/corneal

PCP = physico-chemical properties

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.