

INDUSTRIAL SUPERGLUE HV

Page: 1

Compilation date: 11/2/2015

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: INDUSTRIAL SUPERGLUE HV

Product code: HV20, 50

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW ENGLAND

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

Email: sds@everbuild.co.uk

1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/37/38

Classification under CLP: STOT SE 3: H335; Eye Irrit. 2: H319; Skin Irrit. 2: H315; -: EUH202; -: EUH208

Most important adverse effects: Irritating to eyes, respiratory system and skin.

2.2. Label elements

Label elements under CLP:

Hazard statements: H315: Causes skin irritation.

H319: Causes serious eye irritation.H335: May cause respiratory irritation.

EUH202: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the

reach of children.

EUH208: Contains hydroquinone. May produce an allergic reaction.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark

INDUSTRIAL SUPERGLUE HV

Page: 2



Precautionary statements: P261: Avoid breathing vapours.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor if you feel unwell.

P264: Wash hands thoroughly after handling.

P321: Specific treatment (see section 4 on this label).

P332+313: If skin irritation occurs: Get medical advice.

P337+313: If eye irritation persists: Get medical advice.

P362: Take off contaminated clothing and wash before reuse.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P501: Dispose of contents to hazardous waste point.

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases: R36/37/38: Irritating to eyes, respiratory system and skin.

Safety phrases: S2: Keep out of the reach of children.

S46: If swallowed, seek medical advice immediately and show this container or label.

Precautionary phrases: Contains hydroquinone. May produce an allergic reaction.

2.3. Other hazards

Other hazards: Cyanoacrylate adhesives are instant bonding, almost single component adhesives that

bond almost all close fitting smooth surfaces in seconds

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

INDUSTRIAL SUPERGLUE HV

Page: 3

Hazardous ingredients:

ETHYL-2-CYANOACRYLATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
230-391-5	7085-85-0	Xi: R36/37/38	Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315	>90%

HYDROQUINONE

204-617-8	123-31-9	Xn: R40; Xn: R68; Xn: R22; Xi:	Carc. 2: H351; Muta. 2: H341; Acute	<1%
		R41; Sens.: R43; N: R50	Tox. 4: H302; Eye Dam. 1: H318; Skin	
			Sens. 1: H317; Aquatic Acute 1: H400	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. For persistant irritation seek medical advice.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

INDUSTRIAL SUPERGLUE HV

Page: 4

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Refer to section 13 of SDS for suitable method of

disposal.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Store in original

containers between +5 and +25°C. Storage outside these paramaters will dramatically

reduce shelf life and invalidates all product warranties.

Suitable packaging: Polyethylene.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ETHYL-2-CYANOACRYLATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	1.5 mg/m3	-	-

INDUSTRIAL SUPERGLUE HV

Page: 5

HYDROQUINONE

UK	0.5 mg/m3	-	-	-
----	-----------	---	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour

filter, type A: organic vapours (EN141).

Hand protection: Protective gloves. Change gloves regularly to prevent permeability.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Negligible

Solubility in water: Reacts with water.

Also soluble in: Acetone.

Viscosity: Viscous

Kinematic viscosity: 1200-1500

Viscosity test method: Cone and Plate @ 25°C

Boiling point/range°C: >149

Autoflammability°C: 45

Flash point°C: 80 - 93

Vapour pressure: <700mbar

Relative density: ~1.05 VOC g/l: <20

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

INDUSTRIAL SUPERGLUE HV

Page: 6

10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight. Moist air.

10.5. Incompatible materials

Materials to avoid: Water. Bases. Amines. Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHYL-2-CYANOACRYLATE

ORL	RAT	LD50	>5	ml/kg
-----	-----	------	----	-------

HYDROQUINONE

ORL	MUS	LD50	150	mg/kg
ORL	RAT	LD50	720	mg/kg
SCU	RAT	LDLO	300	mg/kg

Relevant effects for mixture:

Effect	Route	Basis	
Irritation	OPT INH DRM	Hazardous: calculated	

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

INDUSTRIAL SUPERGLUE HV

Page: 7

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company. Dispose of according to local or national legislation

Waste code number: 08 04 09

Disposal of packaging: Completely emptied packaging or practically empty packaging containing dried/cured

residues can be disposed of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3334

14.2. UN proper shipping name

Shipping name: AVIATION REGULATED LIQUID, N.O.S (ETHYL-2-CYANOACRYLATE)

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No **Marine pollutant:** No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

INDUSTRIAL SUPERGLUE HV

Page: 8

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH202: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the

reach of children.

EUH208: Contains < name of sensitising substance >. May produce an allergic reaction.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H341: Suspected of causing genetic defects <state route of exposure if it is conclusively

proven that no other routes of exposure cause the hazard>.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven

that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

R22: Harmful if swallowed.

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R50: Very toxic to aquatic organisms.

R68: Possible risk of irreversible effects.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

INDUSTRIAL SUPERGLUE HV

Page: 9

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.