

INDUSTRIAL SUPERGLUE GP

Page: 1

Compilation date: 08/12/2014

Revision No: 2

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: INDUSTRIAL SUPERGLUE GP

Product code: CYN20/50/100

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

### 1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

**LEEDS** 

**WEST YORKSHIRE** 

LS9OSW ENGLAND

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

Email: sds@everbuild.co.uk

## 1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

## **Section 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/37/38

Classification under CLP: STOT SE 3: H335; Eye Irrit. 2: H319; Skin Irrit. 2: H315; -: EUH202

Most important adverse effects: Irritating to eyes, respiratory system and skin.

### 2.2. Label elements

# Label elements under CLP:

Hazard statements: H315: Causes skin irritation.

H319: Causes serious eye irritation.H335: May cause respiratory irritation.

EUH202: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the

reach of children.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



#### INDUSTRIAL SUPERGLUE GP

Page: 2

Precautionary statements: P261: Avoid breathing fumes.

P264: Wash contaminated skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P271: Use only outdoors or in a well-ventilated area.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.
P312: Call a POISON CENTER or doctor if you feel unwell.

P332+313: If skin irritation occurs: Get medical advice.

P337+313: If eye irritation persists: Get medical attention.

P362: Take off contaminated clothing and wash before reuse.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P501: Dispose of contents/container to hazardous waste.

Label elements under CHIP:

Hazard symbols: Irritant.



**Risk phrases:** R36/37/38: Irritating to eyes, respiratory system and skin.

Safety phrases: S2: Keep out of the reach of children.

S46: If swallowed, seek medical advice immediately and show this container or label.

#### 2.3. Other hazards

Other hazards: Cyanoacrylate adhesives are instant bonding, almost single component adhesives that

bond almost all close fitting smooth surfaces in seconds

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

## 3.2. Mixtures

# Hazardous ingredients:

#### ETHYL-2-CYANOACRYLATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
230-391-5	7085-85-0	Xi: R36/37/38	Eye Irrit. 2: H319; STOT SE 3: H335;	>90%
			Skin Irrit. 2: H315	

INDUSTRIAL SUPERGLUE GP

Page: 3

### Non-classified ingredients:

#### **HYDROQUINONE**

EINECS	CAS	CHIP Classification	CLP Classification	Percent
204-617-8	123-31-9	Xn: R40; Xn: R68; Xn: R22; Xi:	Carc. 2: H351; Muta. 2: H341; Acute	<1%
		R41; Sens.: R43; N: R50	Tox. 4: H302; Eye Dam. 1: H318; Skin	
			Sens. 1: H317; Aquatic Acute 1: H400	

### Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

**Delayed** / **immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

#### INDUSTRIAL SUPERGLUE GP

Page: 4

contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

## 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Store in original

containers between +5 and +25°C. Storage outside these paramaters will dramatically

Respirable dust

reduce shelf life and invalidates all product warranties.

15 min. STEL

Suitable packaging: Polyethylene.

# 7.3. Specific end use(s)

### Section 8: Exposure controls/personal protection

### 8.1. Control parameters

### Hazardous ingredients:

#### **ETHYL-2-CYANOACRYLATE**

### Workplace exposure limits:

•	
8 hour TWA	15 min. STEL

### **DNEL/PNEC Values**

State

UK

DNEL / PNEC No data available.

8 hour TWA

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration

1.5 mg/m3

is above OES or if ventilation is poor Self-contained breathing apparatus must be

available in case of emergency.

Hand protection: Protective gloves.

INDUSTRIAL SUPERGLUE GP

Page: 5

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Perceptible odour

Solubility in water: Reacts with water.

Also soluble in: Acetone.

Viscosity: Viscous

Kinematic viscosity: 75-125

Viscosity test method: Cone and Plate @ 25°C

Boiling point/range°C: >149

Flash point°C: 80-93.4

Autoflammability°C: 450

Vapour pressure: <700mbar

Relative density: 1.05 pH: Not applicable.

VOC g/I: <20

#### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight. Moist air.

# 10.5. Incompatible materials

Materials to avoid: Water. Alcohols. Amines. Strong oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

INDUSTRIAL SUPERGLUE GP

Page: 6

### 11.1. Information on toxicological effects

#### **Hazardous ingredients:**

#### **ETHYL-2-CYANOACRYLATE**

ORL	RAT	LD50	>5	ml/ka
UKL	KAI	LDSU	/3	IIII/Kg

#### Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT INH DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### **Section 12: Ecological information**

### 12.1. Toxicity

Ecotoxicity values: No data available.

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

### Section 13: Disposal considerations

# 13.1. Waste treatment methods

Disposal operations: Dispose of according to local or national legislation Transfer to a suitable container and

arrange for collection by specialised disposal company.

Waste code number: 08 04 09

**NB:** The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

[cont...]

### INDUSTRIAL SUPERGLUE GP

Page: 7

### **Section 14: Transport information**

#### 14.1. UN number

UN number: UN3334

### 14.2. UN proper shipping name

Shipping name: AVIATION REGULATED LIQUID, N.O.S (ETHYL-2-CYANOACRYLATE)

### 14.3. Transport hazard class(es)

Transport class: 9

### 14.4. Packing group

Packing group: III

### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

### 14.6. Special precautions for user

### Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

## **Section 16: Other information**

# Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH202: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the

reach of children.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H341: Suspected of causing genetic defects <state route of exposure if it is conclusively

proven that no other routes of exposure cause the hazard>.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven

that no other routes of exposure cause the hazard>.

#### INDUSTRIAL SUPERGLUE GP

Page: 8

H400: Very toxic to aquatic life.

R22: Harmful if swallowed.

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R50: Very toxic to aquatic organisms.

R68: Possible risk of irreversible effects.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.