

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** LUMBERJACK 550 PARQUET ADHESIVE

**Product code:** LJ550

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Adhesive for parquet flooring

### 1.3. Details of the supplier of the safety data sheet

**Company name:** EVERBUILD BUILDING PRODUCTS LTD  
SITE 41, KNOWSTHORPE WAY  
CROSS GREEN INDUSTRIAL ESTATE  
LEEDS  
WEST YORKSHIRE  
LS9OSW  
ENGLAND

**Tel:** 0044 113 240 3456

**Fax:** 0044 113 240 0024

**Email:** sds@everbuild.co.uk

### 1.4. Emergency telephone number

**Emergency tel:** 0044 113 240 3456 (office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Skin Sens. 1: H317; -: EUH208

**Classification under CHIP:** This product has no classification under CHIP.

### 2.2. Label elements

#### Label elements under CLP:

**Hazard statements:** EUH208: Contains n-(2-aminoethyl)-3-aminopropyltrimethoxysilane, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.  
H317: May cause an allergic skin reaction.

**Signal words:** Warning

**Hazard pictograms:** GHS07: Exclamation mark



# SAFETY DATA SHEET

## LUMBERJACK 550 PARQUET ADHESIVE

Page: 2

**Precautionary statements:** P272: Contaminated work clothing should not be allowed out of the workplace.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of soap and water.  
P321: Specific treatment (see information on this label).  
P333+313: If skin irritation or rash occurs: Get medical advice/attention.  
P363: Wash contaminated clothing before reuse.  
P501: Dispose of contents/container to local authority waste disposal.

### Label elements under CHIP:

**Hazard symbols:** No significant hazard.

**Precautionary phrases:** Contains n-(2-aminoethyl)-3-aminopropyltrimethoxysilane, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### TRIMETHOXY VINYLSILANE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
220-449-8	2768-02-7	-: R10; Xn: R20	Acute Tox. 4: H332; Flam. Liq. 3: H226	1-10%

##### N-(2-AMINOETHYL)-3-AMINOPROPYLTRIMETHOXYSILANE

217-164-6	1760-24-3	Xi: R41; Sens.: R43; Xn: R20; N: R51/53	Eye Dam. 1: H318; Aquatic Chronic 2: H411; Acute Tox. 4: H332; Skin Sens. 1: H317	<1%
-----------	-----------	---	---	-----

##### BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE.

-	-	Sens.: R43; N: R50/53	Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	<1%
---	---	-----------------------	--	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.  
**Eye contact:** Bathe the eye with running water for 15 minutes.  
**Ingestion:** Wash out mouth with water.  
**Inhalation:** Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

[cont...]

**SAFETY DATA SHEET**  
LUMBERJACK 550 PARQUET ADHESIVE

Page: 3

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** In combustion emits toxic fumes.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear protective clothing to prevent contact with skin and eyes. Wear self-contained breathing apparatus.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Allow to solidify and remove by mechanical means.

**6.4. Reference to other sections**

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Ensure there is sufficient ventilation of the area.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in cool, well ventilated area.

**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Workplace exposure limits:** No data available.

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

[cont...]

**SAFETY DATA SHEET**  
LUMBERJACK 550 PARQUET ADHESIVE

Page: 4

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses.

**Skin protection:** Protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Paste

**Colour:** Yellow-green

**Odour:** Barely perceptible odour

**Solubility in water:** Not miscible

**Viscosity:** Highly viscous

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE.**

ORAL	RAT	LD50	3230	mg/kg
------	-----	------	------	-------

[cont...]

# SAFETY DATA SHEET

LUMBERJACK 550 PARQUET ADHESIVE

Page: 5

**Toxicity values:** No data available.

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

#### TRIMETHOXY VINYLSILANE

Daphnia magna	-	21D NOEC 28	mg/l
Daphnia magna	48H EC50	169	mg/l
GREEN ALGA (Selenastrum capricornutum)	-	72H NOEC 25	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H IC50	210	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	191	mg/l

#### N-(2-AMINOETHYL)-3-AMINOPROPYLTRIMETHOXYSILANE

Scenedesmus Subspicatus	72H EC50	126	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	597	mg/l

#### BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE.

DESMODESMUS SUBSPICATUS	72H ErC50	1.68	mg/l
Daphnia magna	24H EC50	20	mg/l
FISH	96H LC50	0.97	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	7.9	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Not biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

## Section 13: Disposal considerations

[cont...]

**SAFETY DATA SHEET**  
LUMBERJACK 550 PARQUET ADHESIVE

Page: 6

**13.1. Waste treatment methods**

**Disposal operations:** Dispose of according to local or national legislation

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H332: Harmful if inhaled.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

R10: Flammable.

R20: Harmful by inhalation.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Legend to abbreviations:** PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

[cont...]

## SAFETY DATA SHEET

LUMBERJACK 550 PARQUET ADHESIVE

Page: 7

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = physico-chemical properties

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.