



BS5534:2014 Annex A Zone suitability

Zone suitability applies only for underlays in applications where a well-sealed ceiling is present, ridge height is not greater than 15m, roof pitch is between 12.5° and 70°, site altitude is not greater than 100m, and no significant site topography is present. Other applications might require underlays with greater wind uplift resistance and it is advisable to seek professional advice. Zones 3 & 4 apply to Northern Ireland.

Batten Gauge	Lap Fixing Method	Zone Suitability
≤345mm	Lap Fixing Batten*	1-5

≤250mm	Lap Fixing Batten*	1-5
--------	--------------------	-----

≤100mm	Lap Fixing Batten*	1-5
--------	--------------------	-----

≤345mm	Lap Fixing Batten*	1-3
--------	--------------------	-----

≤250mm	Lap Fixing Batten*	1-5
--------	--------------------	-----

≤100mm	Lap Fixing Batten*	1-5
--------	--------------------	-----

≤345mm	Lap Fixing Batten*	1-2
--------	--------------------	-----

≤250mm	Lap Fixing Batten*	1-5
--------	--------------------	-----

≤100mm	Lap Fixing Batten*	1-5
--------	--------------------	-----

≤345mm	Lap Fixing Batten*	N/A
--------	--------------------	-----

≤250mm	Lap Fixing Batten*	1-5
--------	--------------------	-----

≤100mm	Lap Fixing Batten*	1-5
--------	--------------------	-----



Pro
170gsm



Vent3
135gsm



Classic
115gsm



Light
95gsm



* Denotes either taped or battened laps.