



INSTRUCTIONS FOR

2/3-LEVEL COMPOSITE TROLLEY HEAVY-DUTY

MODEL NO: **CX204, CX205**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instructions

1. SAFETY

- ✓ Only use on firm, level, unobstructed surfaces which are capable of supporting the trolley plus load.
- ✗ **DO NOT** overload.
- ✓ Always load evenly with the centre of gravity of the load as near the centre as possible.
- ✓ Apply the brakes before commencing work.
- ✗ **DO NOT** stand/ride on the trolley, or allow others to do so.
- ✓ Replace or repair damaged parts. Use only recommended parts. Unauthorised parts may be dangerous and will invalidate the warranty.
- ☐ **WARNING!** Failure to comply with these instructions may result in loss of load, damage to the stand or other property and/or personal injury.
- ☐ **WARNING!** The warnings, cautions and instructions discussed in this instruction manual cannot cover all possible conditions and situations that may occur. It must be understood that common sense and caution are factors which cannot be built into this product, but must be applied by the operator.

2. INTRODUCTION

Heavy-duty garage and workshop trolley with 80/60kg capacity per shelf. Manufactured from extra-strong impact resistant plastic. Ideal for a variety of applications. One piece moulded shelves prevents spills transferring to lower levels. Fitted with four swivel castor wheels, two of which have brakes.

3. SPECIFICATION

Model No.....	CX204 (fig.1).....	CX205 (fig.2)
Overall (W x D x H).....	810 x 460 x 785mm.....	810 x 460 x 785mm
Shelf Size.....	675 x 410 x 95mm.....	675 x 410 x 95mm
Capacity.....	80kg/Level.....	60kg/Level
Total load Capacity.....	160Kg.....	180kg

4. ASSEMBLY

- 4.1. Unpack all parts.
- 4.2. Attach castors to bottom tray by pushing them into the corners of tray ensure tray is the correct way up. Use rubber mallet if required.
- 4.3. Apply brakes. Push four uprights into corners of bottom tray.
- 4.4. Align middle tray sockets with four uprights push into place. (CX205 Only)
- 4.5. Push four uprights into corners of middle tray. (CX205 Only)
- 4.6. Align top tray sockets with four uprights push into place.



fig.1



fig.2

Parts support is available for this product. To obtain a parts listing and/or diagram, please log on to www.sealey.co.uk, email sales@sealey.co.uk or telephone 01284 757500.



Environmental Protection

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment.

When the product becomes completely unserviceable and requires disposal, drain off any fluids (if applicable) into approved containers and dispose of the product and the fluids according to local regulations.

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

IMPORTANT: No liability is accepted for incorrect use of this product.

WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim.



Sole UK Distributor, Sealey Group.
Kempson Way, Suffolk Business Park,
Bury St. Edmunds, Suffolk.
IP32 7AR



01284 757500



01284 703534



www.sealey.co.uk



sales@sealey.co.uk