

PRODUCT DATA

Thinner 7301

DESCRIPTION

Special thinner for Rust-Oleum 7300 CombiColor® product range.

MAIN PROPERTIES

Optimal solvent combination for 7300-product range. Good thinning properties.

RECOMMENDED USES

Thinner for 7300 CombiColor topcoats and primers.

TECHNICAL DATA

Colour: Colourless
Density: 0,82 g/cm³
Flashpoint: > 45°C
VOC-content: 820 g/l

DIRECTION FOR USE

Brush: Use up to max. 10 vol. %

Roller: Use up to max. 10 vol. %

Air-atomised spray: Use 10 to max. 25 vol. %

Remark: For air-atomised spraying of CombiColor Hammertone topcoats use the special thinner 7302

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.
Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S
11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.
Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu