

# S AY B Р S A 0 N I 0 Ш

Rust-Oleum Netherlands B.V. Braak 1, 4704 RJ P.O. Box 138, 4700 AC Roosendaal, The Netherlands T +31 (0)165 593 636 F +31 (0)165 593 600 info@rust-oleum.eu www.rust-oleum.eu www.x flechsprays.com

N.V. Martin Mathys S.A. Kolonbergstraat 23 3545 Zelem Halen, Belgium T +32 (0)13 460 200 F +32 (0)13 460 201 info@rust-oleum.eu www.rust-oleum.eu

www.x ftechsprays.com

Rust-Oleum France S.A.S 11, Rue Jules Verne, B.P. 60039 95322 St-Leu-la-Forêt Codex

T +33 (0)1 30 40 00 44 F +33 (0)1 30 40 99 80 Info@rust-oleum.eu www.rust-oleum.eu www.x ftechsprays.com

Rust-Oleum UK Ltd. Rotterdam House 116 Quayside Newcastle, NE1 3DY United Kingdom T +44 (0)2476 717 329 F +44 (0)2476 718 930 Info@rust-oleum.eu www.rust-oleum.eu www.x ftechsprays.com

## An RPM Company

#### PRODUCT DATA 1613 - X1 MULTI-PURPOSE WELD SPRAY

#### DESCRIPTION

1613 X1 eXcellent Multi-Purpose Weld spray is a high quality, technical spray that effectively prevents the adhesion of weld spatter to metal surfaces. It protects welded materials from

X1 eXcellent Multi-Purpose Weld spray provides eXcellent performance. It withstands extreme temperatures, will resist chemical attacks and has excellent thermal conductivity.

#### **MAIN PROPERTIES**

Protecting properties - non corrosive - non silicon - contains no chlorinated solvents - low toxicity.

#### **RECOMMENDED USES**

Work pieces, welding equipment. Suitable for MIG. ARC or TIG welding.

### **TECHNICAL DATA**

Appearance: Transparent Colour: Transparent Operating temperature: -5°C to 200°C

#### **DIRECTION FOR USE**

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply.

#### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

# SHELLIFE / STORAGE CONDITIONS

3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Page: 1 / 1 - Ver. 00 PDS 1613-gb Edition: 08-12-11

The information contained herein is given in good faith. However, since application conditions are beyond our control, Rust-Oleum Netherlands B.V. cannot assume responsibility for any risks or liabilities which may result from the use of these products. The company reserves the right to modify data without prior notice.